

# MC74HC1G08

## Single 2-Input AND Gate

The MC74HC1G08 is a high speed CMOS 2-input AND gate fabricated with silicon gate CMOS technology.

The internal circuit is composed of multiple stages, including a buffer output which provides high noise immunity and stable output.

The MC74HC1G08 output drive current is 1/2 compared to MC74HC series.

### Features

- High Speed:  $t_{PD} = 7 \text{ ns}$  (Typ) at  $V_{CC} = 5 \text{ V}$
- Low Power Dissipation:  $I_{CC} = 1 \mu\text{A}$  (Max) at  $T_A = 25^\circ\text{C}$
- High Noise Immunity
- Balanced Propagation Delays ( $t_{PLH} = t_{PHL}$ )
- Symmetrical Output Impedance ( $I_{OH} = I_{OL} = 2 \text{ mA}$ )
- Chip Complexity: < 100 FETs
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant




Figure 1. Pinout




Figure 2. Logic Symbol

| PIN ASSIGNMENT |                 |
|----------------|-----------------|
| 1              | B               |
| 2              | A               |
| 3              | GND             |
| 4              | Y               |
| 5              | V <sub>CC</sub> |





ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)




SC-88A  
DF SUFFIX  
CASE 419A

### MARKING DIAGRAMS



TSOP-5  
DT SUFFIX  
CASE 483




XX = Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.



SC-74A  
DBV SUFFIX  
CASE 318BQ



XXX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### FUNCTION TABLE

| Inputs |   | Output |
|--------|---|--------|
| A      | B | Y      |
| L      | L | L      |
| L      | H | L      |
| H      | L | L      |
| H      | H | H      |

### ORDERING INFORMATION

See detailed ordering, marking and shipping information in the package dimensions section on page 6 of this data

# MC74HC1G08

## MAXIMUM RATINGS

| Symbol                | Parameter                                                                                          | Value                           | Unit |
|-----------------------|----------------------------------------------------------------------------------------------------|---------------------------------|------|
| $V_{CC}$              | DC Supply Voltage<br>SC-88A (NLV), TSOP-5<br>SC-88A, SC-74A                                        | - 0.5 to + 7.0<br>- 0.5 to +6.5 | V    |
| $V_{IN}$              | DC Input Voltage                                                                                   | - 0.5 to $V_{CC} + 0.5$         | V    |
| $V_{OUT}$             | DC Output Voltage                                                                                  | - 0.5 to $V_{CC} + 0.5$         | V    |
| $I_{IK}$              | DC Input Diode Current                                                                             | $\pm 20$                        | mA   |
| $I_{OK}$              | DC Output Diode Current                                                                            | $\pm 20$                        | mA   |
| $I_{OUT}$             | DC Output Source/Sink Current                                                                      | $\pm 12.5$                      | mA   |
| $I_{CC}$ or $I_{GND}$ | DC Supply Current per Supply Pin or Ground Pin                                                     | $\pm 25$                        | mA   |
| $T_{STG}$             | Storage Temperature Range                                                                          | -65 to + 150                    | °C   |
| $T_L$                 | Lead Temperature, 1 mm from Case for 10 Seconds                                                    | 260                             | °C   |
| $T_J$                 | Junction Temperature Under Bias                                                                    | + 150                           | °C   |
| $\theta_{JA}$         | Thermal Resistance (Note 1)<br>SC70-5/SC-88A/SOT-353<br>SOT23-5/TSOP-5/SC59-5<br>SC-74A            | 659<br>555<br>555               | °C/W |
| $P_D$                 | Power Dissipation in Still Air at 85°C<br>SC70-5/SC-88A/SOT-353<br>SOT23-5/TSOP-5/SC59-5<br>SC-74A | 190<br>225<br>225               | mW   |
| MSL                   | Moisture Sensitivity                                                                               | Level 1                         |      |
| $F_R$                 | Flammability Rating<br>Oxygen Index: 28 to 34                                                      | UL 94 V-0 @ 0.125 in            |      |
| $V_{ESD}$             | ESD Withstand Voltage (Note 2)<br>Human Body Model<br>Charged Device Model                         | 2000<br>1000                    | V    |
| $I_{LATCHUP}$         | Latchup Performance (Note 3)<br>SC-88A (NLV), SOT-23<br>SC-88A, SC-74A                             | $\pm 500$<br>$\pm 100$          | mA   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 20 ounce copper trace with no air flow.
2. HBM tested to ANSI/ESDA/JEDEC JS-001-2017. CDM tested to JESD22-C101-F. JEDEC recommends that ESD qualification to EIA/JESD22-A115A (Machine Model) be discontinued per JEDEC/JEP172A.
3. Tested to EIA/JESD78 Class II.

# MC74HC1G08

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter                   | Min                                | Max             | Unit |      |
|---------------------------------|-----------------------------|------------------------------------|-----------------|------|------|
| V <sub>CC</sub>                 | DC Supply Voltage           | 2.0                                | 6.0             | V    |      |
| V <sub>IN</sub>                 | DC Input Voltage            | 0.0                                | V <sub>CC</sub> | V    |      |
| V <sub>OUT</sub>                | DC Output Voltage           | 0.0                                | V <sub>CC</sub> | V    |      |
| T <sub>A</sub>                  | Operating Temperature Range | − 55                               | + 125           | °C   |      |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time    | SC-88A (NLV), TSOP-5               |                 |      | ns/V |
|                                 |                             | V <sub>CC</sub> = 2.0 V            | 0               | 1000 |      |
|                                 |                             | V <sub>CC</sub> = 3.0 V            | 0               | 600  |      |
|                                 |                             | V <sub>CC</sub> = 4.5 V            | 0               | 500  |      |
|                                 |                             | V <sub>CC</sub> = 6.0 V            | 0               | 400  |      |
|                                 | Input Rise and Fall Time    | SC-88A, SC-74A                     |                 |      |      |
|                                 |                             | V <sub>CC</sub> = 1.65 V to 1.95 V | 0               | 20   |      |
|                                 |                             | V <sub>CC</sub> = 2.3 V to 2.7 V   | 0               | 20   |      |
|                                 |                             | V <sub>CC</sub> = 3.0 V to 3.6 V   | 0               | 10   |      |
|                                 |                             | V <sub>CC</sub> = 4.5 V to 6.0 V   | 0               | 5    |      |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS

| Symbol   | Parameter                 | Test Conditions                                                                       | $V_{CC}$<br>(V) | $T_A = 25^\circ\text{C}$ |      |                | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ |           | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ |           | Unit          |
|----------|---------------------------|---------------------------------------------------------------------------------------|-----------------|--------------------------|------|----------------|----------------------------------------------------|-----------|-----------------------------------------------------|-----------|---------------|
|          |                           |                                                                                       |                 | Min                      | Typ  | Max            | Min                                                | Max       | Min                                                 | Max       |               |
| $V_{IH}$ | High-Level Input Voltage  |                                                                                       | 2.0             | 1.5                      | –    | –              | 1.5                                                | –         | 1.5                                                 | –         | V             |
|          |                           |                                                                                       | 3.0             | 2.1                      | –    | –              | 2.1                                                | –         | 2.1                                                 | –         |               |
|          |                           |                                                                                       | 4.5             | 3.15                     | –    | –              | 3.15                                               | –         | 3.15                                                | –         |               |
|          |                           |                                                                                       | 6.0             | 4.20                     | –    | –              | 4.20                                               | –         | 4.20                                                | –         |               |
| $V_{IL}$ | Low-Level Input Voltage   |                                                                                       | 2.0             | –                        | –    | 0.5            | –                                                  | 0.5       | –                                                   | 0.5       | V             |
|          |                           |                                                                                       | 3.0             | –                        | –    | 0.9            | –                                                  | 0.9       | –                                                   | 0.9       |               |
|          |                           |                                                                                       | 4.5             | –                        | –    | 1.35           | –                                                  | 1.35      | –                                                   | 1.35      |               |
|          |                           |                                                                                       | 6.0             | –                        | –    | 1.80           | –                                                  | 1.80      | –                                                   | 1.80      |               |
| $V_{OH}$ | High-Level Output Voltage | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$I_{OH} = -20\text{ }\mu\text{A}$                    | 2.0             | 1.9                      | 2.0  | –              | 1.9                                                | –         | 1.9                                                 | –         | V             |
|          |                           |                                                                                       | 3.0             | 2.9                      | 3.0  | –              | 2.9                                                | –         | 2.9                                                 | –         |               |
|          |                           |                                                                                       | 4.5             | 4.4                      | 4.5  | –              | 4.4                                                | –         | 4.4                                                 | –         |               |
|          |                           |                                                                                       | 6.0             | 5.9                      | 6.0  | –              | 5.9                                                | –         | 5.9                                                 | –         |               |
|          |                           | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$I_{OH} = -2\text{ mA}$<br>$I_{OH} = -2.6\text{ mA}$ | 4.5             | 4.18                     | 4.31 | –              | 4.13                                               | –         | 4.08                                                | –         |               |
|          |                           |                                                                                       | 6.0             | 5.68                     | 5.80 | –              | 5.63                                               | –         | 5.58                                                | –         |               |
| $V_{OL}$ | Low-Level Output Voltage  | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$I_{OL} = 20\text{ }\mu\text{A}$                     | 2.0             | –                        | 0.0  | 0.1            | –                                                  | 0.1       | –                                                   | 0.1       | V             |
|          |                           |                                                                                       | 3.0             | –                        | 0.0  | 0.1            | –                                                  | 0.1       | –                                                   | 0.1       |               |
|          |                           |                                                                                       | 4.5             | –                        | 0.0  | 0.1            | –                                                  | 0.1       | –                                                   | 0.1       |               |
|          |                           |                                                                                       | 6.0             | –                        | 0.0  | 0.1            | –                                                  | 0.1       | –                                                   | 0.1       |               |
|          |                           | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$I_{OL} = 2\text{ mA}$<br>$I_{OL} = 2.6\text{ mA}$   | 4.5             | –                        | 0.17 | 0.26           | –                                                  | 0.33      | –                                                   | 0.40      |               |
|          |                           |                                                                                       | 6.0             | –                        | 0.18 | 0.26           | –                                                  | 0.33      | –                                                   | 0.40      |               |
| $I_{IN}$ | Input Leakage Current     | $V_{IN} = 6.0\text{ V}$ or GND                                                        | 6.0             | –                        | –    | $\pm 0.1$<br>* | –                                                  | $\pm 1.0$ | –                                                   | $\pm 1.0$ | $\mu\text{A}$ |
| $I_{CC}$ | Quiescent Supply Current  | $V_{IN} = V_{CC}$ or GND                                                              | 6.0             | –                        | –    | 1.0            | –                                                  | 10        | –                                                   | 40        | $\mu\text{A}$ |

\*Guaranteed by design.


# MC74HC1G08

## AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 6.0$ ns)

| Symbol                                 | Parameter                               | Test Conditions                                  | T <sub>A</sub> = 25°C |     |     | –40°C ≤ T <sub>A</sub> ≤ 85°C |     | –55°C ≤ T <sub>A</sub> ≤ 125°C |     | Unit |
|----------------------------------------|-----------------------------------------|--------------------------------------------------|-----------------------|-----|-----|-------------------------------|-----|--------------------------------|-----|------|
|                                        |                                         |                                                  | Min                   | Typ | Max | Min                           | Max | Min                            | Max |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Propagation Delay,<br>Input A or B to Y | V <sub>CC</sub> = 5.0 V   C <sub>L</sub> = 15 pF | –                     | 3.5 | 15  | –                             | 20  | –                              | 25  | ns   |
|                                        |                                         | V <sub>CC</sub> = 2.0 V   C <sub>L</sub> = 50 pF | –                     | 20  | 100 | –                             | 125 | –                              | 155 |      |
|                                        |                                         | V <sub>CC</sub> = 3.0 V                          | –                     | 11  | 27  | –                             | 35  | –                              | 90  |      |
|                                        |                                         | V <sub>CC</sub> = 4.5 V                          | –                     | 8   | 20  | –                             | 25  | –                              | 35  |      |
|                                        |                                         | V <sub>CC</sub> = 6.0 V                          | –                     | 7   | 17  | –                             | 21  | –                              | 26  |      |
| t <sub>TLH</sub> ,<br>t <sub>THL</sub> | Output Transition<br>Time               | V <sub>CC</sub> = 5.0 V   C <sub>L</sub> = 15 pF | –                     | 3   | 10  | –                             | 15  | –                              | 20  | ns   |
|                                        |                                         | V <sub>CC</sub> = 2.0 V   C <sub>L</sub> = 50 pF | –                     | 25  | 125 | –                             | 155 | –                              | 200 |      |
|                                        |                                         | V <sub>CC</sub> = 3.0 V                          | –                     | 16  | 35  | –                             | 45  | –                              | 60  |      |
|                                        |                                         | V <sub>CC</sub> = 4.5 V                          | –                     | 11  | 25  | –                             | 31  | –                              | 38  |      |
|                                        |                                         | V <sub>CC</sub> = 6.0 V                          | –                     | 9   | 21  | –                             | 26  | –                              | 32  |      |
| C <sub>IN</sub>                        | Input Capacitance                       |                                                  | –                     | 5   | 10  | –                             | 10  | –                              | 10  | pF   |
| C <sub>PD</sub>                        | Power Dissipation Capacitance (Note 4)  | Typical @ 25°C, V <sub>CC</sub> = 5.0 V          |                       |     |     |                               |     |                                |     | pF   |
|                                        |                                         | 10                                               |                       |     |     |                               |     |                                |     |      |

4.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$ .  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .

# MC74HC1G08



\* $C_L$  includes probe and jig capacitance  
 $R_T$  is  $Z_{OUT}$  of pulse generator (typically 50  $\Omega$ )  
 $f = 1$  MHz

Figure 3. Test Circuit




Figure 4. Switching Waveforms

| Test                         | Switch Position | $C_L$ , pF                   | $R_L$ , $\Omega$ |
|------------------------------|-----------------|------------------------------|------------------|
| $t_{PLH} / t_{PHL}$          | Open            | See AC Characteristics Table | X                |
| $t_{TLH} / t_{THL}$ (Note 5) | Open            |                              | X                |
| $t_{PLZ} / t_{PZL}$          | $V_{CC}$        |                              | 1 k              |
| $t_{PHZ} / t_{PZH}$          | GND             |                              | 1 k              |

X - Don't Care

| $V_{CC}$ , V | $V_{mi}$ , V | $V_{mo}$ , V          |                                      | $V_L$ , V                        | $V_H$ , V                        | $V_Y$ , V |
|--------------|--------------|-----------------------|--------------------------------------|----------------------------------|----------------------------------|-----------|
|              |              | $t_{PLH}, t_{PHL}$    | $t_{PZL}, t_{PLZ}, t_{PZH}, t_{PHZ}$ |                                  |                                  |           |
| 3.0 to 3.6   | $V_{CC}/2$   | $(V_{OH} - V_{OL})/2$ | $V_{CC}/2$                           | $V_{OL} + 0.1 (V_{OH} - V_{OL})$ | $V_{OL} + 0.9 (V_{OH} - V_{OL})$ | 0.3       |
| 4.5 to 5.5   | $V_{CC}/2$   | $(V_{OH} - V_{OL})/2$ | $V_{CC}/2$                           | $V_{OL} + 0.1 (V_{OH} - V_{OL})$ | $V_{OL} + 0.9 (V_{OH} - V_{OL})$ | 0.3       |

5.  $t_{TLH}$  and  $t_{THL}$  are measured from 10% to 90% of  $(V_{OH} - V_{OL})$ , and 90% to 10% of  $(V_{OH} - V_{OL})$ , respectively.

# MC74HC1G08

## ORDERING INFORMATION


| Device                               | Packages | Specific Device Code | Pin 1 Orientation<br>(See below) | Shipping <sup>†</sup> |
|--------------------------------------|----------|----------------------|----------------------------------|-----------------------|
| MC74HC1G08DFT1G                      | SC-88A   | H2                   | Q2                               | 3000 / Tape & Reel    |
| NLVHC1G08DFT1G*                      | SC-88A   | H2                   | Q2                               | 3000 / Tape & Reel    |
| MC74HC1G08DFT2G                      | SC-88A   | H2                   | Q4                               | 3000 / Tape & Reel    |
| NLVHC1G08DFT2G*                      | SC-88A   | H2                   | Q4                               | 3000 / Tape & Reel    |
| MC74HC1G08DTT1G                      | TSOP-5   | H2                   | Q4                               | 3000 / Tape & Reel    |
| NLVHC1G08DTT1G*                      | TSOP-5   | H2R                  | Q4                               | 3000 / Tape & Reel    |
| MC74HC1G08DBVT1G<br>(In Development) | SC-74A   | TBD                  | Q4                               | 3000 / Tape & Reel    |

<sup>†</sup>For complete information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

## Pin 1 Orientation in Tape and Reel


Direction of Feed



# MC74HC1G08

## PACKAGE DIMENSIONS


**SC-88A (SC-70-5/SOT-353)**  
CASE 419A-02  
ISSUE L



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
  4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |


## SOLDER FOOTPRINT



# MC74HC1G08

## PACKAGE DIMENSIONS

### TSOP-5 CASE 483 ISSUE M




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE, DIMENSION A.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 2.85        | 3.15 |
| B   | 1.35        | 1.65 |
| C   | 0.90        | 1.10 |
| D   | 0.25        | 0.50 |
| G   | 0.95 BSC    |      |
| H   | 0.01        | 0.10 |
| J   | 0.10        | 0.26 |
| K   | 0.20        | 0.60 |
| M   | 0°          | 10°  |
| S   | 2.50        | 3.00 |

#### SOLDERING FOOTPRINT\*






\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HC1G08

## PACKAGE DIMENSIONS

### SC-74A CASE 318BQ ISSUE B




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 0.90        | 1.10 |
| A1  | 0.01        | 0.10 |
| b   | 0.25        | 0.50 |
| c   | 0.10        | 0.26 |
| D   | 2.85        | 3.15 |
| E   | 2.50        | 3.00 |
| E1  | 1.35        | 1.65 |
| e   | 0.95 BSC    |      |
| L   | 0.20        | 0.60 |
| M   | 0°          | 10°  |

### RECOMMENDED SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9