N-Channel Power MOSFET

800V, 6A, 0.95Ω

FEATURES

- Super-Junction technology
- High performance due to small figure-of-merit
- High ruggedness performance
- High commutation performance
- Pb-free plating
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition

KEY PERFORMANCE PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
V_{DS}	800	V
$R_{DS(on)}$ (max)	0.95	Ω
Q_g	19.6	nC

Pb-Free RoHS COMPLIANT HALOGEN FREE

APPLICATION

- Power Supply
- Lighting

TO-251 (IPAK)



TO-252 (DPAK)





Notes: MSL 3 (Moisture Sensitivity Level) for TO-252 (D-PAK) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	800	V
Gate-Source Voltage		V_{GS}	±30	V
Continuous Drain Current (Note 1)	T_C = 25°C	I_D	6	A
	T_C = 100°C		3.8	A
Pulsed Drain Current (Note 2)		I_{DM}	18	A
Total Power Dissipation @ T_C = 25°C		P_{DTOT}	110	W
Single Pulsed Avalanche Energy (Note 3)		E_{AS}	121	mJ
Single Pulsed Avalanche Current (Note 3)		I_{AS}	2.2	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	1.14	°C/W
Junction to Ambient Thermal Resistance	$R_{\Theta JA}$	62	°C/W

Notes: $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins. $R_{\Theta JA}$ is guaranteed by design while $R_{\Theta CA}$ is determined by the user's board design. $R_{\Theta JA}$ shown below for single device operation on FR-4 PCB with minimum recommended footprint in still air.

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static (Note 4)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	BV_{DSS}	800	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	$V_{GS(TH)}$	2	--	4	V
Gate Body Leakage	V_{GS} = ±30V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 800V, V_{GS} = 0V	I_{DSS}	--	--	1	μA
Drain-Source On-State Resistance	V_{GS} = 10V, I_D = 3A	$R_{DS(on)}$	--	0.8	0.95	Ω
Dynamic (Note 5)						
Total Gate Charge	V_{DS} = 380V, I_D = 6A, V_{GS} = 10V	Q_g	--	19.6	--	nC
Gate-Source Charge		Q_{gs}	--	3.5	--	
Gate-Drain Charge		Q_{gd}	--	9.7	--	
Input Capacitance	V_{DS} = 100V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	691	--	pF
Output Capacitance		C_{oss}	--	63	--	
Gate Resistance	F = 1MHz, open drain	R_g	--	3.4	--	Ω
Switching (Note 6)						
Turn-On Delay Time	V_{DD} = 380V, R_{GEN} = 25Ω, I_D = 6A, V_{GS} = 10V,	$t_{d(on)}$	--	23	--	ns
Turn-On Rise Time		t_r	--	12	--	
Turn-Off Delay Time		$t_{d(off)}$	--	57	--	
Turn-Off Fall Time		t_f	--	11	--	
Source-Drain Diode (Note 4)						
Forward On Voltage	I_S = 6A, V_{GS} = 0V	V_{SD}	--	--	1.4	V
Reverse Recovery Time	V_R = 100V, I_S = 6A dI_F/dt = 100A/μs	t_{rr}	--	249	--	ns
Reverse Recovery Charge		Q_{rr}	--	2.6	--	μC

Notes:

1. Current limited by package.
2. Pulse width limited by the maximum junction temperature.
3. L = 50mH, I_{AS} = 2.2A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C
4. Pulse test: PW ≤ 300μs, duty cycle ≤ 2%.
5. For DESIGN AID ONLY, not subject to production testing.
6. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSM80N950CH C5G	TO-251 (IPAK)	75pcs / Tube
TSM80N950CP ROG	TO-252 (DPAK)	2,500pcs / 13” Reel

CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Current vs. Voltage



CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)

Capacitance vs. Drain-Source Voltage



BV_{DSS} vs. Junction Temperature



Maximum Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-251 (IPAK)



MARKING DIAGRAM



Y = Year Code

M = Month Code for Halogen Free Product

O =Jan	**P** =Feb	**Q** =Mar	**R** =Apr
S =May	**T** =Jun	**U** =Jul	**V** =Aug
W =Sep	**X** =Oct	**Y** =Nov	**Z** =Dec

L = Lot Code (1~9, A~Z)

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-252 (DPAK)



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



Y = Year Code

M = Month Code for Halogen Free Product

O	=Jan	**P**	=Feb	**Q**	=Mar	**R**	=Apr
S	=May	**T**	=Jun	**U**	=Jul	**V**	=Aug
W	=Sep	**X**	=Oct	**Y**	=Nov	**Z**	=Dec

L = Lot Code (1~9, A~Z)

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9