

## PRODUCT PREVIEW

The VE8910, VE8910-HV, VE8901, VE8911, VE8911-HV and VE8921 chipsets are highly integrated, cost-effective FXS, FXO and FXS + FXO chipsets that are optimized for residential VoIP access devices. These chipsets implement a complete BORSCHT functionality by providing the necessary voice interface functions to connect to, and power, one or more telephones and an isolated Direct Access Arrangement (DAA) for connection to the PSTN. The VE890 Series chipsets significantly increase design flexibility, improve system performance, and reduce BOM costs. These chipsets are supported by the Zarlink VoicePath™ API-II™ (VP API-II), which enables designers to offer a single hardware design that is software programmable for worldwide markets.



| VE890 Series |         |             |
|--------------|---------|-------------|
| Chipset      | OPN     | Description |
| 1FXS         |         |             |
| VE8910       | Le89116 | SLAC        |
|              | Le89810 | SLIC        |
| VE8910-HV    | Le89136 | SLAC        |
|              | Le89830 | SLIC        |
| 1FXO         |         |             |
| VE8901       | Le89010 | OLAC        |
|              | Le89900 | DAA         |
| 1FXS + 1FXO  |         |             |
| VE8911       | Le89316 | SOLAC       |
|              | Le89810 | SLIC        |
|              | Le89900 | DAA         |
| VE8911-HV    | Le89336 | SOLAC       |
|              | Le89830 | SLIC        |
|              | Le89900 | DAA         |
| 2FXS + 1FXO  |         |             |
| VE8921       | Le89316 | SOLAC       |
|              | Le89116 | SLAC        |
|              | Le89810 | SLIC        |
|              | Le89810 | SLIC        |
|              | Le89900 | DAA         |

### Features

- ➔ Highly integrated, low-cost 1FXS, 1FXO and 1FXS + 1FXO chipset optimized for residential VoIP gateways
- ➔ Full worldwide programmability, a single hardware design can be configured via software for use in all worldwide markets
- ➔ FXS channel performs all the standard BORSCHT functions
- ➔ Integrated power management minimizes power consumption, making the VE890 Series suitable for battery backed applications
- ➔ Full support for wideband audio with 16 kHz sampling
- ➔ FXO channel performs all PSTN interface functions with software programmable parameters
- ➔ Best in class DAA performance in common mode noise rejection and RF immunity
- ➔ Unique adaptive hybrid balance feature for impedance matching reduces local echo and improves voice quality
- ➔ DAA isolation using no-cost PCB capacitors reduces RBOM cost
- ➔ Integrated VoicePath™ API-II Software implements all FXS & FXO functions, significantly reducing development time and providing one common interface for FXS and FXO functions
- ➔ Comprehensive line sensing and line monitoring with VeriVoice™ Test Suite software—provides complete GR-909/TIA-1063 diagnostics, loop test and supervision functions
- ➔ Direct FXO to FXS voice path eliminates processor buffering overhead
- ➔ Package offerings support board stuffing options for popular voice configurations—1FXS, 1FXO, 2FXS, 1FXS + 1FXO and 2FXS + 1FXO

### Applications

- ➔ Residential and SOHO VoIP CPE, such as ADSL2+/VDSL2 Integrated Access Devices (IADs)
- ➔ Residential VoIP Gateways and Routers

## APPLICATION


Zarlink provides a world-class suite of development tools to facilitate the integration of Legerity voice solutions into end-user applications and to significantly reduce design time.

The VoicePath API-II™ (VP API-II) is a set of 'C' code used to abstract devices from application code while providing functions for controlling, supervising, packet exchanging, and testing a set of subscriber lines. It is application and OS independent in that it requires no memory (only memory required is provided by application space) and supports reentrancy. It has been used in Linux (application and kernel space), VxWorks, and non-OS architec-


tures. The API-II is common across all Legerity voice solutions so applications written for one device are the same for other devices. It integrates seamlessly with the Zarlink's Legerity Software Development Kit (SDK) Tools so your development time is significantly reduced.

The VeriVoice™ Test Suite is a subscriber line software package for VoIP equipment, providing the market's most cost effective and reliable solution for VoIP line test while at the same time minimizing the cost of ownership for service providers. Self-test available with VeriVoice Professional.

### VE8910 or VE8910-HV Chipset—1 Channel FXS



### VE8911 or VE8911-HV Chipset—1 Channel FXS + 1 Channel FXO



Information relating to products and services furnished herein by Zarlink Semiconductor Inc. or its subsidiaries is believed to be reliable. The products, their specifications, services and other information appearing in this publication are subject to change by Zarlink without notice.

ZARLINK, ZL, and the Zarlink logo are trademarks of Zarlink Semiconductor Inc.

© 2010, Zarlink Semiconductor Inc. All Rights Reserved. Part Number 10ZS024



[www.ZARLINK.com](http://www.ZARLINK.com)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9