

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0465567345](#)
Status: **Active**
Description: 1.27mm (.050") by 1.27mm (.050") Pitch SEARAY* Slim Plug, 100 Circuits, 3.50mm (.137") Unmated Height, 4 Rows, With Pegs, Solder Charge™ Lead-free

Documents:

3D Model	Product Specification PS-45970-001 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification


CSA	LR19980
UL	E29179

General

Product Family	PCB Headers
Series	46556
Application	Board-to-Board
Product Name	SEARAY*

Physical

Breakaway	No
Circuits (Loaded)	100
Circuits (maximum)	100
Circuits Detail	100
Color - Resin	Black
Durability (mating cycles max)	100
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	Yes
Keying to Mating Part	None
Lock to Mating Part	None
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	4
Orientation	Vertical
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface (in)	0.050 In
Pitch - Mating Interface (mm)	1.27 mm
Pitch - Term. Interface (in)	0.050 In
Pitch - Term. Interface (mm)	1.27 mm
Plating min: Mating (µin)	30
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Robotic Placement	Pick and Place Cap
Shrouded	No
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-55°C to +125°C
Termination Interface: Style	Surface Mount



Series

image - Reference only

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series

[46556Series](#)

Mates With

[46557](#) SEARAY* Slim Receptacles

Electrical

Current - Maximum per Contact	1A
Voltage - Maximum	240V AC

Solder Process Data

Duration at Max. Process Temperature (seconds)	20
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	3
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Product Specification	PS-45970-001
Sales Drawing	SD-46556-001

*SEARAY is a trademark of Samtec, Inc.

This document was generated on 03/24/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

6

5

4



3

2

1

NOTES:

1. MATERIALS: HOUSING: LCP, UL94V-0, BLACK
CONTACTS: COPPER ALLOY
SOLDER CHARGE: SEE CHART
2. FINISH: ALL OPTIONS - SELECT GOLD IN CONTACT AREA: 30 MI MIN
OPTIONS 2.0 & 2.5: SELECT GOLD FLASH IN TAIL, 7 MI MIN
OPTIONS 3.0 THRU 7.0: SELECT TIN IN TAIL, 100 MI MIN
ALL OPTIONS - OVER NICKEL
3. PRODUCT SPECIFICATION: PS-45970-001
4. PACKAGING SPECIFICATION: PK-45970-002
5. MATES WITH SEARAY RECPT ASSEMBLY 46557
6. APPLICATION SPECIFICATION: AS-45970-001
7. COSMETIC SPECIFICATION: PS-45499-002 CLASS B
8. PART STATUS: CONTACT MOLEX






LEAD CODE:
1 = TIN
2 = TIN / LEAD

SEE TABLE

ACROSS ALL
SOLDER
CHARGES

DIM P
REF ONLY
MATED STACK
HEIGHT
(MILLIMETERS)



POSITIONS	DIM G	
10	.696	.006
15	.946	.006
20	1.196	.006
25	1.446	.006
30	1.696	.006
35	1.946	.006
40	2.196	.006
45	2.446	.009
50	2.696	.009

UPDATED NOTE 2

EC NO: UCP2010-2270
DRWN: TREGORI 2010/03/05
CHKD: JCOMERC I 2007/05/17
APPR: JCOMERC I 2010/03/05

DESCRIPTION

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
INCH ONLY

DRAWN BY TREGORI
DATE 2007/05/17
CHECKED BY JCOMERC I
DATE 2007/05/17
APPROVED BY JCOMERC I
DATE 2010/03/05

MATERIAL NO.

SEE CHART

SIZE
A

SCALE
4:1

DESIGN UNITS
INCH

THIRD ANGLE
PROJECTION

SEARAY SLIM
PLUG ASSEMBLY
.050 PITCH

MOLEX INCORPORATED

DOCUMENT NO.

SD-46556-001

SHEET NO.

1 OF 4

6		5		4		3		2		1	
DIM P	2.0 MM	3.0 MM	3.5 MM	2.5 MM	4.5 MM	5.0 MM	7.0 MM				
DIM R: HOUSING HEIGHT:	.221	.260	.280	.241	.319	.339	.418				
POSITIONS	MATERIAL NO	MATERIAL NO	MATERIAL NO	MATERIAL NO	MATERIAL NO	MATERIAL NO	MATERIAL NO				
10	46556-1145	46556-1245	46556-1345	46556-1445	46556-1545	46556-1645	46556-1745				
20	46556-2145	46556-2245	46556-2345	46556-2445	46556-2545	46556-2645	46556-2745				
30	46556-3145	46556-3245	46556-3345	46556-3445	46556-3545	46556-3645	46556-3745				
40	46556-4145	46556-4245	46556-4345	46556-4445	46556-4545	46556-4645	46556-4745				
50	46556-5145	46556-5245	46556-5345	46556-5445	46556-5545	46556-5645	46556-5745				
15	46556-6145	46556-6245	46556-6345	46556-6445	46556-6545	46556-6645	46556-6745				
25	46556-7145	46556-7245	46556-7345	46556-7445	46556-7545	46556-7645	46556-7745				
35	46556-8145	46556-8245	46556-8345	46556-8445	46556-8545	46556-8645	46556-8745				
45	46556-9145	46556-9245	46556-9345	46556-9445	46556-9545	46556-9645	46556-974				
NOTES: 1. THIS SHEET CONTAINS THE FOLLOWING OPTIONS SOLDER CHARGE: TIN											
SEE SHEET 1 EC NO: UCP2010-2270 DRWN: TGREGORI 2010/03/05 CHKD: JCOMERCI 2007/05/17 APPR: JCOMERCI 2010/03/05 DESCRIPTION REV GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .005 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DIMENSION STYLE INCH ONLY DRAWN BY DATE TGREGORI 2007/05/17 CHECKED BY DATE JCOMERCI 2007/05/17 APPROVED BY DATE JCOMERCI 2010/03/05 MATERIAL NO. SEE CHART SIZE A SCALE 1:1 DESIGN UNITS INCH THIRD ANGLE PROJECTION TITLE SEARAY SLIM PLUG ASSEMBLY .050 PITCH MOLEX INCORPORATED DOCUMENT NO. SD-46556-001 SHEET NO. 3 OF 4 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
tb_frame_A_P_AM_T Rev. E 2006/04/15		5		4		3		2		1	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9