



## Features

- Compact design to save board space - 0805 footprint
- Small size results in very fast time to react to fault events
- Symmetrical design
- Low profile
- RoHS compliant\* and halogen free\*\*
- Agency recognition: <sup>®</sup>

## Applications

- USB port protection - USB 2.0, 3.0 & OTG
- HDMI 1.4 Source protection
- PC motherboards - Plug and Play protection
- Mobile phones - Battery and port protection
- PDAs / digital cameras
- Game console port protection

# MF-PSMF Series - PTC Resettable Fuses

### Electrical Characteristics

| Model       | V max. Volts | I max. Amps | I <sub>hold</sub> | I <sub>trip</sub> | Resistance        |                    | Max. Time To Trip |                  | Tripped Power Dissipation |
|-------------|--------------|-------------|-------------------|-------------------|-------------------|--------------------|-------------------|------------------|---------------------------|
|             |              |             | Amperes at 23 °C  |                   | Ohms at 23 °C     |                    | Amperes at 23 °C  | Seconds at 23 °C | Watts at 23 °C            |
|             |              |             | Hold              | Trip              | R <sub>Min.</sub> | R <sub>1Max.</sub> |                   |                  | Typ.                      |
| MF-PSMF010X | 15           | 40          | 0.10              | 0.30              | 1.0               | 7.5                | 0.5               | 1.5              | 0.5                       |
| MF-PSMF020X | 9            | 40          | 0.20              | 0.50              | 0.65              | 3.5                | 8.00              | 0.02             | 0.5                       |
| MF-PSMF035X | 6            | 40          | 0.35              | 0.75              | 0.250             | 1.200              | 8.00              | 0.10             | 0.5                       |
| MF-PSMF050X | 6            | 40          | 0.50              | 1.00              | 0.150             | 0.900              | 8.00              | 0.10             | 0.5                       |
| MF-PSMF075X | 6            | 40          | 0.75              | 1.50              | 0.090             | 0.350              | 8.00              | 0.20             | 0.6                       |
| MF-PSMF110X | 6            | 40          | 1.10              | 2.20              | 0.060             | 0.210              | 8.00              | 0.30             | 0.6                       |

### Environmental Characteristics

|   |  |
|---|--|
| Operating Temperature.....                                | -40 °C to +85 °C   |
| Maximum Device Surface Temperature in Tripped State ..... | 125 °C   |
| Passive Aging .....                                       | +85 °C, 1000 hours..... ±5 % typical resistance change           |
| Humidity Aging .....                                      | +85 °C, 85 % R.H. 1000 hours..... ±5 % typical resistance change |
| Thermal Shock .....                                       | +85 °C to -40 °C, 20 times..... ±10 % typical resistance change  |
| Solvent Resistance.....                                   | MIL-STD-202, Method 215..... No change                           |
| Vibration .....   | MIL-STD-883C, Method 2007.1,..... No change<br>Condition A       |

### Test Procedures And Requirements For Model MF-PSMF Series

| Test                 | Test Conditions                                       | Accept/Reject Criteria                   |
|----------------------|---|--|
| Visual/Mech.....     | Verify dimensions and materials.....                  | Per MF physical description              |
| Resistance.....      | In still air @ 23 °C.....                             | R <sub>min</sub> ≤ R ≤ R <sub>1max</sub> |
| Time to Trip.....    | At specified current, V <sub>max</sub> , 23 °C.....   | T ≤ max. time to trip (seconds)          |
| Hold Current.....    | 30 min. at I <sub>hold</sub> .....                    | No trip                                  |
| Trip Cycle Life..... | V <sub>max</sub> , I <sub>max</sub> , 100 cycles..... | No arcing or burning                     |
| Trip Endurance.....  | V <sub>max</sub> , 48 hours.....                      | No arcing or burning                     |
| Solderability.....   | ANSI/J-STD-002.....                                   | 95 % min. coverage                       |

UL File Number ..... E174545  
<http://www.ul.com/> Follow link to Certifications, then UL File No., enter E174545

### Thermal Derating Chart - I<sub>hold</sub> (Amps)

| Model       | Ambient Operating Temperature |        |      |       |       |       |       |       |       |
|-------------|-------------------------------|--------|------|-------|-------|-------|-------|-------|-------|
|             | -40 °C                        | -20 °C | 0 °C | 23 °C | 40 °C | 50 °C | 60 °C | 70 °C | 85 °C |
| MF-PSMF010X | 0.15                          | 0.13   | 0.12 | 0.10  | 0.09  | 0.08  | 0.07  | 0.06  | 0.05  |
| MF-PSMF020X | 0.28                          | 0.25   | 0.23 | 0.20  | 0.17  | 0.14  | 0.12  | 0.10  | 0.07  |
| MF-PSMF035X | 0.47                          | 0.44   | 0.39 | 0.35  | 0.30  | 0.27  | 0.24  | 0.20  | 0.14  |
| MF-PSMF050X | 0.68                          | 0.62   | 0.55 | 0.50  | 0.40  | 0.37  | 0.33  | 0.29  | 0.23  |
| MF-PSMF075X | 1.00                          | 0.90   | 0.79 | 0.75  | 0.63  | 0.57  | 0.53  | 0.42  | 0.35  |
| MF-PSMF110X | 1.45                          | 1.35   | 1.20 | 1.10  | 0.92  | 0.84  | 0.75  | 0.65  | 0.52  |

\*RoHS Directive 2002/95/EC Jan 27, 2003 including Annex.

\*\*To be considered halogen free, each homogenous material can have a maximum concentration of 900 ppm of either bromine or chlorine.

Specifications are subject to change without notice.

Customers should verify actual device performance in their specific applications.

## Additional Applications

- Automotive electronic control modules

# MF-PSMF Series - PTC Resettable Fuses


# BOURNS®

### Product Dimensions

| Model       | A                      |                        | B                      |                        | C                      |                        | D                      |
|-------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
|             | Min.                   | Max.                   | Min.                   | Max.                   | Min.                   | Max.                   | Min.                   |
| MF-PSMF010X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.48}{(0.019)}$ | $\frac{0.85}{(0.033)}$ | $\frac{0.20}{(0.008)}$ |
| MF-PSMF020X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.48}{(0.019)}$ | $\frac{0.85}{(0.033)}$ | $\frac{0.20}{(0.008)}$ |
| MF-PSMF035X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.48}{(0.019)}$ | $\frac{0.85}{(0.033)}$ | $\frac{0.20}{(0.008)}$ |
| MF-PSMF050X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.48}{(0.019)}$ | $\frac{0.85}{(0.033)}$ | $\frac{0.20}{(0.008)}$ |
| MF-PSMF075X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.75}{(0.030)}$ | $\frac{1.25}{(0.049)}$ | $\frac{0.20}{(0.008)}$ |
| MF-PSMF110X | $\frac{2.00}{(0.079)}$ | $\frac{2.30}{(0.091)}$ | $\frac{1.20}{(0.047)}$ | $\frac{1.50}{(0.059)}$ | $\frac{0.75}{(0.030)}$ | $\frac{1.25}{(0.049)}$ | $\frac{0.20}{(0.008)}$ |

Packaging: 3000 pcs. per reel.

DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$



### Terminal material:

Nickel/gold plated.


### Termination pad solderability:

Standard Au finish:  
Meets ANSI/J-STD-002 Category 2.

### Recommended Storage:

40 °C max./70 % RH max.

### Typical Time to Trip at 23 °C



The Time to Trip curves represent typical performance of a device in a simulated application environment. Actual performance in specific customer applications may differ from these values due to the influence of other variables.


### How to Order

**MF - PSMF 050 X - 2**

Multifuse® Product  
Designator  
Series  
PSMF = 0805 Surface Mount Component  
Hold Current, I<sub>hold</sub>  
010-110 (0.10 - 1.10 Amps)  
Multifuse® freeXpansion™ Design  
Packaging  
Packaged per EIA 481-1  
-2 = Tape and Reel

### Typical Part Marking

Represents total content. Layout may vary.



BIWEEKLY DATE CODE WILL APPEAR ON THE PACKAGING LABEL:  
WEEK 1 AND 2 = A  
WEEK 51 AND 52 = Z

Specifications are subject to change without notice.  
Customers should verify actual device performance in their specific applications.

## Solder Reflow Recommendations



### Notes:

- MF-NSMF models cannot be wave soldered. Please contact Bourns for hand soldering recommendations.
- If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.
- Compatible with Pb and Pb-free solder reflow profiles.
- Excess solder may cause a short circuit, especially during hand soldering. Please refer to the Multifuse® Polymer PTC Soldering Recommendation guidelines.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9