FAIRCHILD SEMICONDUCTOR™

October 1986
Revised March 2000

# DM74AS280
# 9-Bit Parity Generator/Checker

## General Description

These universal, 9-bit parity generators/checkers utilize advanced Schottky high performance circuitry and feature odd/even outputs to facilitate operation of either odd or even parity applications. The word length capability is easily expanded by cascading.

The DM74AS280 can be used to upgrade the performance of most systems utilizing the '180 parity generator/checker. Although the DM74AS280 is implemented without expander inputs, the corresponding function is provided by the availability of an input at pin 4 and no internal connection at pin 3. This permits the DM74AS280 to be substituted for the '180 in existing designs to produce identical function even if DM74AS280s are mixed with existing '180s.

## Features


- Generates either odd or even parity for nine data lines
- Inputs are buffered to lower the drive requirements
- Can be used to upgrade existing systems using MSI parity circuits
- Cascadable for N-bits
- Advanced oxide-isolated, ion-implanted Schottky TTL process
- Switching specifications at 50 pF
- Switching specifications guaranteed over full temperature and $V_{CC}$ range

## Ordering Code:

| Order Number | Package Number | Package Description |
|---|---|---|
| DM74AS280M | M14A | 14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow |
| DM74AS280N | N14A | 14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

## Connection Diagram





## Function Table

| Number of Inputs (A thru I) that are HIGH | Outputs | |
|---|---|---|
| | ∑Even | ∑Odd |
| 0, 2, 4, 6, 8 | H | L |
| 1, 3, 5, 7, 9 | L | H |

L = LOW State
H = HIGH State

© 2000 Fairchild Semiconductor Corporation 

## Logic Diagram



## Absolute Maximum Ratings(Note 1)

| | |
|---|---|
| Supply Voltage | 7V |
| Input Voltage | 7V |
| Operating Free Air Temperature Range | 0°C to +70°C |
| Storage Temperature Range | −65°C to +150°C |
| Typical $\theta_{JA}$ | |
| N Package | 77.0°C/W |
| M Package | 108.0°C/W |

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

## Recommended Operating Conditions

| Symbol | Parameter | Min | Typ | Max | Units |
|---|---|---|---|---|---|
| $V_{CC}$ | Supply Voltage | 4.5 | 5 | 5.5 | V |
| $V_{IH}$ | HIGH Level Input Voltage | 2 | | | V |
| $V_{IL}$ | LOW Level Input Voltage | | | 0.8 | V |
| $I_{OH}$ | HIGH Level Output Current | | | −2 | mA |
| $I_{OL}$ | LOW Level Output Current | | | 20 | mA |
| $T_A$ | Free-Air Operating Temperature | 0 | | 70 | °C |

## Electrical Characteristics

Over recommended free-air temperature range. All typical values are measured at $V_{CC}$ = 5V, $T_A$ = 25°C.

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| $V_{IK}$ | Input Clamp Voltage | $V_{CC}$ = 4.5V, $I_I$ = −18 mA | | | −1.2 | V |
| $V_{OH}$ | HIGH Level Output Voltage | $I_{OH}$ = −2 mA, $V_{CC}$ = 4.5V to 5.5V | $V_{CC}$ − 2 | | | V |
| $V_{OL}$ | LOW Level Output Voltage | $V_{CC}$ = 4.5V, $I_{OL}$ = Max | | 0.35 | 0.5 | V |
| $I_I$ | Input Current @ Max Input Voltage | $V_{CC}$ = 5.5V, $V_{IH}$ = 7V | | | 0.1 | mA |
| $I_{IH}$ | HIGH Level Input Current | $V_{CC}$ = 5.5V, $V_{IH}$ = 2.7V | | | 20 | μA |
| $I_{IL}$ | LOW Level Input Current | $V_{CC}$ = 5.5V, $V_{IL}$ = 0.4V | | | −0.5 | mA |
| $I_O$ | Output Drive Current | $V_{CC}$ = 5.5V, $V_O$ = 2.25V | −30 | | −112 | mA |
| $I_{CC}$ | Supply Current | $V_{CC}$ = 5.5V | | 25 | 40 | mA |

## Switching Characteristics

over recommended operating free air temperature range

| Symbol | Parameter | Conditions | From | To | Min | Max | Units |
|---|---|---|---|---|---|---|---|
| $t_{PLH}$ | Propagation Delay Time, LOW-to-HIGH Level Output | $V_{CC}$ = 4.5V to 5.5V, $C_L$ = 50 pF, $R_L$ = 500Ω | Data | ΣEven | 3 | 12 | ns |
| $t_{PHL}$ | Propagation Delay Time, HIGH-to-LOW Level Output | | | | 3 | 11 | ns |
| $t_{PLH}$ | Propagation Delay Time, LOW-to-HIGH Level Output | | Data | ΣOdd | 3 | 12 | ns |
| $t_{PHL}$ | Propagation Delay Time, HIGH-to-LOW Level Output | | | | 3 | 11.5 | ns |

## Typical Applications

Three DM74AS280s can be used to implement a 25-line parity generator/checker.

As an alternative, the outputs of two or three parity generators/checkers can be decoded with a 2-input (AS86) or 3-input (S135) exclusive-OR gate for 18 or 27-line parity applications.

Longer word lengths can be implemented by cascading DM74AS280s. As shown in Figure 2, parity can be generated for word lengths up to 81 bits.





**FIGURE 1. 25-Line Parity/Generator Checker**







**FIGURE 2. 81-Line Parity/Generator Checker**

## Physical Dimensions inches (millimeters) unless otherwise noted




**14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow**
**Package Number M14A**

## Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




**14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide**
**Package Number N14A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**www.fairchildsemi.com**

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9