

NBSG72A

2.5V/3.3V SiGe Differential 2 x 2 Crosspoint Switch with Output Level Select

The NBSG72A is a high-bandwidth fully differential 2 X 2 crosspoint switch with Output Level Select (OLS) capabilities. This is a part of the GigaComm™ family of high performance Silicon Germanium products. The device is housed in a low profile 3 X 3 mm 16-pin QFN package.

Differential inputs incorporate internal 50 Ω termination resistors and accept NECL (Negative ECL), PECL (Positive ECL), LVCMOS/LVTTL, CML, or LVDS. The OLS input is used to program the peak-to-peak output amplitude between 0 mV and 800 mV in five discrete steps. The SELECT inputs are single-ended and can be driven with either LVECL or LVCMOS/LVTTL input levels.

Features

- Maximum Input Clock Frequency > 7 GHz Typical
- Maximum Input Data Rate > 7 Gb/s Typical
- 200 ps Typical Propagation Delay (OLS = FLOAT)
- 55/45 ps Typical Rise/Fall Times (OLS = FLOAT)
- Selectable Swing PECL Output with Operating Range:
 $V_{CC} = 2.375\text{ V to }3.465\text{ V}$ with $V_{EE} = 0\text{ V}$
- Selectable Swing NECL Output with NECL Inputs with Operating Range: $V_{CC} = 0\text{ V}$ with $V_{EE} = -2.375\text{ V to }-3.465\text{ V}$
- Selectable Output Levels (0 mV, 200 mV, 400 mV, 600 mV or 800 mV Peak-to-Peak Output)
- 50 Ω Internal Input Termination Resistors
- Single-Ended LVECL or LVCMOS/LVTTL Select Inputs (SELA, SELB)
- Pb-Free Packages are Available




ON Semiconductor®

<http://onsemi.com>

MARKING DIAGRAM*



QFN-16
MN SUFFIX
CASE 485G



A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb-Free Package
(Note: Microdot may be in either location)

*For additional marking information, refer to Application Note AND8002/D.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 13 of this data sheet.

NBSG72A




Figure 1. QFN-16 Pinout (Top View)

Table 1. PIN DESCRIPTION

| Pin No. | Name | I/O | Description |
|---------|-----------------|--------------------------------------|---|
| 1 | VTD0 | - | Common Internal 50 Ω Termination Pin for D0 and $\overline{D0}$ Input. See Table 4. (Note 1) |
| 2 | $\overline{D0}$ | LVDS, CML, ECL, LVTTTL, LVCMOS Input | Inverted Differential Input 0. |
| 3 | D0 | LVDS, CML, ECL, LVTTTL, LVCMOS Input | Noninverted Differential Input 0. |
| 4 | SELA | LVECL, LVCMOS Input | Select Logic Input A. Internal 75 k Ω Pulldown to V_{EE} . |
| 5 | V_{EE} | - | Negative Supply. All V_{EE} Pins must be Externally Connected to Power Supply to Guarantee Proper Operation. |
| 6 | $\overline{D1}$ | LVDS, CML, ECL, LVTTTL, LVCMOS Input | Inverted Differential Input 1. |
| 7 | D1 | LVDS, CML, ECL, LVTTTL, LVCMOS Input | Noninverted Differential Input 1. |
| 8 | VTD1 | - | Common Internal 50 Ω Termination Pin for D1 and $\overline{D1}$ Input. See Table 4. (Note 1) |
| 9 | SELB | LVECL, LVCMOS Input | Select Logic Input B. Internal 75 k Ω Pulldown to V_{EE} . |
| 10 | Q1 | RSECL Output | Noninverted Differential Output. |
| 11 | $\overline{Q1}$ | RSECL Output | Inverted Differential Output. |
| 12 | V_{CC} | - | Positive Supply. All V_{CC} Pins must be Externally Connected to Power Supply to Guarantee Proper Operation. |
| 13 | OLS (Note 2) | Input | Input Pin for Output Level Select (OLS) See Table 3. |
| 14 | Q0 | RSECL Output | Noninverted Differential Output Typically Terminated with 50 Ω Resistor to $V_{TT} = V_{CC} - 2.0$ V. |
| 15 | $\overline{Q0}$ | RSECL Output | Inverted Differential Output Typically Terminated with 50 Ω Resistor to $V_{TT} = V_{CC} - 2.0$ V. |
| 16 | V_{CC} | - | Positive Supply. All V_{CC} Pins must be Externally Connected to Power Supply to Guarantee Proper Operation. |
| - | EP | - | The Exposed Pad (EP) and the QFN-16 package bottom is thermally connected to the die for improved heat transfer out of package. The exposed pad must be attached to a heat-sinking conduit. The pad is not electrically connected to the die but may be electrically and thermally connected to V_{EE} on the PC board. |

1. In the differential configuration when the input termination pins (VTD0, VTD1) are connected to a common termination voltage, and if no signal is applied then the device will be susceptible to self-oscillation.
2. When an output level of 400 mV is desired and $V_{CC} - V_{EE} > 3.0$ V, 2 k Ω resistor should be connected from OLS pin to V_{EE} .

NBSG72A




Figure 2. Logic/Block Diagram

Table 2. TRUTH TABLE

| SELA | SELB | Q0 | Q1 |
|------|------|----|----|
| LOW | LOW | D0 | D0 |
| HIGH | LOW | D1 | D0 |
| LOW | HIGH | D0 | D1 |
| HIGH | HIGH | D1 | D1 |

Table 3. OUTPUT LEVEL SELECT (OLS)

| OLS | Output Amplitude (V_{OUTPP}) | OLS Sensitivity |
|-------------------|----------------------------------|------------------|
| V_{CC} | 800 mV | OLS - 75 mV |
| $V_{CC} - 0.4 V$ | 200 mV | OLS \pm 150 mV |
| $V_{CC} - 0.8 V$ | 600 mV | OLS \pm 100 mV |
| $V_{CC} - 1.2 V$ | 0 | OLS \pm 75 mV |
| V_{EE} (Note 3) | 400 mV | OLS \pm 100 mV |
| FLOAT | 600 mV | N/A |

3. When an output level of 400 mV is desired and $V_{CC} - V_{EE} > 3.0 V$, a 2 k Ω resistor should be connected from OLS to V_{EE} .

Table 4. INTERFACING OPTIONS

| Interfacing Options | Connections |
|---------------------|---|
| CML | Connect VTD0 and VTD1 to V_{CC} |
| LVDS | VTD0 and VTD1 Should Be Left Floating. |
| AC-COUPLED | Bias VTD0 and VTD1 Inputs within Common Mode Range (VIHCMR) |
| RSECL, PECL, NECL | Standard ECL Termination Techniques |
| LVC MOS / LVTTTL | The external voltage should be applied to the unused complementary differential input. Nominal voltage is 1.5 V for LVTTTL and $V_{CC}/2$ for LVC MOS Inputs. |

NBSG72A

Table 5. ATTRIBUTES

| Characteristics | Value |
|--|---|
| Internal Input Pulldown Resistor (SELA, SELB) | 75 kΩ |
| ESD Protection | Human Body Model Machine Model Charged Device Model |
| | > 2 kV > 50 V > 1 kV |
| Moisture Sensitivity (Note 1) | Level 1 |
| Flammability Rating | Oxygen Index: 28 to 34 |
| | UL 94 V-0 @ 0.125 in |
| Transistor Count | 436 |
| Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test | |

1. For additional information, see Application Note AND8003/D.

Table 6. MAXIMUM RATINGS

| Symbol | Parameter | Condition 1 | Condition 2 | Rating | Units |
|-------------------|---|--|--|---|--------------|
| V _{CC} | Positive Power Supply | V _{EE} = 0 V | | 3.6 | V |
| V _{EE} | Negative Power Supply | V _{CC} = 0 V | | -3.6 | V |
| V _I | Positive Input Negative Input | V _{EE} = 0 V V _{CC} = 0 V | V _I ≤ V _{CC} V _I ≥ V _{EE} | 3.6 -3.6 | V V |
| V _{INPP} | Differential Input Voltage D _X - \overline{D}_X | V _{EE} - V _{CC} ≥ 2.8 V V _{EE} - V _{CC} < 2.8 V | | 2.8 V _{CC} - V _{EE} | V |
| I _{out} | Output Current | Continuous Surge | | 25 50 | mA mA |
| I _{IN} | Input Current Through R _T (50 Ω Resistor) | Static Surge | | 45 80 | mA mA |
| T _A | Operating Temperature Range | | | -40 to +85 | °C |
| T _{stg} | Storage Temperature Range | | | -65 to +150 | °C |
| θ _{JA} | Thermal Resistance (Junction-to-Ambient) (Note 2) | 0 lfpm 500 lfpm | QFN-16 QFN-16 | 42 35 | °C/W °C/W |
| θ _{JC} | Thermal Resistance (Junction-to-Case) | (Note 2) | QFN-16 | 4 | °C/W |
| T _{sol} | Wave Solder | Pb Pb-Free | < 3 sec @ 260°C < 3 sec @ 260°C | 265 265 | °C |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

2. JEDEC standard multilayer board – 1S2P (1 signal, 2 power).

NBSG72A

Table 7. DC CHARACTERISTICS, INPUT WITH PECL OUTPUT $V_{CC} = 2.5\text{ V}$; $V_{EE} = 0\text{ V}$ (Note 3)

| Symbol | Characteristic | -40°C | | | 25°C | | | 85°C | | | Unit |
|-------------|--|-----------------|-------------------|----------------|-----------------|-------------------|----------------|-----------------|-------------------|----------------|---------------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| I_{EE} | Negative Power Supply Current | 40 | 55 | 65 | 40 | 55 | 65 | 40 | 55 | 65 | mA |
| V_{OH} | Output HIGH Voltage (Note 4) | 1460 | 1510 | 1560 | 1490 | 1540 | 1590 | 1515 | 1565 | 1615 | mV |
| V_{OL} | Output LOW Voltage (Note 4) | | | | | | | | | | mV |
| | (OLS = V_{CC}) | 555 | 705 | 855 | 595 | 745 | 895 | 625 | 775 | 925 | |
| | (OLS = $V_{CC} - 0.4\text{ V}$) | 1235 | 1295 | 1385 | 1270 | 1330 | 1420 | 1295 | 1355 | 1445 | |
| | (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) | 775 | 895 | 1015 | 810 | 930 | 1050 | 840 | 960 | 1080 | |
| | (OLS = $V_{CC} - 1.2\text{ V}$) | 1455 | 1505 | 1585 | 1490 | 1540 | 1620 | 1510 | 1560 | 1640 | |
| | (OLS = V_{EE}) | 1005 | 1095 | 1215 | 1040 | 1130 | 1250 | 1065 | 1155 | 1275 | |
| V_{OUTPP} | Output Voltage Amplitude | | | | | | | | | | mV |
| | (OLS = V_{CC}) | 670 | 800 | | 660 | 795 | | 655 | 790 | | |
| | (OLS = $V_{CC} - 0.4\text{ V}$) | 125 | 215 | | 120 | 210 | | 120 | 210 | | |
| | (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) | 510 | 615 | | 505 | 610 | | 500 | 605 | | |
| | (OLS = $V_{CC} - 1.2\text{ V}$) | 0 | 5 | | 0 | 0 | | 0 | 5 | | |
| | (OLS = V_{EE}) | 325 | 415 | | 320 | 410 | | 320 | 410 | | |
| V_{IH} | Input HIGH Voltage (Single-Ended) (Note 6) D0, $\overline{D0}$, D1, $\overline{D1}$, SELA, SELB | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | mV |
| V_{IL} | Input LOW Voltage (Single-Ended) (Note 7) D0, $\overline{D0}$, D1, $\overline{D1}$, SELA, SELB | V_{EE} | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | V_{EE} | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | V_{EE} | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | mV |
| V_{IHCMR} | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 5) | 1.2 | | 2.5 | 1.2 | | 2.5 | 1.2 | | 2.5 | V |
| R_{TIN} | Internal Input Termination Resistor | 45 | 50 | 55 | 45 | 50 | 55 | 45 | 50 | 55 | Ω |
| I_{IH} | Input HIGH Current (@ V_{IH}) | | 35 | 100 | | 35 | 100 | | 35 | 100 | μA |
| I_{IL} | Input LOW Current (@ V_{IL}) | | 20 | 100 | | 20 | 100 | | 20 | 100 | μA |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

*Typicals used for testing purposes.

3. Input and output parameters vary 1:1 with V_{CC} . V_{EE} can vary +0.125 V to -0.965 V.

4. All loading with 50 Ω to $V_{CC} - 2.0\text{ V}$.

5. V_{IHCMR} min varies 1:1 with V_{EE} , V_{IHCMR} max varies 1:1 with V_{CC} . The V_{IHCMR} range is referenced to the most positive side of the differential input signal.

6. V_{IH} cannot exceed V_{CC} .

7. V_{IL} always $\geq V_{EE}$.

NBSG72A

Table 8. DC CHARACTERISTICS, INPUT WITH PECL OUTPUT $V_{CC} = 3.3\text{ V}$; $V_{EE} = 0\text{ V}$ (Note 8)

| Symbol | Characteristic | -40°C | | | 25°C | | | 85°C | | | Unit |
|-------------|---|-----------------|-------------------|----------------|-----------------|-------------------|----------------|-----------------|-------------------|----------------|---------------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| I_{EE} | Negative Power Supply Current | 40 | 55 | 65 | 40 | 55 | 65 | 40 | 55 | 65 | mA |
| V_{OH} | Output HIGH Voltage (Note 9) | 2260 | 2310 | 2360 | 2290 | 2340 | 2390 | 2315 | 2365 | 2415 | mV |
| V_{OL} | Output LOW Voltage (Note 9) | | | | | | | | | | mV |
| | (OLS = V_{CC}) | 1320 | 1470 | 1620 | 1360 | 1510 | 1660 | 1390 | 1540 | 1690 | |
| | (OLS = $V_{CC} - 0.4\text{ V}$) | 2030 | 2090 | 2180 | 2065 | 2125 | 2215 | 2090 | 2150 | 2240 | |
| | (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) | 1550 | 1670 | 1790 | 1585 | 1705 | 1825 | 1615 | 1735 | 1855 | |
| | (OLS = $V_{CC} - 1.2\text{ V}$) | 2260 | 2310 | 2390 | 2290 | 2340 | 2420 | 2315 | 2365 | 2445 | |
| | ** (OLS = V_{EE}) | 1785 | 1875 | 1995 | 1820 | 1910 | 2030 | 1850 | 1940 | 2060 | |
| V_{OUTPP} | Output Amplitude Voltage | | | | | | | | | | mV |
| | (OLS = V_{CC}) | 705 | 815 | | 695 | 805 | | 690 | 800 | | |
| | (OLS = $V_{CC} - 0.4\text{ V}$) | 130 | 220 | | 125 | 215 | | 125 | 215 | | |
| | (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) | 535 | 640 | | 530 | 635 | | 525 | 630 | | |
| | (OLS = $V_{CC} - 1.2\text{ V}$) | 0 | 0 | | 0 | 0 | | 0 | 0 | | |
| | ** (OLS = V_{EE}) | 345 | 435 | | 340 | 430 | | 335 | 425 | | |
| V_{IH} | Input HIGH Voltage (Single-Ended) (Note 11) D0, $\overline{D0}$, D1, $\overline{D1}$, SELA, SELB | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | mV |
| V_{IL} | Input LOW Voltage (Single-Ended) (Note 12) D0, $\overline{D0}$, D1, $\overline{D1}$, SELA, SELB | $V_{IH} - 2600$ | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | $V_{IH} - 2600$ | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | $V_{IH} - 2600$ | $V_{CC} - 1400^*$ | $V_{IH} - 150$ | mV |
| V_{IHCMR} | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 10) | 1.2 | | 3.3 | 1.2 | | 3.3 | 1.2 | | 3.3 | V |
| R_{TIN} | Internal Input Termination Resistor | 45 | 50 | 55 | 45 | 50 | 55 | 45 | 50 | 55 | Ω |
| I_{IH} | Input HIGH Current (@ V_{IH}) | | 35 | 100 | | 35 | 100 | | 35 | 100 | μA |
| I_{IL} | Input LOW Current (@ V_{IL}) | | 20 | 100 | | 20 | 100 | | 20 | 100 | μA |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

*Typicals used for testing purposes.

**When an output level of 400 mV is desired and $V_{CC} - V_{EE} > 3.0\text{ V}$, a 2 k Ω resistor should be connected from OLS to V_{EE} .

8. Input and output parameters vary 1:1 with V_{CC} . V_{EE} can vary +0.925 V to -0.165 V.

9. All loading with 50 Ω to $V_{CC} - 2.0\text{ V}$.

10. V_{IHCMR} min varies 1:1 with V_{EE} , V_{IHCMR} max varies 1:1 with V_{CC} . The V_{IHCMR} range is referenced to the most positive side of the differential input signal.

11. V_{IH} cannot exceed V_{CC} .

12. V_{IL} always $\geq V_{EE}$.

NBSG72A

Table 9. DC CHARACTERISTICS, NECL INPUT WITH NECL OUTPUT $V_{CC} = 0\text{ V}$; $V_{EE} = -3.465\text{ V}$ to -2.375 V (Note 13)

| Symbol | Characteristic | -40°C | | | 25°C | | | 85°C | | | Unit | | | |
|-------------|--|----------------|--|--------------------|---------------------|-------------------|--------------------|---------------------|-------------------|--------------------|---------------------|-------------------|----|----|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | | | | |
| I_{EE} | Negative Power Supply Current | 40 | 55 | 65 | 40 | 55 | 65 | 40 | 55 | 65 | mA | | | |
| V_{OH} | Output HIGH Voltage (Note 14) | -1040 | -990 | -940 | -1010 | -960 | -910 | -985 | -935 | -885 | mV | | | |
| V_{OL} | Output LOW Voltage (Note 14) $-3.465\text{ V} \leq V_{EE} \leq -3.0\text{ V}$ (OLS = V_{CC}) (OLS = $V_{CC} - 0.4\text{ V}$) (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) (OLS = $V_{CC} - 1.2\text{ V}$) ** (OLS = V_{EE}) $-3.0\text{ V} < V_{EE} \leq -2.375\text{ V}$ (OLS = V_{CC}) (OLS = $V_{CC} - 0.4\text{ V}$) (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) (OLS = $V_{CC} - 1.2\text{ V}$) (OLS = V_{EE}) | -1980 | -1830 | -1680 | -1940 | -1790 | -1640 | -1910 | -1760 | -1610 | mV | | | |
| | | -1270 | -1210 | -1120 | -1235 | -1175 | -1085 | -1210 | -1150 | -1060 | | | | |
| | | -1750 | -1630 | -1510 | -1715 | -1595 | -1475 | -1685 | -1565 | -1445 | | | | |
| | | -1040 | -990 | -910 | -1010 | -960 | -880 | -985 | -935 | -855 | | | | |
| | | -1515 | -1425 | -1305 | -1480 | -1390 | -1270 | -1450 | -1360 | -1240 | | | | |
| | | -1945 | -1795 | -1645 | -1905 | -1755 | -1605 | -1875 | -1725 | -1575 | | | | |
| | | -1265 | -1205 | -1115 | -1230 | -1170 | -1080 | -1205 | -1145 | -1055 | | | | |
| | | -1725 | -1605 | -1485 | -1690 | -1570 | -1450 | -1660 | -1540 | -1420 | | | | |
| | | -1045 | -995 | -915 | -1010 | -960 | -880 | -990 | -940 | -860 | | | | |
| | | -1495 | -1405 | -1285 | -1460 | -1370 | -1250 | -1435 | -1345 | -1225 | | | | |
| | | V_{OUTPP} | Output Voltage Amplitude $-3.465\text{ V} \leq V_{EE} \leq -3.0\text{ V}$ (OLS = V_{CC}) (OLS = $V_{CC} - 0.4\text{ V}$) (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) (OLS = $V_{CC} - 1.2\text{ V}$) ** (OLS = V_{EE}) $-3.0\text{ V} < V_{EE} \leq -2.375\text{ V}$ (OLS = V_{CC}) (OLS = $V_{CC} - 0.4\text{ V}$) (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) (OLS = $V_{CC} - 1.2\text{ V}$) (OLS = V_{EE}) | 705 | 815 | | 695 | 805 | | 690 | | 800 | | mV |
| | | | | 130 | 220 | | 125 | 215 | | 125 | | 215 | | |
| 535 | 640 | | | | 530 | 635 | | 525 | 630 | | | | | |
| 0 | 0 | | | | 0 | 0 | | 0 | 0 | | | | | |
| 345 | 435 | | | | 340 | 430 | | 335 | 425 | | | | | |
| 670 | 800 | | | | 660 | 795 | | 655 | 790 | | | | | |
| 125 | 215 | | | | 120 | 210 | | 120 | 210 | | | | | |
| 510 | 615 | | | | 505 | 610 | | 500 | 605 | | | | | |
| 0 | 5 | | | | 0 | 0 | | 0 | 5 | | | | | |
| 325 | 415 | | | | 320 | 410 | | 320 | 410 | | | | | |
| V_{IH} | Input HIGH Voltage (Single-Ended) (Note 16) D0, D0, D1, D1, SELA, SELB | | | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | $V_{EE} + 1275$ | $V_{CC} - 1000^*$ | V_{CC} | mV | |
| | | | | V_{IH}^- 2600 | V_{CC}^- 1400* | V_{IH}^- 150 | V_{IH}^- 2600 | V_{CC}^- 1400* | V_{IH}^- 150 | V_{IH}^- 2600 | V_{CC}^- 1400* | V_{IH}^- 150 | mV | |
| V_{IHCMR} | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 15) | $V_{EE} + 1.2$ | | 0.0 | $V_{EE} + 1.2$ | | 0.0 | $V_{EE} + 1.2$ | | 0.0 | V | | | |
| R_{TIN} | Internal Input Termination Resistor | 45 | 50 | 55 | 45 | 50 | 55 | 45 | 50 | 55 | Ω | | | |
| I_{IH} | Input HIGH Current (@ V_{IH}) | | 35 | 100 | | 35 | 100 | | 35 | 100 | μA | | | |
| I_{IL} | Input LOW Current (@ V_{IL}) | | 20 | 100 | | 20 | 100 | | 20 | 100 | μA | | | |
| I_{OLS} | OLS Input Current (See Figure 9) (OLS = V_{CC}) (OLS = $V_{CC} - 0.4\text{ V}$) (OLS = $V_{CC} - 0.8\text{ V}$, OLS = FLOAT) (OLS = $V_{CC} - 1.2\text{ V}$) $-3.0\text{ V} < V_{EE} \leq -2.375\text{ V}$ (OLS = V_{EE}) $-3.465\text{ V} \leq V_{EE} \leq -3.0\text{ V}$ *(OLS = V_{EE}) | | 300 | 900 | | 300 | 900 | | 300 | 900 | μA | | | |
| | | | 100 | 300 | | 100 | 300 | | 100 | 300 | | | | |
| | | | 5 | 100 | | 5 | 100 | | 5 | 100 | | | | |
| | | -300 | -100 | | -300 | -100 | | -300 | -100 | | | | | |
| | | -1000 | -400 | | -1000 | -400 | | -1000 | -400 | | | | | |
| | | -1500 | -600 | | -1500 | -600 | | -1500 | -600 | | | | | |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

*Typicals used for testing purposes.

**When an output level of 400 mV is desired and $V_{CC} - V_{EE} > 3.0\text{ V}$, a 2 k Ω resistor should be connected from OLS to V_{EE} .

13. Input and output parameters vary 1:1 with V_{CC} .

14. All loading with 50 Ω to $V_{CC} - 2.0\text{ V}$.

15. V_{IHCMR} min varies 1:1 with V_{EE} , V_{IHCMR} max varies 1:1 with V_{CC} . The V_{IHCMR} range is referenced to the most positive side of the differential input signal.

16. V_{IH} cannot exceed V_{CC} .

17. V_{IL} always $\geq V_{EE}$.

NBSG72A

Table 10. AC CHARACTERISTICS $V_{CC} = 0\text{ V}$; $V_{EE} = -3.465\text{ V}$ to -2.375 V or $V_{CC} = 2.375\text{ V}$ to 3.465 V ; $V_{EE} = 0\text{ V}$ (Note 18)

| Symbol | Characteristic | -40°C | | | 25°C | | | 85°C | | | Unit | |
|----------------------------------|--|----------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | | |
| V _{OUTPP} | Output Voltage Amplitude (Note 18) | $f_{in} < 5\text{ GHz}$ | 400 | 590 | | 450 | 590 | | 440 | 590 | | mV |
| | | $f_{in} \leq 7\text{ GHz}$ | 200 | 250 | | 180 | 250 | | 130 | 250 | | |
| t _{PLH} | Propagation Delay to Output Differential D0, D1 → Q0, Q1 SELA, SELB → Q0, Q1 | | 170 | 205 | 255 | 170 | 205 | 255 | 170 | 210 | 260 | ps |
| | | | 190 | 265 | 350 | 190 | 265 | 350 | 190 | 265 | 350 | |
| t _{PHL} | Propagation Delay to Output Differential D0, D1 → Q0, Q1 SELA, SELB → Q0, Q1 | | 170 | 205 | 255 | 170 | 205 | 255 | 170 | 210 | 260 | ps |
| | | | 150 | 215 | 270 | 150 | 215 | 270 | 150 | 215 | 270 | |
| t _{SKEW} | Duty Cycle Skew (Note 19) Within-Device Skew Device-to-Device Skew | | | 5.0 | 25 | | 5.0 | 25 | | 5.0 | 25 | ps |
| | | | | 5.0 | 25 | | 5.0 | 25 | | 5.0 | 25 | |
| | | | | 15 | 50 | | 15 | 50 | | 15 | 50 | |
| t _{JITTER} | RMS Random Clock Jitter (Note 20) ≤ 1 GHz OLS = V _{CC} ≤ 5 GHz OLS = V _{CC} ≤ 6.5 GHz OLS = V _{CC} ≤ 1 GHz OLS = V _{CC} - 400 mV ≤ 5 GHz OLS = V _{CC} - 400 mV ≤ 6.5 GHz OLS = V _{CC} - 400 mV ≤ 1 GHz OLS = V _{CC} - 800 mV ≤ 5 GHz OLS = V _{CC} - 800 mV ≤ 6.5 GHz OLS = V _{CC} - 800 mV ≤ 1 GHz OLS = V _{EE} ≤ 5 GHz OLS = V _{EE} ≤ 6.5 GHz OLS = V _{EE} Peak-to-Peak Data Dependent Jitter (Note 21) $f_{in} \leq 7\text{ Gb/s}$ | | | 0.16 | 0.3 | | 0.17 | 0.3 | | 0.18 | 0.4 | ps |
| | | | | 0.14 | 0.4 | | 0.16 | 0.4 | | 0.19 | 0.4 | |
| | | | | 0.21 | 0.5 | | 0.31 | 0.7 | | 0.44 | 0.9 | |
| | | | | 0.23 | 0.4 | | 0.23 | 0.4 | | 0.25 | 0.4 | |
| | | | | 0.18 | 0.5 | | 0.19 | 0.5 | | 0.23 | 0.5 | |
| | | | | 0.2 | 0.5 | | 0.25 | 0.6 | | 0.32 | 0.7 | |
| | | | | 0.17 | 0.3 | | 0.18 | 0.3 | | 0.19 | 0.3 | |
| | | | | 0.14 | 0.4 | | 0.16 | 0.3 | | 0.2 | 0.3 | |
| | | | | 0.2 | 0.5 | | 0.27 | 0.7 | | 0.38 | 0.9 | |
| | | | | 0.18 | 0.3 | | 0.19 | 0.3 | | 0.2 | 0.3 | |
| | | | | 0.16 | 0.6 | | 0.17 | 0.4 | | 0.2 | 0.4 | |
| | | | | 0.18 | 0.5 | | 0.24 | 0.6 | | 0.34 | 0.8 | |
| V _{INPP} | Input Voltage Swing/Sensitivity (Differential Configuration) (Note 22) | 75 | | 2600 | 75 | | 2600 | 75 | | 2600 | mV | |
| t _r t _f | Output Rise/Fall Times (Q0, Q1) (20% - 80%) @ 1 GHz | t _r t _f | 40 30 | 55 45 | 70 55 | 40 30 | 55 45 | 70 55 | 40 30 | 55 45 | 70 55 | ps |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

18. Measured using a 75 mV source, 50% duty cycle clock source. All loading with 50 Ω to V_{CC} - 2.0 V. OLS = FLOAT. Input edge rates 40 ps (20% - 80%).

19. t_{SKEW} = |t_{PLH} - t_{PHL}| for a nominal 50% differential clock input waveform.

20. Additive RMS jitter with 50% Duty Cycle clock signal.

21. Additive Peak-to-Peak data dependent jitter with NRZ PRBS 2³¹-1 data at 7 Gb/s.

22. Input Voltage Swing is a single-ended measurement operating in differential mode. V_{INPP} (max) cannot exceed V_{CC} - V_{EE}.

NBSG72A




Figure 3. Output Voltage Amplitude (V_{OUTPP}) vs. Input Clock Frequency (f_{IN}) @ Ambient Temperature (Typical)

*When an output level of 400 mV is desired and $V_{CC} - V_{EE} > 3.0$ V, a 2 k Ω resistor should be connected from OLS to V_{EE} .





Figure 4. Channel-to-Channel Crosstalk Isolation at Ambient Temperature (D0 to Q0 Signal Path Selected; SelA = Low, SelB = High)





Figure 5. Channel-to-Channel Crosstalk Isolation at Ambient Temperature (D1 to Q0 Signal Path Selected; SelA = High, SelB = Low)

NBSG72A





Figure 6. Channel-to-Channel Crosstalk Isolation at Ambient Temperature (D0 to Q0 and Q1 Signal Path Selected; SelA = Low, SelB = Low)






Figure 7. Channel-to-Channel Crosstalk Isolation at Ambient Temperature (D1 to Q0 and Q1 Signal Path Selected; SelA = High, SelB = High)


NBSG72A



Total System Jitter = 17.2 ps
 Input Generator Jitter = 10 ps
 Device Jitter = 6.8 ps

X = 60 ps/div

Figure 8. Eye Diagram at 3.2 Gb/s
 ($V_{CC} - V_{EE} = 3.3$ V, OLS = FLOAT @ 25°C with input pattern of $2^{31}-1$ PRBS, 5000 Waveforms)



Total System Jitter = 17.2 ps
 Input Generator Jitter = 10 ps
 Device Jitter = 7.2 ps

X = 21 ps/div

Figure 9. Eye Diagram at 7 Gb/s/s
 ($V_{CC} - V_{EE} = 3.3$ V, OLS = FLOAT @ 25°C with input pattern of $2^{31}-1$ PRBS, 5000 Waveforms)




Figure 10. Typical OLS Input Current vs. OLS Input Voltage
 ($V_{CC} - V_{EE} = 3.3$ V @ 25°C)

NBSG72A




Figure 11. OLS Operating Area




Figure 12. AC Reference Measurement




Figure 13. Typical Termination for Output Driver and Device Evaluation
(See Application Note AND8020/D – Termination of ECL Logic Devices.)

NBSG72A

ORDERING INFORMATION

| Device | Package | Shipping† |
|--------------|---------------------|--------------------|
| NBSG72AMN | QFN-16 | 123 Units / Rail |
| NBSG72AMNG | QFN-16 (Pb-Free) | 123 Units / Rail |
| NBSG72AMNR2 | QFN-16 | 3000 / Tape & Reel |
| NBSG72AMNR2G | QFN-16 (Pb-Free) | 3000 / Tape & Reel |

| Board | Description |
|--------------|----------------------------|
| NBSG72AMNEVB | NBSG72AMN Evaluation Board |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


Resource Reference of Application Notes

- AN1405/D** - ECL Clock Distribution Techniques
- AN1406/D** - Designing with PECL (ECL at +5.0 V)
- AN1503/D** - ECLinPS™ I/O SPiCE Modeling Kit
- AN1504/D** - Metastability and the ECLinPS Family
- AN1568/D** - Interfacing Between LVDS and ECL
- AN1672/D** - The ECL Translator Guide
- AND8001/D** - Odd Number Counters Design
- AND8002/D** - Marking and Date Codes
- AND8020/D** - Termination of ECL Logic Devices
- AND8066/D** - Interfacing with ECLinPS
- AND8090/D** - AC Characteristics of ECL Devices

NBSG72A

PACKAGE DIMENSIONS

16 PIN QFN
CASE 485G-01
ISSUE C



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. L_{max} CONDITION CAN NOT VIOLATE 0.2 MM MINIMUM SPACING BETWEEN LEAD TIP AND FLAG

| DIM | MILLIMETERS | |
|-----|-------------|------|
| | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 REF | |
| b | 0.18 | 0.30 |
| D | 3.00 BSC | |
| D2 | 1.65 | 1.85 |
| E | 3.00 BSC | |
| E2 | 1.65 | 1.85 |
| e | 0.50 BSC | |
| K | 0.18 TYP | |
| L | 0.30 | 0.50 |

GigaComm is a trademark of Semiconductor Components Industries, LLC.

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9