NEW PRODUCT

DCX (LO-R1) H

COMPLEMENTARY NPN/PNP PRE-BIASED SMALL SIGNAL DUAL SURFACE MOUNT TRANSISTOR

Features

- Epitaxial Planar Die Construction
- Built-In Biasing Resistors
- **Lead Free By Design/RoHS Compliant (Note 3)**
- **"Green" Device (Note 4 and 5)**

Mechanical Data

- Case: SOT-563
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish - Matte Tin annealed over Alloy 42 leadframe. Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Weight: 0.005 grams (approximate)



SOT-563			
Dim	**Min**	**Max**	**Typ**
A	0.15	0.30	0.25
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D		0.50	
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.56	0.60	0.60
L	0.15	0.25	0.20
M	0.10	0.18	0.11
All Dimensions in mm			

P/N	R1 (NOM)	R2 (NOM)	MARKING
DCX122LH	0.22KΩ	10KΩ	C81
DCX142JH	0.47KΩ	10KΩ	C82
DCX122TH	0.22KΩ	OPEN	C83
DCX142TH	0.47KΩ	OPEN	C84



R_1, R_2 R_1 Only

SCHEMATIC DIAGRAM, TOP VIEW

Maximum Ratings NPN Section

@T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit
Supply Voltage		V_{CC}	50	V
Input Voltage	DCX122LH DCX142JH	V_{IN}	-5 to +6 -5 to +6	V
Input Voltage	DCX122TH DCX142TH	$V_{EBO\ (MAX)}$	5	V
Output Current	All	I_C	100	mA
Power Dissipation	(Note 1, 2)	P_d	150	mW
Thermal Resistance, Junction to Ambient Air	(Note 1)	$R_{\theta JA}$	833	°C/W
Operating and Storage Temperature Range		T_j, T_{STG}	-55 to +150	°C

Notes:
1. Mounted on FR4 PC Board with recommended pad layout at http://www.diodes.com/datasheets/ap02001.pdf.
2. NPN Section, PNP Section, or maximum combined.
3. No purposefully added lead.
4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.

© Diodes Incorporated

NEW PRODUCT

Maximum Ratings PNP Section @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit
Supply Voltage		V_{CC}	-50	V
Input Voltage	DCX122LH DCX142JH	V_{IN}	+5 to -6 +5 to -6	V
Input Voltage	DCX122TH DCX142TH	$V_{EBO\ (MAX)}$	-5	V
Output Current	All	I_C	-100	mA
Power Dissipation	(Note 1, 2)	P_d	150	mW
Thermal Resistance, Junction to Ambient Air	(Note 1)	$R_{\theta JA}$	833	°C/W
Operating and Storage Temperature Range		T_j, T_{STG}	-55 to +150	°C

Electrical Characteristics NPN Section @T_A = 25°C unless otherwise specified **R1, R2 Types**

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Input Voltage	DCX122LH DCX142JH	$V_{I(off)}$	0.3 0.3	—	—	V	V_{CC} = 5V, I_O = 100μA
	DCX122LH DCX142JH	$V_{I(on)}$	—	—	2.0 2.0	V	V_O = 0.3V, I_O = 20mA V_O = 0.3V, I_O = 20mA
Output Voltage		$V_{O(on)}$	—	—	0.3V	V	I_O/I_I = 5mA/0.25mA
Input Current	DCX122LH DCX142JH	I_I	—	—	28 13	mA	V_I = 5V
Output Current		$I_{O(off)}$	—	—	0.5	μA	V_{CC} = 50V, V_I = 0V
DC Current Gain	DDCX122LH DDCX142JH	G_I	56 56	—	—	—	V_O = 5V, I_O = 10mA
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = 10V, I_E = 5mA, f = 100MHz

* Transistor - For Reference Only

Electrical Characteristics NPN Section @T_A = 25°C unless otherwise specified **R1-Only**

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage		BV_{CBO}	50	—	—	V	I_C = 50μA
Collector-Emitter Breakdown Voltage		BV_{CEO}	40	—	—	V	I_C = 1mA
Emitter-Base Breakdown Voltage	DCX122TH DCX142TH	BV_{EBO}	5	—	—	V	I_E = 50μA I_E = 50μA
Collector Cutoff Current		I_{CBO}	—	—	0.5	μA	V_{CB} = 50V
Emitter Cutoff Current	DCX122TH DCX142TH	I_{EBO}	— —	—	0.5 0.5	μA	V_{EB} = 4V
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	—	—	0.3	V	I_C = 5mA, I_B = 0.25mA
DC Current Transfer Ratio	DCX122TH DCX142TH	h_{FE}	100 100	250 250	600 600	—	I_C = 1mA, V_{CE} = 5V
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = 10V, I_E = -5mA, f = 100MHz

* Transistor - For Reference Only

© Diodes Incorporated

NEW PRODUCT

Electrical Characteristics PNP Section @T_A = 25°C unless otherwise specified — R1, R2 Types

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Input Voltage	DCX122LH DCX142JH	$V_{I(off)}$	-0.3 -0.3	—	—	V	V_{CC} = -5V, I_O = -100μA
	DCX122LH DCX142JH	$V_{I(on)}$	—	—	-2.0 -2.0	V	V_O = -0.3V, I_O = -20mA V_O = -0.3V, I_O = -20mA
Output Voltage		$V_{O(on)}$	—	—	-0.3V	V	I_O/I_I = -5mA/-0.25mA
Input Current	DCX122LH DCX142JH	I_I	—	—	-28 -13	mA	V_I = -5V
Output Current		$I_{O(off)}$	—	—	-0.5	μA	V_{CC} = -50V, V_I = 0V
DC Current Gain	DCX122LH DCX142JH	G_I	56 56	—	—	—	V_O = -5V, I_O = -10mA
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = -10V, I_E = -5mA, f = 100MHz

* Transistor - For Reference Only

Electrical Characteristics @T_A = 25°C unless otherwise specified — R1-Only Types

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage		BV_{CBO}	-50	—	—	V	I_C = -50μA
Collector-Emitter Breakdown Voltage		BV_{CEO}	-40	—	—	V	I_C = -1mA
Emitter-Base Breakdown Voltage	DCX122TH DCX142TH	BV_{EBO}	-5	—	—	V	I_E = -50μA I_E = -50μA
Collector Cutoff Current		I_{CBO}	—	—	-0.5	μA	V_{CB} = -50V
Emitter Cutoff Current	DCX122TH DCX142TH	I_{EBO}	— —	—	-0.5 -0.5	μA	V_{EB} = -4V
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	—	—	-0.3	V	I_C = -5mA, I_B = -0.25mA
DC Current Transfer Ratio	DCX122TH DCX142TH	h_{FE}	100 100	250 250	600 600	—	I_C = -1mA, V_{CE} = -5V
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = -10V, I_E = 5mA, f = 100MHz

* Transistor - For Reference Only



Fig. 1 Derating Curve - Total

© Diodes Incorporated

NEW PRODUCT

Ordering Information (Note 6)

Device	Packaging	Shipping
DCX122LH-7	SOT-563	3000/Tape & Reel
DCX142JH-7	SOT-563	3000/Tape & Reel
DCX122TH-7	SOT-563	3000/Tape & Reel
DCX142TH-7	SOT-563	3000/Tape & Reel

Notes: 6. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



CXX = Product Type Marking Code (See Page 1)
YM = Date Code Marking
Y = Year ex: T = 2006
M = Month ex: 9 = September

Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9