



## Features

Supports Data Rates up to 32 Gbps

- ## 660 mW Power Consumption


-3.3 V or +3.3 V Operation is Available

### Supports Single-Ended and Differential Operation

24 Lead Ceramic 4x4 mm SMT Package: 16 mm<sup>2</sup>

## Invert Port Allows Scrambling for SERDES Application

### General Description



All differential inputs to the HMC955LC4B are CML and terminated on-chip with 50 Ohms to the positive supply, GND, and may be AC or DC coupled. The differential CML outputs are source terminated to 50 Ohms and may also be AC or DC coupled. Outputs can be connected directly to a 50 Ohm ground-terminated system or drive devices with CML logic input. The HMC955LC4B operates from a single -3.3 V supply and is available in a ceramic ROHS-compliant 4x4 mm SMT package.

**Electrical Specifications,  $T_A = +25\text{ }^{\circ}\text{C}$ ,  $V_{EE} = -3.3\text{ V}$ ,  $V_R = 0\text{ V}$**

| Parameter                           | Conditions         | Min. | Typ. | Max  | Units |
|-------------------------------------|--------------------|------|------|------|-------|
| Power Supply Voltage (Vee)          |                    | -3.6 | -3.3 | -3.0 | V     |
| Power Supply Current                |                    |      | 200  |      | mA    |
| Maximum Data Rate                   |                    |      | 32   |      | Gbps  |
| Maximum Clock Rate                  |                    |      | 16   |      | GHz   |
| Input Voltage Range, C and DIN      |                    | -1.5 |      | 0.5  | V     |
| Input Differential Range, C and DIN |                    | 0.1  |      | 2.0  | Vp-p  |
| Data Input Return Loss              | Frequency <26 Gbps |      | 10   |      | dB    |
| Clock Input Return Loss             | Frequency <16 GHz  |      | 10   |      | dB    |
| Invert Input Return Loss            | Frequency <16 GHz  |      | 10   |      | dB    |

For price, delivery, and to place orders: Analog Devices, Inc.,  
One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106  
Phone: 781-329-4700 • Order online at [www.analog.com](http://www.analog.com)  
Application Support: Phone: 1-800-ANALOG-D




## 32 Gbps, 1:2 DEMUX WITH PROGRAMMABLE OUTPUT VOLTAGE

### Electrical Specifications (continued)


| Parameter                    | Conditions                                                      | Min. | Typ. | Max | Units  |
|------------------------------|-----------------------------------------------------------------|------|------|-----|--------|
| Output Amplitude             | Single-Ended, peak-to-peak                                      |      | 500  |     | mVp-p  |
|                              | Differential, peak-to-peak                                      |      | 1000 |     | mVp-p  |
| Output High Voltage          |                                                                 |      | -25  |     | mV     |
| Output Low Voltage           |                                                                 |      | -525 |     | mV     |
| Output Rise / Fall Time      | Single-Ended, 20% - 80%                                         |      | 19   |     | ps     |
| Output Return Loss           | Frequency <26 Gbps                                              |      | 10   |     | dB     |
| Random Jitter $J_R$          | rms <sup>[1]</sup>                                              |      | <0.2 |     | ps rms |
| VR Pin Current               | VR = 0.0 V                                                      |      | 3    |     | mA     |
| Deterministic Jitter, $J_D$  | $\delta - \delta$ , 2 <sup>7</sup> -1 PRBS input <sup>[1]</sup> |      | <3   |     | ps     |
| Propagation Delay, $t_{cpd}$ | Rising Edge                                                     |      | 119  |     | ps     |
| Data Setup Time, $t_s$       |                                                                 |      | 1    |     | ps     |
| Data Hold Time, $t_h$        |                                                                 |      | 7    |     | ps     |
| Invert Setup Time, $t_{is}$  |                                                                 |      | 0    |     | ps     |
| Invert Hold Time, $t_{ih}$   |                                                                 |      | 11   |     | ps     |

[1] Jitter captured at 13 Gbps, 2<sup>7</sup>-1 PRBS input.

**DC Current vs. Supply Voltage <sup>[1][3]</sup>**



**DC Current vs. VR <sup>[2][3]</sup>**



[1] VR = 0.0 V

[2] Frequency = 16 Gbps

[3] Vee = -3.3 V


Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

For price, delivery, and to place orders: Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106  
Phone: 781-329-4700 • Order online at [www.analog.com](http://www.analog.com)  
Application Support: Phone: 1-800-ANALOG-D




## 32 Gbps, 1:2 DEMUX WITH PROGRAMMABLE OUTPUT VOLTAGE


**Data Output Differential vs.  
Supply Voltage [1][2]**




**Output Differential vs. VR [2][4]**




**Rise / Fall Time vs. Supply Voltage [1][2]**




**Rise / Fall Time vs. VR [2][4]**



**Clock Input Return Loss vs.  
Frequency [1][3][4]**



**Data Output Return Loss vs.  
Frequency [1][3][4]**



[1] VR = 0.0V


[2] Frequency = 16 Gbps output [3] Device measured on evaluation board with gating after connector

[4] Vee = -3.3 V




**32 Gbps, 1:2 DEMUX  
WITH PROGRAMMABLE OUTPUT VOLTAGE**


**Data Input Return Loss vs.  
Frequency [1][3][4]**



**Invert Input Return Loss vs.  
Frequency [1][3][4]**




**Eye Diagram, 16 Gbps**



[1] Test Conditions:  
Single-ended 200 mV, 32 Gbps data input; 16 GHz clock input  
Pattern generated with a 2<sup>7</sup>-1 quasi PN, 32 Gbps PRBS pattern  
Resulting in 16 Gbps, 2<sup>7</sup>-1 quasi PN output measured with  
Tektronix CSA 8000

**Timing Diagram**





## 32 Gbps, 1:2 DEMUX WITH PROGRAMMABLE OUTPUT VOLTAGE


### Absolute Maximum Ratings

|                                                                                       |                   |
|---------------------------------------------------------------------------------------|-------------------|
| Power Supply Voltage (Vee)                                                            | -3.75 V to +0.5 V |
| Input Signals                                                                         | -2 V to +0.5 V    |
| Output Signals                                                                        | -1.5 V to +1 V    |
| Junction Temperature                                                                  | 125 °C            |
| Continuous P <sub>diss</sub> (T=85 °C)<br>(derate 30 mW/°C above 85 °C)               | 1.22 W            |
| Thermal Resistance (R <sub>th j-p</sub> )<br>Worse case junction to package<br>paddle | 32.8 °C/W         |
| Storage Temperature                                                                   | -65 °C to +150 °C |
| Operating Temperature                                                                 | -40 °C to +85 °C  |
| ESD Sensitivity (HBM)                                                                 | Class 1B          |



ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS

### Outline Drawing



### Package Information

| Part Number | Package Body Material | Lead Finish      | MSL Rating          | Package Marking <sup>[2]</sup> |
|-------------|-----------------------|------------------|---------------------|--------------------------------|
| HMC955LC4B  | Alumina, White        | Gold over Nickel | MSL3 <sup>[1]</sup> | H955<br>XXXX                   |

[1] Max peak reflow temperature of 260 °C




[2] 4-Digit lot number XXXX

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

For price, delivery, and to place orders: Analog Devices, Inc.,  
One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106  
Phone: 781-329-4700 • Order online at [www.analog.com](http://www.analog.com)  
Application Support: Phone: 1-800-ANALOG-D

## 32 Gbps, 1:2 DEMUX WITH PROGRAMMABLE OUTPUT VOLTAGE


### Pin Descriptions

| Pin Number             | Function                   | Description                                                                                                                              | Interface Schematic                                                                   |
|------------------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 1, 6, 8, 11, 13, 18    | GND                        | Signal Grounds                                                                                                                           |    |
| 2, 3<br>4, 5<br>9, 10  | DP, DN<br>CP, CN<br>IP, IN | Differential Data Inputs: Current Mode Logic (CML) referenced to positive supply.                                                        |    |
| 7, 12, 22              | N/C                        | The pins are not connected internally; however, all data shown herein was measured with these pins connected to RF/DC ground externally. |                                                                                       |
| 14, 15<br>16, 17       | O2N, O2P<br>O1N, O1P       | Differential Outputs: Current Mode Logic (CML) referenced to positive supply                                                             |   |
| 19, 24                 | GND                        | Supply Grounds                                                                                                                           |  |
| 20, 23<br>Package Base | Vee                        | These pins and the exposed paddle must be connected to the negative voltage supply.                                                      |                                                                                       |
| 21                     | VR                         | Output level control. Output level may be increased or decreased by applying a voltage to VR per "Output Differential vs. VR" plot.      |  |



**32 Gbps, 1:2 DEMUX  
WITH PROGRAMMABLE OUTPUT VOLTAGE**

**Evaluation PCB**



**List of Materials for  
Evaluation PCB EVAL01-HMC955LC4B [1]**

| Item      | Description                               |
|-----------|-------------------------------------------|
| J1 - J10  | PCB Mount 2.92 mm RF Connectors           |
| J15 - J18 | DC Pin                                    |
| JP1       | 0.1" Header with Shorting Jumper          |
| C1, C2    | 4.7 $\mu$ F Capacitor, Tantalum           |
| C3 - C5   | 330 pF, Capacitor, 0603 Pkg               |
| R1        | 10 Ohm Resistor, 0603 Pkg.                |
| U1        | HMC955LC4B<br>High Speed Logic, 1:2 Demux |
| PCB [2]   | 126570 Evaluation Board                   |


[1] Reference this number when ordering complete evaluation PCB

[2] Circuit Board Material: Arlon 25FR or Rogers 4350

The circuit board used in the application should use RF circuit design techniques. Signal lines should have 50 Ohm impedance while the package ground leads should be connected directly to the ground plane similar to that shown. The exposed packaged base should be connected to Vee. A sufficient number of via holes should be used to connect the top and bottom ground planes. The evaluation circuit board shown is available from Hittite upon request. Install jumper on JP1 to short VR to GND for normal operation.

**32 Gbps, 1:2 DEMUX  
WITH PROGRAMMABLE OUTPUT VOLTAGE**

**Application Circuit**



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9