

# HCMOS SURFACE-MOUNT CRYSTAL CLOCK OSCILLATOR

## ASA SERIES

Moisture Sensitivity Level (MSL) – This product is  
Hermetically Sealed and not Moisture Sensitive -  
MSL = N/A: Not Applicable



RoHS  
Compliant



2.0 x 1.6 x 0.7mm

### FEATURES:

- Ultra miniature package, 2.0 x 1.6 x 0.7mm
- Tri-state function
- Suitable for high density SMT
- Suitable for RoHS compliant reflow process
- Seam sealed package assures high reliability

### APPLICATIONS:

- CCD clock for VTR camera
- Computers and peripherals
- Portable electronics
- Mobile communication, PDA

### STANDARD SPECIFICATIONS:

| Parameters                        |                 | Minimum                                                         | Typical | Maximum | Units | Notes                                       |
|-----------------------------------|-----------------|-----------------------------------------------------------------|---------|---------|-------|---------------------------------------------|
| Frequency Range                   |                 | 1.0                                                             | ----    | 80      | MHz   |                                             |
| Operating Temperature             |                 | -10                                                             | ----    | +60     | °C    | See options                                 |
| Storage Temperature               |                 | -40                                                             | ----    | +85     | °C    |                                             |
| Overall Frequency Stability*      |                 | -50                                                             | ----    | +50     | ppm   | See options                                 |
| Supply Voltage (Vdd)              |                 | 2.97                                                            | 3.3     | 3.66    | V     | Standard                                    |
|                                   |                 | 2.25                                                            | 2.5     | 2.75    |       | Option 1 (CMOS )                            |
|                                   |                 | 1.62                                                            | 1.8     | 1.98    |       | Option 2 (CMOS)                             |
| Supply Current (I <sub>dd</sub> ) | Vdd = 3.3 V     | ----                                                            | 2.0     | 5.0     | mA    | 1MHz ≤ F ≤ 20 MHz                           |
|                                   |                 | ----                                                            | 4.0     | 10.0    |       | 20 MHz < F ≤ 50 MHz                         |
|                                   |                 | ----                                                            | 7.0     | 15.0    |       | 50 MHz < F ≤ 80 MHz                         |
|                                   | Vdd = 2.5 V     | ----                                                            | 2.0     | 5.0     |       | 1MHz ≤ F ≤ 20 MHz                           |
|                                   |                 | ----                                                            | 3.0     | 10.0    |       | 20 MHz < F ≤ 50 MHz                         |
|                                   |                 | ----                                                            | 5.0     | 10.0    |       | 50 MHz < F ≤ 80 MHz                         |
|                                   | Vdd = 1.8 V     | ----                                                            | 1.5     | 5.0     |       | 1MHz ≤ F ≤ 20 MHz                           |
|                                   |                 | ----                                                            | 2.5     | 5.0     |       | 20 MHz < F ≤ 50 MHz                         |
|                                   |                 | ----                                                            | 4.0     | 10.0    |       | 50 MHz < F ≤ 80 MHz                         |
|                                   | Output Load     | ----                                                            | ----    | 15      | pF    |                                             |
|                                   |                 | ----                                                            | ----    | 2       | TTL   |                                             |
| Output Voltage                    | V <sub>OH</sub> | 0.9*Vdd                                                         | ----    | ----    | V     | CMOS                                        |
|                                   | V <sub>OL</sub> | ----                                                            | ----    | 0.1*Vdd |       | CMOS                                        |
|                                   | V <sub>OH</sub> | 2.4                                                             | ----    | ----    |       | TTL                                         |
|                                   | V <sub>OL</sub> | ----                                                            | ----    | 0.4     |       | TTL                                         |
| Tri-state function                |                 | "1" (VIH ≥ 0.7*Vdd) : Oscillation<br>"0" (VIH < 0.3*Vdd) : Hi Z |         |         |       | Pin 1 must be pulled "high" for oscillation |
| Aging                             |                 | -3.0                                                            | ----    | +3.0    | ppm   | @+25°C First year                           |
| Symmetry @1/2Vdd                  |                 | 40                                                              | 50      | 60      | %     | Standard                                    |
|                                   |                 | 45                                                              | 50      | 55      |       | Option S                                    |
| Start-up Time                     |                 |                                                                 |         | 10.0    | ms    |                                             |
| Rise/Fall Time (Tr/Tf)            |                 |                                                                 |         | 10.0    | ns    |                                             |

\*Overall frequency stability includes initial frequency tolerance @+25°C and stability over the operating temperature.

### OPTIONS AND PART IDENTIFICATION:

(Left blank if standard)

ASA  -  MHz -  -  -  -

| Supply Voltage  |
|-----------------|
| Blank: 3.3V±10% |
| 1: 2.5 V±10%    |
| 2: 1.8 V±10%    |

| Packaging               |
|-------------------------|
| Blank: Bulk             |
| T: Tape & Reel (1kpcs)  |
| T3: Tape & Reel (3kpcs) |

| Frequency in MHz                                         |
|----------------------------------------------------------|
| Please specify the frequency in MHz.<br>e.g. 14.31818MHz |

| Operating Temp.      |
|----------------------|
| Blank: -10°C ~ +60°C |
| E: -20°C ~ +70°C     |
| L: -40°C ~ +85°C     |

| Overall Freq. Stability |
|-------------------------|
| Blank: ±50ppm           |
| R**: ±25ppm             |
| K***: ±30 ppm           |

| Symmetry              |
|-----------------------|
| Blank: 40/60% @1/2Vdd |
| S: 45/55% @1/2Vdd     |

\*\*Available for -10 to +60°C only

\*\*\*Available for -10 to +60°C, option E only

Contact Abracon for tighter frequency stability options

ABRACON IS  
ISO9001:2008  
CERTIFIED



**ABRACON**  
CORPORATION

Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale **Revised: 03.12.12**

30332 Esperanza, Rancho Santa Margarita, California 92688

tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)

# HCMOS SURFACE-MOUNT CRYSTAL CLOCK OSCILLATOR

ASA SERIES




RoHS  
Compliant




2.0 x 1.6 x 0.7mm

## OUTLINE DRAWING:



Recommended land pattern




Dimensions: inches (mm)

| PIN # | Name                 |
|-------|----------------------|
| 1     | Tri-state (Stand-by) |
| 2     | GND                  |
| 3     | Output               |
| 4     | Vdd                  |


## TAPE & REEL:

T= Tape and reel (1,000pcs/reel)  
T3= Tape and reel (3,000pcs/reel)



Dimensions: mm

## REFLOW PROFILE:



Need a test socket for the ASA Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, [click here](#).

**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO9001:2008  
CERTIFIED



Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale **Revised: 03.12.12**

30332 Esperanza, Rancho Santa Margarita, California 92688

tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9