


# 1500W Transient Voltage Suppressor

## 1.5KE-G Series

**Breakdown Voltage: 6.8 to 600 Volts**

**Peak Pulse Power: 1500 Watts**

**RoHS Device**




### Features

- Glass passivated chip.
- 1500W peak pulse power capability with a 10/1000 $\mu$ s waveform, repetitive rate (duty cycle):0.01%
- Low leakage.
- Uni and Bidirectional unit.
- Excellent clamping capability.
- Very fast response time.
- UL recognized file # E349157   
Range: 1.5KE6.8(C)A thru. 1.5KE120(C)A

### Mechanical Data

- Case: Molded plastic DO-201
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Solderable per MIL-STD-202, method 208 guaranteed.
- Polarity: Color band denotes cathode end except Bipolar.
- Mounting position: Any
- Weight: 0.844 gram (approx.)



### Maximum Ratings (TA=25°C unless otherwise noted)

| Parameter                                                                                           | Symbol   | Value          | Unit |
|-----------------------------------------------------------------------------------------------------|----------|----------------|------|
| Peak power dissipation with a 10/1000 $\mu$ s waveform (Note 1)                                     | PPP      | 1500           | W    |
| Peak pulse current with a 10/1000 $\mu$ s waveform (Note 1)                                         | IPP      | See Next Table | A    |
| Power dissipation on infinite heatsink at TL=75°C                                                   | PD       | 6.5            | W    |
| Peak forward surge current, 8.3ms single half sine-wave unidirectional only (JEDEC method) (Note 2) | IFSM     | 200            | A    |
| Maximum instantaneous forward voltage at 100 A for unidirectional only (Note 3)                     | VF       | 3.5/5.0        | V    |
| Operating junction and storage temperature range                                                    | TJ, TSTG | -55 to +150    | °C   |

NTOES:

(1) Non-repetitive current pulse, per fig.5 and derated above TA=25°C per fig.1

(2) Measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum

(3) VF<3.5V for devices of VBR<200V and VF<5.0V for devices of VBR>201V

Company reserves the right to improve product design , functions and reliability without notice.

## RATING AND CHARACTERISTIC CURVES (1.5KE6.8-G Thru. 1.5KE600-G)

Fig.1 - Pulse Derating Curve




Fig.2 - Max. Non-repetitive Surge Current




Fig.3 - Steady State Power Derating Curve




Fig.4 - Peak Pulse Power Rating Curve




Fig.5 - Pulse Waveform





Fig.6 - Typical Junction Capacitance



Company reserves the right to improve product design , functions and reliability without notice.

# 1500W Transient Voltage Suppressor

## Electrical Characteristics (1.5KE6.8-G Thru. 1.5KE600-G)

| Part No.       | Breakdown voltage<br>VBR @ IT |             |            | Maximum<br>Reverse<br>Leakage<br>@VRWM<br>IR (uA) | Working<br>Peak<br>Reverse<br>Voltage<br>VRWM (V) | Maximum<br>Reverse<br>Surge<br>Current<br>IPP (A) | Maximum<br>Clamping<br>Voltage<br>@IPP<br>Vc (V) | Marking Code |            |
|----------------|-------------------------------|-------------|------------|---------------------------------------------------|---------------------------------------------------|---------------------------------------------------|--------------------------------------------------|--------------|------------|
|                | Min.<br>(V)                   | Max.<br>(V) | IT<br>(mA) |                                                   |                                                   |                                                   |                                                  | UNI          | BI         |
| 1.5KE6.8(C)A-G | 6.46                          | 7.14        | 10         | 1000                                              | 5.8                                               | 142.86                                            | 10.5                                             | 1.5KE6.8A    | 1.5KE6.8CA |
| 1.5KE7.5(C)A-G | 7.13                          | 7.88        | 10         | 500                                               | 6.4                                               | 132.74                                            | 11.3                                             | 1.5KE7.5A    | 1.5KE7.5CA |
| 1.5KE8.2(C)A-G | 7.79                          | 8.61        | 10         | 200                                               | 7.0                                               | 123.97                                            | 12.1                                             | 1.5KE8.2A    | 1.5KE8.2CA |
| 1.5KE9.1(C)A-G | 8.65                          | 9.56        | 1.0        | 50                                                | 7.8                                               | 111.94                                            | 13.4                                             | 1.5KE9.1A    | 1.5KE9.1CA |
| 1.5KE10(C)A-G  | 9.50                          | 10.50       | 1.0        | 10                                                | 8.6                                               | 103.45                                            | 14.5                                             | 1.5KE10A     | 1.5KE10CA  |
| 1.5KE11(C)A-G  | 10.45                         | 11.55       | 1.0        | 5.0                                               | 9.4                                               | 96.15                                             | 15.6                                             | 1.5KE11A     | 1.5KE11CA  |
| 1.5KE12(C)A-G  | 11.40                         | 12.60       | 1.0        | 5.0                                               | 10.2                                              | 89.82                                             | 16.7                                             | 1.5KE12A     | 1.5KE12CA  |
| 1.5KE13(C)A-G  | 12.35                         | 13.65       | 1.0        | 1.0                                               | 11.1                                              | 82.42                                             | 18.2                                             | 1.5KE13A     | 1.5KE13CA  |
| 1.5KE15(C)A-G  | 14.25                         | 15.75       | 1.0        | 1.0                                               | 12.8                                              | 70.75                                             | 21.2                                             | 1.5KE15A     | 1.5KE15CA  |
| 1.5KE16(C)A-G  | 15.20                         | 16.80       | 1.0        | 1.0                                               | 13.6                                              | 66.67                                             | 22.5                                             | 1.5KE16A     | 1.5KE16CA  |
| 1.5KE18(C)A-G  | 17.10                         | 18.90       | 1.0        | 1.0                                               | 15.3                                              | 59.52                                             | 25.2                                             | 1.5KE18A     | 1.5KE18CA  |
| 1.5KE20(C)A-G  | 19.00                         | 21.00       | 1.0        | 1.0                                               | 17.1                                              | 54.15                                             | 27.7                                             | 1.5KE20A     | 1.5KE20CA  |
| 1.5KE22(C)A-G  | 20.90                         | 23.10       | 1.0        | 1.0                                               | 18.8                                              | 49.02                                             | 30.6                                             | 1.5KE22A     | 1.5KE22CA  |
| 1.5KE24(C)A-G  | 22.80                         | 25.20       | 1.0        | 1.0                                               | 20.5                                              | 45.18                                             | 33.2                                             | 1.5KE24A     | 1.5KE24CA  |
| 1.5KE27(C)A-G  | 25.65                         | 28.35       | 1.0        | 1.0                                               | 23.1                                              | 40.00                                             | 37.5                                             | 1.5KE27A     | 1.5KE27CA  |
| 1.5KE30(C)A-G  | 28.50                         | 31.50       | 1.0        | 1.0                                               | 25.6                                              | 36.23                                             | 41.4                                             | 1.5KE30A     | 1.5KE30CA  |
| 1.5KE33(C)A-G  | 31.35                         | 34.65       | 1.0        | 1.0                                               | 28.2                                              | 32.82                                             | 45.7                                             | 1.5KE33A     | 1.5KE33CA  |
| 1.5KE36(C)A-G  | 34.20                         | 37.80       | 1.0        | 1.0                                               | 30.8                                              | 30.06                                             | 49.9                                             | 1.5KE36A     | 1.5KE36CA  |
| 1.5KE39(C)A-G  | 37.05                         | 40.95       | 1.0        | 1.0                                               | 33.3                                              | 27.83                                             | 53.9                                             | 1.5KE39A     | 1.5KE39CA  |
| 1.5KE43(C)A-G  | 40.85                         | 45.15       | 1.0        | 1.0                                               | 36.8                                              | 25.30                                             | 59.3                                             | 1.5KE43A     | 1.5KE43CA  |
| 1.5KE47(C)A-G  | 44.65                         | 49.35       | 1.0        | 1.0                                               | 40.2                                              | 23.15                                             | 64.8                                             | 1.5KE47A     | 1.5KE47CA  |
| 1.5KE51(C)A-G  | 48.45                         | 53.55       | 1.0        | 1.0                                               | 43.6                                              | 21.40                                             | 70.1                                             | 1.5KE51A     | 1.5KE51CA  |
| 1.5KE56(C)A-G  | 53.20                         | 58.80       | 1.0        | 1.0                                               | 47.8                                              | 19.48                                             | 77.0                                             | 1.5KE56A     | 1.5KE56CA  |
| 1.5KE62(C)A-G  | 58.90                         | 65.10       | 1.0        | 1.0                                               | 53.0                                              | 17.65                                             | 85.0                                             | 1.5KE62A     | 1.5KE62CA  |
| 1.5KE68(C)A-G  | 64.60                         | 71.40       | 1.0        | 1.0                                               | 58.1                                              | 16.30                                             | 92.0                                             | 1.5KE68A     | 1.5KE68CA  |
| 1.5KE75(C)A-G  | 71.25                         | 78.75       | 1.0        | 1.0                                               | 64.1                                              | 14.56                                             | 103.0                                            | 1.5KE75A     | 1.5KE75CA  |
| 1.5KE82(C)A-G  | 77.90                         | 86.10       | 1.0        | 1.0                                               | 70.1                                              | 13.27                                             | 113.0                                            | 1.5KE82A     | 1.5KE82CA  |
| 1.5KE91(C)A-G  | 86.45                         | 95.55       | 1.0        | 1.0                                               | 77.8                                              | 12.00                                             | 125.0                                            | 1.5KE91A     | 1.5KE91CA  |
| 1.5KE100(C)A-G | 95.00                         | 105.00      | 1.0        | 1.0                                               | 85.5                                              | 10.95                                             | 137.0                                            | 1.5KE100A    | 1.5KE100CA |
| 1.5KE110(C)A-G | 104.50                        | 115.50      | 1.0        | 1.0                                               | 94.0                                              | 9.87                                              | 152.0                                            | 1.5KE110A    | 1.5KE110CA |
| 1.5KE120(C)A-G | 114.00                        | 126.00      | 1.0        | 1.0                                               | 102.0                                             | 9.09                                              | 165.0                                            | 1.5KE120A    | 1.5KE120CA |
| 1.5KE130(C)A-G | 123.50                        | 136.50      | 1.0        | 1.0                                               | 111.0                                             | 8.38                                              | 179.0                                            | 1.5KE130A    | 1.5KE130CA |
| 1.5KE150(C)A-G | 142.50                        | 157.50      | 1.0        | 1.0                                               | 128.0                                             | 7.25                                              | 207.0                                            | 1.5KE150A    | 1.5KE150CA |
| 1.5KE160(C)A-G | 152.00                        | 168.00      | 1.0        | 1.0                                               | 136.0                                             | 6.85                                              | 219.0                                            | 1.5KE160A    | 1.5KE160CA |
| 1.5KE170(C)A-G | 161.50                        | 178.50      | 1.0        | 1.0                                               | 145.0                                             | 6.41                                              | 234.0                                            | 1.5KE170A    | 1.5KE170CA |
| 1.5KE180(C)A-G | 171.00                        | 189.00      | 1.0        | 1.0                                               | 154.0                                             | 6.10                                              | 246.0                                            | 1.5KE180A    | 1.5KE180CA |
| 1.5KE200(C)A-G | 190.00                        | 210.00      | 1.0        | 1.0                                               | 171.0                                             | 5.47                                              | 274.0                                            | 1.5KE200A    | 1.5KE200CA |
| 1.5KE220(C)A-G | 209.00                        | 231.00      | 1.0        | 1.0                                               | 185.0                                             | 4.57                                              | 328.0                                            | 1.5KE220A    | 1.5KE220CA |
| 1.5KE250(C)A-G | 237.50                        | 262.50      | 1.0        | 1.0                                               | 214.0                                             | 4.36                                              | 344.0                                            | 1.5KE250A    | 1.5KE250CA |
| 1.5KE300(C)A-G | 285.00                        | 315.00      | 1.0        | 1.0                                               | 256.0                                             | 3.62                                              | 414.0                                            | 1.5KE300A    | 1.5KE300CA |
| 1.5KE350(C)A-G | 332.50                        | 367.50      | 1.0        | 1.0                                               | 299.3                                             | 3.11                                              | 482.0                                            | 1.5KE350A    | 1.5KE350CA |
| 1.5KE380(C)A-G | 361.00                        | 399.00      | 1.0        | 1.0                                               | 324.9                                             | 2.86                                              | 524.4                                            | 1.5KE380A    | 1.5KE380CA |
| 1.5KE400(C)A-G | 380.00                        | 420.00      | 1.0        | 1.0                                               | 342.0                                             | 2.72                                              | 548.0                                            | 1.5KE400A    | 1.5KE400CA |
| 1.5KE440(C)A-G | 418.00                        | 462.00      | 1.0        | 1.0                                               | 376.2                                             | 2.47                                              | 602.0                                            | 1.5KE440A    | 1.5KE440CA |
| 1.5KE500(C)A-G | 475.00                        | 525.00      | 1.0        | 1.0                                               | 427.5                                             | 2.17                                              | 690.0                                            | 1.5KE500A    | 1.5KE500CA |
| 1.5KE520(C)A-G | 494.00                        | 546.00      | 1.0        | 1.0                                               | 444.6                                             | 2.09                                              | 717.6                                            | 1.5KE520A    | 1.5KE520CA |
| 1.5KE550(C)A-G | 522.50                        | 577.50      | 1.0        | 1.0                                               | 470.3                                             | 1.98                                              | 759.0                                            | 1.5KE550A    | 1.5KE550CA |
| 1.5KE600(C)A-G | 570.00                        | 630.00      | 1.0        | 1.0                                               | 513.0                                             | 1.81                                              | 828.0                                            | 1.5KE600A    | 1.5KE600CA |

Note: 1) Suffix A denotes 5% tolerance devices.


2) Add suffix "C" or "CA" after part number to specify Bi-directional devices.

3) For Bi-Directional devices having VR of 10 volts and under, the IR limit is double.

Company reserves the right to improve product design , functions and reliability without notice.

REV:D

## Taping Specification For Axial Lead Diodes



| DO-201 | SYMBOL | A                 | B                 | Z           | T                 | E           | L1          | L2          |
|--------|--------|-------------------|-------------------|-------------|-------------------|-------------|-------------|-------------|
|        | (mm)   | $10.00 \pm 0.50$  | $52.00 \pm 0.50$  | 1.20 (max)  | $6.00 \pm 0.40$   | 1.00 (max)  | 1.00 (max)  | 1.00 (max)  |
|        | (inch) | $0.394 \pm 0.020$ | $2.047 \pm 0.020$ | 0.047 (max) | $0.236 \pm 0.016$ | 0.039 (max) | 0.039 (max) | 0.039 (max) |

| DO-201 | SYMBOL | D1                | D0                | D      | W0                | L      | W     | H      |
|--------|--------|-------------------|-------------------|--------|-------------------|--------|-------|--------|
|        | (mm)   | $85.70 \pm 0.30$  | $16.60 \pm 0.40$  | 330.00 | $72.00 \pm 3.00$  | 260.00 | 75.00 | 145.00 |
|        | (inch) | $3.374 \pm 0.012$ | $0.654 \pm 0.016$ | 13.000 | $2.835 \pm 0.118$ | 10.236 | 2.953 | 5.709  |

Company reserves the right to improve product design , functions and reliability without notice.

## Standard Packaging

| Packaging | Code | Part Number     |
|-----------|------|-----------------|
| AMMO PACK | NA   | 1.5KEXXX(C)A-G  |
| REEL PACK | T    | 1.5KEXXX(C)AT-G |
| BULK PACK | B    | 1.5KEXXX(C)AB-G |

Note: (1)Suffix code after part number to specify packaging item.  
(2)XXX on behalf of serial products.

| Case Type | REEL PACK       |                     |
|-----------|-----------------|---------------------|
|           | REEL<br>( pcs ) | Reel Size<br>(inch) |
| DO-201AD  | 1,200           | 13                  |

| Case Type | AMMO PACK      |                   |
|-----------|----------------|-------------------|
|           | BOX<br>( pcs ) | CARTON<br>( pcs ) |
| DO-201AD  | 1,000          | 10,000            |

| Case Type | BULK PACK      |                   |
|-----------|----------------|-------------------|
|           | BOX<br>( pcs ) | CARTON<br>( pcs ) |
| DO-201AD  | 200            | 10,000            |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9