


FLORENTINA-2X2-D

~18° diffused spot beam

TECHNICAL SPECIFICATIONS:

Dimensions	89.6 mm
Height	22.2 mm
Fastening	pin, screw
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ROSE-CMC-D	Single lens	PC	clear	
FLORENTINA-2X2-HLD	Holder	PC	black	











ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCP14966_FLORENTINA-2X2-D	Single lens	88	24	8	4.3
» Box size: 476 x 273 x 292 mm					



PHOTOMETRIC DATA (MEASURED):

<p>COMET ELECTRONICS</p> <p>LED EASY-T FLUX 2x2 FLR XG xxx G7 FWHM 18.0° Efficiency 83 % Peak intensity 6.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>COMET ELECTRONICS</p> <p>LED EASY-T FLUX 2x2 FLR XT xxx G5 FWHM 16.0° Efficiency 84 % Peak intensity 7.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>CREE</p> <p>LED XHP35 HD FWHM 21.0° Efficiency 80 % Peak intensity 4.7 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>CREE</p> <p>LED XHP35 HD FWHM 21.0° Efficiency 80 % Peak intensity 4.7 cd/lm LEDs/each optic 1 Light colour White Required components: C15196_FLORENTINA-2X2-SHD-OPEN</p>		



PHOTOMETRIC DATA (MEASURED):



LED XP-L HD
FWHM 19.0°
Efficiency 77 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14960_FLORENTINA-2X2-SHD-WHT




LED XP-L HD
FWHM 19.0°
Efficiency 77 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14734_FLORENTINA-2X2-SHD



LED XP-L HD
FWHM 19.0°
Efficiency 77 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15196_FLORENTINA-2X2-SHD-OPEN




LED LUXEON MZ
FWHM 20.0°
Efficiency 78 %
Peak intensity 5.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15196_FLORENTINA-2X2-SHD-OPEN



PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED LUXEON MZ
 FWHM 20.0°
 Efficiency 80 %
 Peak intensity 5.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14960_FLORENTINA-2X2-SHD-WHT




LUMILEDS

LED LUXEON MZ
 FWHM 20.0°
 Efficiency 78 %
 Peak intensity 5.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD



LUMILEDS









LED LUXEON TX
 FWHM 15.0°
 Efficiency 82 %
 Peak intensity 8.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD



LUMILEDS

LED LUXEON TX
 FWHM 15.0°
 Efficiency 82 %
 Peak intensity 8.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C15196_FLORENTINA-2X2-SHD-OPEN

PHOTOMETRIC DATA (MEASURED):



<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM 18.0° Efficiency 81 % Peak intensity 6.8 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM 18.0° Efficiency 81 % Peak intensity 6.8 cd/lm LEDs/each optic 1 Light colour White Required components: C15196_FLORENTINA-2X2-SHD-OPEN</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLOM Square CSSRM2/CSSRM3 FWHM 15.0° Efficiency 76 % Peak intensity 8.3 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLOM Square CSSRM2/CSSRM3 FWHM 15.0° Efficiency 77 % Peak intensity 8.3 cd/lm LEDs/each optic 1 Light colour White Required components: C14960_FLORENTINA-2X2-SHD-WHT</p>		

PHOTOMETRIC DATA (MEASURED):

OSRAM

Opto Semiconductors

LED OSLOM Square EC
FWHM 15.0°
Efficiency 81 %
Peak intensity 8.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14734_FLORENTINA-2X2-SHD





OSRAM

Opto Semiconductors

LED OSLOM Square EC
FWHM 15.0°
Efficiency 81 %
Peak intensity 8.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15196_FLORENTINA-2X2-SHD-OPEN

SAMSUNG

LED HiLOM SC16 (LH181B)
FWHM 32.0°
Efficiency 65 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14734_FLORENTINA-2X2-SHD



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

www.ledil.com/where_to_buy

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

www.ledil.com/where_to_buy

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9