Features

- Carbon element
- Metal housing
- 15-60 mm travel
- Single and dual gang
- Center detent option
- Dust cover option
- RoHS compliant*

BOURNS® PRO AUDIO

PTA Series - Low Profile Slide Potentiometer

Electrical Characteristics

Taper ..... Linear, audio
Standard Resistance Range
..... 1 K ohms to 1 M ohms
Standard Resistance Tolerance..... ±20 %
Residual Resistance
..... 500 ohms or 1 % max.
Insulation Resistance
..... Min. 100 megohms at 250 V DC

Environmental Characteristics

Operating Temperature
..... -10 °C to +50 °C
Power Rating, Linear
15 mm .... 0.05 W (0.025 W Dual Gang)
20 mm ..... 0.1 W (0.05 W)
30 mm ..... 0.2 W (0.1 W)
45 mm ..... 0.25 W (0.125 W)
60 mm ..... 0.25 W (0.125 W)
Power Rating, Audio
15 mm .. 0.025 W (0.015 W Dual Gang)
20 mm ..... 0.05 W (0.025 W)
30 mm ..... 0.1 W (0.05 W)
45 mm ..... 0.125 W (0.06 W)
60 mm ..... 0.125 W (0.06 W)
Maximum Operating Voltage, Linear
15 mm ..... 100 V DC
20-60 mm ..... 200 V DC
Maximum Operating Voltage, Audio
15 mm ..... 50 V DC
20-60 mm ..... 150 V DC
Withstand Voltage, Audio
..... 1 Min. at 300 V AC
Sliding Noise ..... 100 mV maximum
Tracking Error ..... 3 dB at -40 to 0 dB

Mechanical Characteristics

Operating Force ..... 30 to 250 g-cm
Stop Strength ..... 5 kg-cm min.
Sliding Life ..... 15,000 cycles
Soldering Condition
..... 300 °C max. within 3 seconds
Travel ..... 15, 20, 30, 45, 60 mm

Derating Curve



Lever Style & Product Dimensions

Actuator Styles

DP METAL LEVER



CP METAL LEVER



CI INSULATED LEVER



DIMENSIONS: MM / (INCHES)

How To Order

PTA 15 4 3 - 2 0 10 DP B 203

Model
Stroke Length
- 15 = 15 mm
- 20 = 20 mm
- 30 = 30 mm
- 45 = 45 mm
- 60 = 60 mm

Dust Cover Option
- 4 = No Dust Cover
- 5 = Rubber Dust Cover**

No. of Gangs
- 3 = Single Gang
- 4 = Dual Gang

Pin Style
- 2 = PC Pins Down Facing

Center Detent Option
- 0 = No Detent
- 2 = Center Detent

Standard Lever Length (See Table)
- 10 = 10 mm (CI Lever)
- 15 = 15 mm (DP, CP and CI)

Lever Style
- DP = Metal Lever (Refer to Drawing)
- CP = Metal Lever (Refer to Drawing)
- CI = Insulated Lever (Refer to Drawing)

Resistance Taper
- A = Audio Taper
- B = Linear Taper

Resistance Code (See Table)

Other styles available.

** Part numbers with dust covers must be mounted with screws to a panel to prevent issues with the dust cover during usage.

Standard Resistance Table

Resistance (Ohms)	Resistance Code
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
500,000	504
1,000,000	105

Optional Dust Cover



NOTE: DUST COVER HAS ADHESIVE BACK. T = 0.3 ± 0.1 / (.0118 ± .004)

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.
Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Applications

- Audio/TV sets
- Car radio
- Amplifiers/mixers/drum machines/synthesizers
- PCs/monitors
- Appliances

PTA Series - Low Profile Slide Potentiometer

BOURNS®

Product Dimensions

PTAxx43



PTAxx44



DIMENSIONS: MM / (INCHES)

Single Gang Dimensions

Model	A	B	C	D	E	Travel
PTA1543	30 (3.18)	26 (1.02)	17.8 (.700)	20.2 (.795)	28.5 (1.12)	15 (.59)
PTA2043	35 (1.37)	31 (1.22)	22.8 (.897)	25.2 (.992)	33 (1.29)	20 (.787)
PTA3043	45 (1.77)	41 (1.61)	32.8 (1.29)	35.2 (1.38)	43.5 (1.71)	30 (1.18)
PTA4543	60 (2.36)	56 (2.20)	47.8 (1.88)	50.2 (1.97)	58.5 (2.30)	45 (1.77)
PTA6043	75 (2.95)	71 (2.79)	62.8 (2.47)	65.2 (2.56)	73.5 (2.89)	60 (2.36)



Dual Gang Dimensions

Model	A	B	C	D	E	F	Travel
PTA1544	30 (3.18)	26 (1.02)	17.8 (.700)	20.2 (.795)	28.5 (1.12)	18 (.708)	15 (.59)
PTA2044	35 (1.37)	31 (1.22)	22.8 (.897)	25.2 (.992)	33 (1.29)	23 (.905)	20 (.787)
PTA3044	45 (1.77)	41 (1.61)	32.8 (1.29)	35.2 (1.38)	43.5 (1.71)	33 (1.29)	30 (1.18)
PTA4544	60 (2.36)	56 (2.20)	47.8 (1.88)	50.2 (1.97)	58.5 (2.30)	48 (1.88)	45 (1.77)
PTA6044	75 (2.95)	71 (2.79)	62.8 (2.47)	65.2 (2.56)	73.5 (2.89)	63 (2.48)	60 (2.36)



REV. 10/12

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9