



For more Information  
please call

1-800-Belden1



### Description:

18 AWG bare copper conductors, PP insulation, PVC jacket with ripcord. Sequential footage marking every two feet.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 4            | 18  | 7x26      | BC - Bare Copper   |

#### Insulation

##### Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|---------------------|---------------------|
| PP - Polypropylene  | 0.178               |

#### Outer Shield

##### Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

#### Outer Jacket

##### Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.432                    |

Outer Jacket Ripcord: Yes

### Overall Cabling

#### Overall Cabling Lay Length & Direction:

| Length (mm) | Twists (m.) |
|-------------|-------------|
| 101.5996    | 0.9144      |

#### Overall Cabling Color Code Chart:

| Color |
|-------|
| Black |
| Red   |
| White |
| Green |

Overall Nominal Diameter: 4.547 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 40.181 Kg/Km

Max. Recommended Pulling Tension: 398.559 N

Min. Bend Radius (Install)/Minor Axis: 45.720 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

|                                       |            |
|---------------------------------------|------------|
| NEC/(UL) Specification:               | CMR        |
| NEC Articles:                         | 800        |
| CEC/C(UL) Specification:              | CMG        |
| EU CE Mark:                           | Yes        |
| EU Directive 2000/53/EC (ELV):        | Yes        |
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |
| EU Directive 2003/11/EC (BFR):        | Yes        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes        |
| MII Order #39 (China RoHS):           | Yes        |

#### Flame Test

|                   |                       |
|-------------------|-----------------------|
| UL Flame Test:    | UL1666 Vertical Shaft |
| C(UL) Flame Test: | FT4                   |

#### Plenum/Non-Plenum

|                |        |
|----------------|--------|
| Plenum Number: | 6302UE |
|----------------|--------|

### Electrical Characteristics (Overall)

#### Nom. Capacitance Conductor to Conductor:

|                    |
|--------------------|
| Capacitance (pF/m) |
| 72.182             |

#### Nom. Conductor DC Resistance:

|                     |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 21.3265             |

#### Max. Operating Voltage - UL:

|           |
|-----------|
| Voltage   |
| 300 V RMS |

#### Max. Recommended Current:

|                             |
|-----------------------------|
| Current                     |
| 4 Amps per conductor @ 25°C |

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

| Item #          | Putup  | Ship Weight | Color | Notes | Item Desc      |
|-----------------|--------|-------------|-------|-------|----------------|
| 5302UE 008U1000 | 305 MT | 13.154 KG   | GRAY  |       | 4 #18 PP FRPVC |
| 5302UE 008U500  | 152 MT | 7.031 KG    | GRAY  |       | 4 #18 PP FRPVC |
| 5302UE 0081000  | 305 MT | 13.608 KG   | GRAY  | C     | 4 #18 PP FRPVC |
| 5302UE 008500   | 152 MT | 6.804 KG    | GRAY  |       | 4 #18 PP FRPVC |

#### Notes:

C = CRATE REEL PUT-UP.

## 5302UE Multi-Conductor - Commercial Applications

Revision Number: 2    Revision Date: 06-02-2008

© 2011 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9