

VIP-3/SC/D37SUB/M

Order No.: 2315146

The illustration shows version VIP-3/SC/D50SUB/M



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315146

VARIOFACE module, with screw connection and male D-Subminiature pin strip, for mounting on NS 35/7.5 or NS 32, 37-pos.



Commercial data EAN 4046356313315 Pack 1 Pcs. 85369010 Customs tariff Weight/Piece 0.2034 KG Page 191 (NTK-2008) Catalog page information



09/02/2008

Product notes WEEE/RoHS-compliant since:



http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U _N	125 V AC/DC
Max. current carrying capacity per branch	2 A
Number of positions	37
Length	69 mm

NAC-JAL	70.7
Width	72.7 mm
Height	62 mm
Status display	No
Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-20 °C 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Pollution degree	2
Surge voltage category	II .
Connection data	
Connection 1	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	4 mm²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M 3
Connection 2	D-SUB connection
Number of positions	37
Certificates / Approvals	
Certification	CUL, UL
CUL	
Nominal voltage U _N	125 V
Nominal current I _N	2 A
AWG/kcmil	30-12
UL	
Nominal voltage U _N	125 V

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315146

Nominal current I _N AWG/kcmil		2 A 30-12		
			Accessories	
Item	Designation	Description		
Cable/cond	uctor			
2302421	CABLE D-SUB-B-B-S//	Shielded round cable, assembled with two D-SUB female connectors, variable cable length		
2302421	CABLE D-SUB-B-B-S//	Shielded round cable, assembled with two D-SUB female connectors, variable cable length		
2302340	CABLE D-SUB-S//	Shielded round cable, assembled with one D-SUB male and one female connector, variable cable length		
2305509	CABLE-D37SUB/B/B/100/ KONFEK/S	Assembled, shielded circular cable, with D-SUB socket strip, 37 pos. from both sides, cable length: 1m		
2305512	CABLE-D37SUB/B/B/200/ KONFEK/S	Assembled, shielded circular cable, with D-SUB socket strip, 37 pos. from both sides, cable length: 2m		
2305525	CABLE-D37SUB/B/B/300/ KONFEK/S	Assembled, shielded circular cable, with D-SUB socket strip, 37 pos. from both sides, cable length: 3 m		
2302191	CABLE-D37SUB/B/S/ 50/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 0.5 m		
2302201	CABLE-D37SUB/B/S/100/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 1 m		
2302214	CABLE-D37SUB/B/S/150/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 1.5 m		
2302227	CABLE-D37SUB/B/S/200/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 2 m		
2302230	CABLE-D37SUB/B/S/300/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 3 m		
2302243	CABLE-D37SUB/B/S/400/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 4 m		
2302256	CABLE-D37SUB/B/S/600/ KONFEK/S	Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 6 m		
General				
5147777	BLUEMARK X1	Printer, Weight: 20 kg, Length: 540 mm, Width: 335 mm, Height: 480 mm, Color: gray		

UC-TM 4

Marking 0818111

UniCard sheets, for labeling terminal blocks using a Zack marker strip groove, 120-section, can be labeled with BLUEMARK X1 and

CMS-P1-PLOTTER, color: White

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315146

0818085	UC-TM 6	UniCard sheets, for labeling terminal blocks using Zack marker strip groove,80-section, labeling with BLUEMARK X1 and CMS-P1-PLOTTER, color: White
0811862	ZB 22:UNBEDRUCKT	Zack marker strip, unprinted: 4-section, for individual labeling with M-PEN, ZB-T or CMS system, sufficient for 100 terminal blocks, for a terminal width of 22 mm, color: White
0809793	ZB 5,08:UNBEDRUCKT	Zack strip, unprinted: 10-section, for individual labeling with M-PEN, ZB-T or CMS system, sufficient for 100 terminal blocks per pack

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315146

Address

PHOENIX CONTACT Inc., USA 586 Fulling Mill Road Middletown, PA 17057,USA Phone (800) 888-7388 Fax (717) 944-1625 http://www.phoenixcon.com



© 2008 Phoenix Contact Technical modifications reserved;

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru 4 moschip.ru 9