

MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574 3.3V Output-Voltage Application

General Description

The MAX17574 3.3V output evaluation kit (EV kit) provides a proven design to evaluate the MAX17574 high-voltage, high-efficiency, synchronous step-down DC-DC converter. The EV kit is preset for 3.3V output at load currents up to 3A and features a 500kHz switching frequency for optimum efficiency and component size. The EV kit features adjustable input undervoltage lockout, adjustable soft-start, open-drain $\overline{\text{RESET}}$ signal, and external frequency synchronization.

Features

- Operates from a 5V to 60V Input Supply
- 3.3V Output Voltage
- Up to 3A Output Current
- 500kHz Switching Frequency
- Enable/UVLO Input, Resistor-Programmable UVLO Threshold
- Adjustable Soft-Start Time
- MODE/SYNC Pin to Select Among PWM, PFM, or DCM Modes
- Open-Drain RESET Output
- External Frequency Synchronization
- Overcurrent and Overtemperature Protection
- Proven PCB Layout
- Fully Assembled and Tested

Ordering Information appears at end of data sheet.

Quick Start

Recommended Equipment

- MAX17574 3.3V output EV kit
- 5V to 60V, 5A DC input power supply
- Load capable of sinking 3A
- Digital voltmeter (DVM)

Procedure

The EV kit is fully assembled and tested. Follow the steps below to verify the board operation. **Caution: Do not turn on power supply until all connections are completed.**

- 1) Set the power supply at a voltage between 5V and 60V. Disable the power supply.
- 2) Connect the positive terminal of the power supply to the VIN PCB pad and the negative terminal to the nearest PGND PCB pad. Connect the positive terminal of the 3A load to the VOUT PCB pad and the negative terminal to the nearest PGND PCB pad.
- 3) Connect the DVM across the VOUT PCB pad and the nearest PGND PCB pad.
- 4) Verify that shunts are installed across pins 1-2 on jumper JU1 (see [Table 1](#) for details).
- 5) Select the shunt position on jumper JU2 according to the intended MODE/SYNC of operation (see [Table 2](#) for details).
- 6) Turn on the DC power supply.
- 7) Enable the load.
- 8) Verify that the DVM displays 3.3V.

MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574 3.3V Output-Voltage Application

Detailed Description

The MAX17574 3.3V output EV kit provides a proven design to evaluate the MAX17574 high-voltage, high-efficiency, synchronous step-down DC-DC converter. The EV kit is preset for 3.3V output from 5V to 60V input at load currents up to 3A and features a 500kHz switching frequency for optimum efficiency and component size.

The EV kit includes an EN/UVLO PCB pad and jumper JU1 to enable the output at a desired input voltage. The SYNC PCB pad allows an external clock to synchronize the device. Jumper JU2 allows the selection of a particular MODE/SYNC of operation based on light-load performance requirements. An additional $\overline{\text{RESET}}$ PCB pad is available for monitoring whether the converter output is in regulation.

Soft-Start Input (SS)

The device utilizes an adjustable soft-start function to limit inrush current during startup. The soft-start time is adjusted by the value of C8, the external capacitor from SS to GND. The selected output capacitance (C_{SEL}) and the output voltage (V_{OUT}) determine the minimum value of C8, as shown by the following equation:

$$C8 \geq 28 \times 10^{-6} \times C_{\text{SEL}} \times V_{\text{OUT}}$$

The soft-start time (t_{SS}) is related to C8 by the following equation:

$$t_{\text{SS}} = C8 / (5.55 \times 10^{-6})$$

For example, to program a 1ms soft-start time, C8 should be 5.6nF.

Regulator Enable/Undervoltage-Lockout Level (EN/UVLO)

The device offers an adjustable input undervoltage-lockout level. For normal operation, a shunt should be installed across pins 1-2 on jumper JU1. To disable the output, install a shunt across pins 2-3 on JU1 and the EN/UVLO pin is pulled to GND. See [Table 1](#) for JU1 settings.

Set the voltage at which the device turns on with the resistive voltage-divider R1/R2 connected from VIN to SGND. Connect the center node of the divider to EN/UVLO.

Choose R1 to be 3.32M Ω and then calculate R2 as follows:

$$R2 = \frac{R1 \times 1.215}{(V_{\text{INU}} - 1.215)}$$

where V_{INU} is the voltage at which the device is required to turn on.

MODE/SYNC Selection (MODE/SYNC)

The device's MODE/SYNC pin can be used to select among PWM, PFM, or DCM modes of operation. The logic state of the MODE/SYNC pin is latched when the V_{CC} and EN/UVLO voltages exceed the respective UVLO rising thresholds and all internal voltages are ready to allow LX switching. State changes on the MODE/SYNC pin are ignored during normal operation. Refer to the MAX17574 IC data sheet for more information on PWM, PFM, and DCM MODE/SYNC modes of operation.

[Table 2](#) shows EV kit jumper settings that can be used to configure the desired mode of operation.

External Clock Synchronization (MODE/SYNC)

The internal oscillator of the device can be synchronized to an external clock signal on the SYNC pin. The external synchronization clock frequency must be between $1.1f_{\text{SW}}$ and $1.4f_{\text{SW}}$, where f_{SW} is the frequency of operation set by R3. The minimum external clock high pulse width should be greater than 50ns and the minimum external clock low pulse width should be greater than 160ns.

Table 1. Regulator Enable (EN/UVLO) Description (JU1)

SHUNT POSITION	EN/UVLO PIN	MAX17574_ OUTPUT
1-2*	Connected to V_{IN}	Enabled
Not installed	Connected to the center node of resistor-divider R1 and R2	Enabled, UVLO level set through the R1 and R2 resistors
2-3	Connected to SGND	Disabled





*Default position.

Table 2. MODE/SYNC Description (JU2)



SHUNT POSITION	MODE/SYNC PIN	MAX17574_ MODE
Not installed*	Unconnected	PFM mode of operation
2-3	Connected to SGND	PWM mode of operation
1-2	Connected to V_{CC}	DCM mode of operation

*Default position.


MAX17574 3.3V EV Kit Test Report




MAX17574 3.3V EV Kit Test Report (continued)





LOAD CURRENT STEPPED FROM NO LOAD TO 1.5A
(3.3V OUTPUT, PWM MODE)



LOAD CURRENT STEPPED FROM 5mA TO 1.5A
(3.3V OUTPUT, PFM MODE)



MAX17574 3.3V EV Kit Test Report (continued)



Component Suppliers

SUPPLIER	WEBSITE
Coilcraft, Inc.	www.coilcraft.com
Murata Americas	www.murata.com
Panasonic Corp.	www.panasonic.com
Taiyo Yuden	www.t-yuden.com
TDK Corp.	www.tdk.com

Note: Indicate that you are using the MAX17574 when contacting these component suppliers.

Ordering Information

PART	TYPE
MAX17574EVKITA#	EV Kit

#Denotes RoHS compliant.

MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574
3.3V Output-Voltage Application

MAX17574A 3.3V EV Bill of Materials

SERIAL NO.	DESCRIPTION	QUANTITY	DESIGNATOR	PART NUMBER
1	2.2μF ±10%, 100V X7R ceramic capacitor (1210)	2	C1,C2	MURATA GRM32ER72A225KA35
2	47μF ±10%, 10V X7R ceramic capacitor (1210)	1	C3	MURATA GRM32ER71A476KE15
3	22μF ±10%, 10V X7R ceramic capacitor (1210)	1	C4	MURATA GRM32ER71A226K
4	0.1μF ±10%, 50V X7R ceramic capacitor (0402)	1	C5	MURATA GRM155R71H104KE14
5	2.2μF ±10%, 10V X7R ceramic capacitor (0603)	1	C6	MURATA GRM188R71A225KE15
6	47uF, 80V electrolytic capacitor (10mm. Dia.)	1	C7	PANASONIC EEE-FK1K470P
7	0.022μF ±10%, 50V X7R ceramic capacitor (0402)	1	C8	MURATA GRM155R71H223KA12
8	0.1μF ±10%, 100V X7R ceramic capacitor (0603)	1	C11	MURATA GRM188R72A104KA35
9	2-pin header (36-pin header 0.1" centers)	2	JU1, JU2	Sullins: PEC03SAAN
10	6.8μH Inductor (8.6mm x 8.1mm x 8mm)	1	L1	Coilcraft XAL8080-682ME
11	3.3MΩ ±1%, resistor (0603)	1	R1	Any
12	750kΩ ±1%, resistor (0603)	1	R2	Any
13	10kΩ ±1%, resistor (0402)	1	R4	Any
14	75kΩ ±1%, resistor (0402)	1	R6	Any
15	19.1kΩ ±1%, resistor (0402)	1	R7	Any
16	Buck Converter MAX17574ATG+	1	U1	MAX17574ATG+
17	OPEN	1	C10	
18	OPEN	1	R3	
19	Shunt	2	See Jumper Table	SULLINS STC02SYAN
20	Test Loops	9	VIN, SGND, VOUT, PGND1, PGND2, RESET, EN/UVLO, MODE/SYNC	EBUSS20W
21	MEDIUM BROWN 9 3/8" X 7 1/4" X 2 1/2	1	Pack-out	
22	WEB instructions for Maxim Data Sheet	1	Pack-out	
23	Label	1	Pack-out	
24	BAG; STATIC SHIELD 5X8;W/ESD LOGO	1	Pack-out	
25	FOAM, ANTI-STATIC PE 12"x12"x5MM	1	Pack-out	
26	Rubber bumpers, 3M SJ-5003	4	Pack-out	


Jumper Table

JUMPER	SHUNT POSITION
JU1	1–2
JU2	1–2 for DCM, 2–3 for PWM, and OPEN for PFM mode

MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574 3.3V Output-Voltage Application


MAX17574A 3.3V EV Kit Schematics




MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574
3.3V Output-Voltage Application


MAX17574A 3.3V EV Kit PCB Layout



MAX17574 3.3V Output EV Kit Component Placement Guide—
Component Side




MAX17574 3.3V Output EV Kit Component Side PCB layout




MAX17574 3.3V Output EV Kit PCB Layout—Inner Layer 1

MAX17574A 3.3V EV Kit PCB Layout (continued)



MAX17574 3.3V Output EV Kit PCB Layout—Inner Layer 2



MAX17574 3.3V Output EV Kit PCB Layout—Solder Side

MAX17574 3.3V Output Evaluation Kit

Evaluates: MAX17574
3.3V Output-Voltage Application

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	11/16	Initial release	—
1	7/17	Updated <i>Quick Start</i> , <i>Detailed Description</i> , <i>Soft-Start Input (SS)</i> and <i>Regulator Enable/Undervoltage-Lockout Level (EN/UVLO)</i> sections, Table 2, TOC01–TOC09, <i>Bill of Materials</i> , and replaced TOC06.	1–6
2	5/18	Updated Table 2 and Jumper Table	4, 6

For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at www.maximintegrated.com.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9