OptiMOS®-P Small-Signal-Transistor

Feature

- Dual P-Channel
- Enhancement mode
- Super Logic Level (2.5 V rated)
- 150°C operating temperature
- Avalanche rated
- d*v*/d*t* rated
- Pb-free lead plating; RoHS compliant
- Qualified according to AEC Q101
- Halogen-free according to IEC61249-2-21

Halogen-Free

AEC Qualified

RoHS

Product Summary

V_{DS}	-20	V
$R_{DS(on)}$	1.2	Ω
I_D	-0.39	A

PG-SOT-363





Type	Package	Tape & Reel	Marking
BSD 223P	PG-SOT-363	H6327: 3000pcs/r	X1s

Maximum Ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current	I_D		A
T_A=25°C		-0.39	
T_A=70°C		-0.31	
Pulsed drain current T_A=25°C	$I_{D\ puls}$	-1.56	
Avalanche energy, single pulse I_D=-0.39 A , V_{DD}=-10V, R_{GS}=25Ω	E_{AS}	1.4	mJ
Reverse diode d*v*/d*t* I_S=-0.39A, V_{DS}=-16V, d*i*/d*t*=200A/µs, T_{jmax}=150°C	d*v*/d*t*	-6	kV/µs
Gate source voltage	V_{GS}	±12	V
Power dissipation T_A=25°C	P_{tot}	0.25	W
Operating and storage temperature	T_j , T_{stg}	-55... +150	°C
IEC climatic category; DIN IEC 68-1		55/150/56	
ESD Class JESD22-A114-HBM		Class 0	

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Thermal resistance, junction - soldering point	R_{thJS}	-	-	180	K/W
Thermal resistance, junction - ambient, leaded	R_{thJA}	-	-	500	

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Drain-source breakdown voltage V_{GS}=0, I_D=-250µA	$V_{(BR)DSS}$	-20	-	-	V
Gate threshold voltage, V_{GS} = V_{DS} I_D=-1.5µA	$V_{GS(th)}$	-0.6	-0.9	-1.2	
Zero gate voltage drain current V_{DS}=-20V, V_{GS}=0, T_j=25°C V_{DS}=-20V, V_{GS}=0, T_j=150°C	I_{DSS}	 - -	 -0.1 -10	 -1 -100	µA
Gate-source leakage current V_{GS}=-12V, V_{DS}=0	I_{GSS}	-	-10	-100	nA
Drain-source on-state resistance V_{GS}=-2.5V, I_D=-0.29A	$R_{DS(on)}$	-	1.27	2.1	Ω
Drain-source on-state resistance V_{GS}=-4.5, I_D=-0.39A	$R_{DS(on)}$	-	0.7	1.2	

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic Characteristics						
Transconductance	g_{fs}	$\lvert V_{DS}\rvert \geq 2 * \lvert I_D\rvert * R_{DS(on)max}$, I_D=-0.31A	0.35	0.7	-	S
Input capacitance	C_{iss}	V_{GS}=0, V_{DS}=-15V, f=1MHz	-	45	56	pF
Output capacitance	C_{oss}		-	21	26	
Reverse transfer capacitance	C_{rss}		-	17	22	
Turn-on delay time	$t_{d(on)}$	V_{DD}=-10V, V_{GS}=-4.5V, I_D=-0.39A, R_G=6Ω	-	3.8	5.7	ns
Rise time	t_r		-	5	7.5	
Turn-off delay time	$t_{d(off)}$		-	5.1	7.6	
Fall time	t_f		-	3.2	4.8	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=-10V, I_D=-0.39A	-	-0.04	-0.05	nC
Gate to drain charge	Q_{gd}		-	-0.4	-0.5	
Gate charge total	Q_g	V_{DD}=-10V, I_D=-0.39A, V_{GS}=0 to -4.5V	-	-0.5	-0.62	
Gate plateau voltage	$V_{(plateau)}$	V_{DD}=-10V, I_D=-0.39A	-	-2.2	-2.7	V
Reverse Diode						
Inverse diode continuous forward current	I_S	T_A=25°C	-	-	-0.39	A
Inv. diode direct current, pulsed	I_{SM}		-	-	-1.56	
Inverse diode forward voltage	V_{SD}	V_{GS}=0, I_F=-0.39	-	-1	-1.33	V
Reverse recovery time	t_{rr}	V_R=-10V, $\lvert I_F\rvert = \lvert I_D\rvert$, di_F/dt=100A/µs	-	7.6	9.5	ns
Reverse recovery charge	Q_{rr}		-	1.1	1.4	nC

1 Power dissipation

$P_{tot} = f(T_A)$



2 Drain current

$I_D = f(T_A)$

parameter: $|V_{GS}| \geq 4.5$ V



3 Safe operating area

$I_D = f(V_{DS})$

parameter : $D = 0$, $T_A = 25$ °C



4 Transient thermal impedance

$Z_{thJA} = f(t_p)$

parameter : $D = t_p/T$



5 Typ. output characteristic

$I_D = f(V_{DS})$

parameter: T_j =25°C



6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D)$

parameter: V_{GS}



7 Typ. transfer characteristics

$I_D = f(V_{GS})$; $|V_{DS}| \geq 2 \times |I_D| \times R_{DS(on)max}$

parameter: T_j = 25 °C



8 Typ. forward transconductance

$g_{fs} = f(I_D)$

parameter: T_j = 25 °C



9 Drain-source on-resistance

$R_{DS(on)} = f(T_j)$

parameter: I_D = -0.39 A, V_{GS} = -4.5 V



10 Typ. gate threshold voltage

$V_{GS(th)} = f(T_j)$

parameter: $V_{GS} = V_{DS}$



11 Typ. capacitances

$C = f(V_{DS})$

parameter: V_{GS}=0, f=1 MHz



12 Forward character. of reverse diode

$I_F = f(V_{SD})$

parameter: T_j



13 Typ. avalanche energy

$E_{AS} = f(T_j)$, par.: I_D = -0.39 A

V_{DD} = -10 V, R_{GS} = 25 Ω



14 Typ. gate charge

$V_{GS} = f(Q_{Gate})$

parameter: I_D = -0.39 A pulsed; T_j = 25 °C



15 Drain-source breakdown voltage

$V_{(BR)DSS} = f(T_j)$



Package Outline:





Footprint:



Packaging:



Reflow soldering:



Dimensions in mm

For symmetric types there is no defined Pin 1 orientation in the reel.

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9