

## 8281F Coax - Double Braided RG-59/U Type

For more Information  
please call

1-800-Belden1

**Description:**

22 AWG stranded (7x29) .031" bare compacted copper conductor, polyethylene insulation, tinned copper/bare copper double braid shield (95% coverage), PVC jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Coax | AWG | Stranding | Conductor Material          | Dia. (in.) |
|--------|-----|-----------|-----------------------------|------------|
| 1      | 22  | 7x29      | BCC - Bare Compacted Copper | .031       |

Total Number of Conductors: 1

**Insulation**

Insulation Material:

| Insulation Material | Dia. (in.) |
|---------------------|------------|
| PE - Polyethylene   | .193       |

**Outer Shield**

Outer Shield Material:

| Layer # | Type  | Outer Shield Material | Coverage (%) |
|---------|-------|-----------------------|--------------|
| 1       | Braid | TC - Tinned Copper    | 95.000       |
| 2       | Braid | TC - Tinned Copper    | 95.000       |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

**Overall Cable**

Overall Nominal Diameter: 0.304 in.

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -20°C To +60°C

Non-UL Temperature Rating: 60°C

Bulk Cable Weight: 63 lbs/1000 ft.

Max. Recommended Pulling Tension: 168 lbs.

Min. Bend Radius/Minor Axis: 3 in.

Min. Flexing Radius: 4.500 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

## 8281F Coax - Double Braided RG-59/U Type

|                                |     |
|--------------------------------|-----|
| EU Directive 2003/11/EC (BFR): | Yes |
|--------------------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| CA Prop 65 (CJ for Wire & Cable): | Yes |
|-----------------------------------|-----|

|                             |     |
|-----------------------------|-----|
| MII Order #39 (China RoHS): | Yes |
|-----------------------------|-----|

|          |      |
|----------|------|
| RG Type: | 59/U |
|----------|------|

**Suitability**

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

**Plenum/Non-Plenum**

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

| Impedance (Ohm) |
|-----------------|
| 75              |

**Nom. Inductance:**

| Inductance (μH/ft) |
|--------------------|
| 0.118              |

**Nom. Capacitance Conductor to Shield:**

| Capacitance (pF/ft) |
|---------------------|
| 21                  |

**Nominal Velocity of Propagation:**

| VP (%) |
|--------|
| 66     |

**Nominal Delay:**

| Delay (ns/ft) |
|---------------|
| 1.54          |

**Nom. Conductor DC Resistance:**

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 12.2                     |

**Nominal Outer Shield DC Resistance:**

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 1.7                      |

**Nom. Attenuation:**

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 1           | .3                       |
| 3.6         | .5                       |
| 10.0        | .9                       |
| 71.5        | 2.5                      |
| 135         | 3.6                      |
| 270         | 5.1                      |
| 360         | 6.0                      |
| 540         | 7.4                      |
| 720         | 8.7                      |
| 750         | 8.9                      |
| 1000        | 10.5                     |

**Max. Operating Voltage - Non-UL:**

| Voltage    |
|------------|
| 2900 V RMS |

**Other Electrical Characteristic 1:**

Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

**Other Electrical Characteristic 2:**

Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

**Minimum Structural Return Loss:**

| Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------------|------------------|---------------|
|-------------------|------------------|---------------|

**8281F Coax - Double Braided RG-59/U Type**

|     |     |    |
|-----|-----|----|
| 5   | 216 | 27 |
| 217 | 830 | 23 |

**Sweep Test**

**Sweep Testing:** 100% sweep tested. 5 MHz to 850 MHz.

**Notes (Overall)**

**Notes:** Compacted copper combines the Impedance uniformity of solid conductors and the "nick-resistance" of stranded conductors.

**Put Ups and Colors:**

| Item #        | Putup    | Ship Weight | Color              | Notes | Item Desc        |
|---------------|----------|-------------|--------------------|-------|------------------|
| 8281F G7V1000 | 1,000 FT | 68.000 LB   | RED, MATTE         | C     | #21H PE DBLB PVC |
| 8281F G7W1000 | 1,000 FT | 68.000 LB   | GREEN, MATTE       | C     | #21H PE DBLB PVC |
| 8281F G7X1000 | 1,000 FT | 68.000 LB   | BLUE, MATTE        | C     | #21H PE DBLB PVC |
| 8281F J5C1000 | 1,000 FT | 68.000 LB   | BLACK, VIVID MATTE | C     | #21H PE DBLB PVC |
| 8281F J5C500  | 500 FT   | 35.000 LB   | BLACK, VIVID MATTE |       | #21H PE DBLB PVC |
| 8281F U901000 | 1,000 FT | 68.000 LB   | GRAY, MATTE        | C     | #21H PE DBLB PVC |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 08-20-2012

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9