

RAYCHEM MATCHED IMPEDANCE SPLICES

FAST, EASY REPAIRS THAT MAINTAIN THE COAXIAL CABLE'S
ELECTRICAL CHARACTERISTICS

MATCHED IMPEDANCE

- Maintains cable's electrical properties
- Meets MIL-PRF-32517 performance requirements
- Matches cable's impedance +10%/-3%

TIME AND COST SAVING

- Repairs made in situ
- No need to remove or replace cable

SEALED

- Heat-shrinkable outer layer plus thermoplastic adhesive for sealing and strain relief

ROBUST

- Withstands high vibration
- Corrosion resistant
- Wide temperature range
- Excellent fluid resistance
- Suitable for high EMI environments

APPLICATIONS

- Military Aerospace
- Commercial Aerospace

With the matched impedance splice, TE Connectivity (TE) solves the problem of costly removal and replacement of damaged coaxial cable. Not only does the new splice allow fast, easy repair of the cable in situ, it maintains the characteristic impedance and other electrical properties. System performance is not affected by the repair.

SAVE TIME AND MONEY

Removing and replacing a damaged coaxial cable can be time consuming and expensive. The matched impedance splice's ability to be applied without removing the cable can significantly speed the repair, saving time and cost.

SIMPLE AND EFFECTIVE

The splice contains three components: a hexagonal crimp barrel for the center conductors, a dielectric shell that helps maintain cable geometry for impedance control, and a SolderShield splice that both terminates the cable's shield and provides sealing to protect the splice environmentally.

The SolderShield splice uses a flux-coated, solder-impregnated copper shield inside an adhesive-lined, heat-shrinkable sleeve. The completed assembly provides an environmentally sealed termination and strain relief.

TE Components . . . TE Technology . . . TE Know-how . . .

AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH
SEACON Phoenix | L.L. Rowe | Phoenix Optix | AFP | SEACON

Get your product to market faster with a smarter, better solution.

Raychem Matched Impedance Splices

Fast, Easy Cable Repair

SPECIFICATIONS

Electrical

Impedance:	MIL-PRF-32517
Insertion Loss:	MIL-PRF-32517
Return Loss:	MIL-PRF-32517
Insulation Resistance:	5000 M Ω

Environmental/Mechanical

Altitude Immersion:	75,000 ft
Heat Aging:	750 hr. at +165°C
Temperature Range:	-55° C to 150°C

Cable Compatibility


Cable Types:	RG-393
---------------------	--------

TE Specifications

Application Specification:	D-6204
Product Specification:	D-6204
Qualification Test Reports:	HT4203 (for D-150-Z393)
Installation Instructions:	RPIP-1108

PART NUMBERS

Cable Type	Part Number
RG-393	D-150-Z393



te.com/matched-impedance-splice

© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773880-4 05/16

Raychem, SolderShield, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other product or company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

North America +1 800 522 6752 • Asia Pacific +86 400 820 6015 • France +33 1 34 20 86 86 • Germany +49 6251 133 1999 • United Kingdom +44 800 267 666
Visit te.com for additional country contacts.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9