

CHIP QUIK® , INC. PRESENTS THE SOLDER / DESOLDER SOLUTION

My Observation

My years of experience in the rework industry have put me in contact with numerous technical people who perform all levels of solder and desolder rework. After performing numerous live demonstrations at trade shows, hi-tech companies, technical organizations, service companies, and electronic schools, I have observed that there is a significant lack of understanding of the basic methods of SMT rework. Due to this lack of knowledge many avoid doing rework. The misconception is that you need to spend thousands of dollars on expensive equipment along with specialized training. Most of us cannot justify this expense for low volume rework. Consequently many boards that could be reworked are scrapped.

CHIP QUIK® Has The Solution Safe, Affordable, Easy, Rework

The greatest challenge in rework is to safely remove an SMD without inflicting damage to the board or the adjacent components. This can easily be done with **Chip Quik® and a simple soldering iron**. Chip Quik® will safely remove all SMD components. Also shields, grounds, and numerous other applications that require removal at safe low temperatures. **No** need for expensive tips and nozzles. **No** expensive equipment, **No** special training required. **Its that easy!**

SMD 1



Ordering Information

SMD 1 SMD Removal Kit
(flux, alloy, alcohol pads)
SMD 16 Removal Alloy
16ft. in 6.5in. lengths
SMD 32 Removal Alloy
32ft. in 6.5in. lengths
SMD 291 NoClean Paste Flux
10cc syringe w /tip
SMD 2000 Solder/Desolder
Rework Kit
NEW Lead free Chip Quik
Instructions Included in all

The Chip Quik® SMD Removal Kit Is The Answer

Included in each Chip Quik® kit is a special removal alloy that has excellent wetting ability with a low melting temperature of 136°F (58°C), a special paste flux used for solder/desolder, alcohol pads for clean up, and instructions.

SMD Removal Instructions With Solder Iron

- Apply paste flux to all leads with the syringe.
- Melt Chip Quik® alloy on all pins of SMD
- With wide tip iron maintain alloy in a molten state long enough to release chip.
- Lift chip from board with pick up tool.

Clean Up After Removal

- Use iron, and a swab dipped in flux to thoroughly clean and polish pads.
- Clean area with alcohol pads.
- You are ready to install new chip.

How To Solder On The New Chip

- Apply paste flux across all pads of SMD.
- Place chip accurately on pads.
- Solder a few pins to hold chip in place.
- Drag solder all pins with a wide tip iron
- Use wick if bridging occurs.

This unique rework method has become known globally as the Chip Quik® Rework Solution

*For Chip Quik® Distributors visit in
USA, Canada, and Globally*

www.chipquik.com
or e-mail chipquik@aol.com

Chip Quik, Inc.
195 Falmouth Road #1C
Mashpee, MA 02649 USA
Tel. 508-477-2264

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9