



**SERIES:** SJ-358XNG | **DESCRIPTION:** 3.5 MM AUDIO JACKS**FEATURES**

- low profile design
- switch options include:
 - no switch
 - tip switch
 - ring switch
 - tip and ring switch
- w/isolated DPDT switch
- plastic bushing
- w/kinked pins

**PART NUMBER KEY****SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	A
contact resistance	between terminal and mating plug			50	mΩ
	between terminal in a closed circuit*			30	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	at 50/60Hz for 1 minute			500	Vac
insertion/withdrawl force		0.3		3	kg
terminal strength	any direction for 10 seconds			500	g
operating temperature		-25		85	°C
life			5,000		cycles

Notes: *When measured at a current of less than 100 mA / 1 kHz



SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5±0.5 seconds at	255	260	265	°C


MECHANICAL DRAWING

units: mm[inches]

TOLERANCE:
 X.X ±0.2mm
 X.XX ±0.1mm
 X.XXX ±0.05mm



	MATERIAL	PLATING
terminal 1	brass	tin
terminal 2	copper alloy	tin
terminal 3	copper alloy	tin
terminal 4	brass	silver
terminal 5	brass	silver
terminal 6	brass	silver
terminal 7	brass	silver
terminal 8	brass	silver
terminal 9	brass	silver
terminal 10	brass	tin
terminal 11	brass	tin
spring	stainless steel	
contact clip	C5210R-EH	silver
insulator	PA66	
plastic	PBT	



Model No.	SJ-3580ANG	SJ-3580BNG	SJ-3581NG	SJ-3589ANG	SJ-3589BNG																														
Schematic																																			
	Plug Not Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Not Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Not Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Not Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Not Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9
	4	7																																	
	5	8																																	
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
Plug Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	Plug Inserted <table><tr><td>4</td><td>7</td></tr><tr><td>5</td><td>8</td></tr><tr><td>6</td><td>9</td></tr></table>	4	7	5	8	6	9	
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
4	7																																		
5	8																																		
6	9																																		
Pin																																			
1	sleeve	sleeve	sleeve	sleeve	sleeve																														
2	tip	tip	tip	tip	tip																														
3	ring	ring	ring	ring	NP																														
10	tip switch	NP	tip switch	NP	tip switch																														
11	NP	ring switch	ring switch	NP	NP																														

REVISION HISTORY

rev.	description	date
1.0	initial release	09/13/2006
1.01	new template applied	01/27/2012

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9