



APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +80 °C	STORAGE TEMPERATURE RANGE	-25 °C TO +60 °C	
	VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	95 % MAX.	
	CURRENT	500mA	APPLICABLE CABLE	—	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz AC). 		60 mΩ MAX.	X	X
INSULATION RESISTANCE	100 V DC.		100 MΩ MIN.	X	X
VOLTAGE PROOF (CONTACT TO CONTACT)	500 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	X	X
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	5000 TIMES INSERTIONS AND EXTRACTIONS.		1) CONTACT RESISTANCE: 90 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, AT 2 HOURS FOR 3 DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 5 μs. 2) CONTACT RESISTANCE: 90 mΩ MAX. 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			X	—
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT, CYCLIC	EXPOSED AT +40 °C, 90 TO 95 % , 500 h		1) CONTACT RESISTANCE: 90 mΩ MAX. 2) INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) 10 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55±3 → 5 TO 35 → 85±2 → 5 TO 35 °C TIME 30 +5/0 → 5 MAX. → 30 +5/0 → 5 MAX. min UNDER 5 CYCLES.		1) CONTACT RESISTANCE: 90 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN. 3) NO DAMAGE, CRACK AND LOOSENESS OF PART	X	—
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		1) CONTACT RESISTANCE: 90 mΩ MAX. 2) NO HEAVY CORROSION.	X	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK			APPROVED	KN. ICHIKAWA	11. 01. 13
			CHECKED	KN. ICHIKAWA	11. 01. 13
			DESIGNED	HN. ANDO	11. 01. 11
Unless otherwise specified, refer to JIS C 5402.			DRAWN	HN. ANDO	11. 01. 11
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-127281-00
HRS	SPECIFICATION SHEET		PART NO.	TM25RS-5CNA-88	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-2967-7-00	△ 1/2

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

RECOMMENDED TEMPERATURE PROFILE (REFLOW SOLDERING, MOUNTING AREA)





RECOMMENDED MANUAL SOLDERING TEMPERATURE

- TEMPERATURE : 350±10°C
- HEATING TIME : 4sec. MAX.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-127281-00		
HRS	SPECIFICATION SHEET		PART NO.	TM25RS-5CNA-88	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL222-2967-7-00	△ 2/2



2 MOUNTING AREA PIN ASSIGNMENT







RECOMMENDED PC BORAD PATTERN

PCB THICKNESS: t1.2
TH: PLATED THROUGH HOLE
LA: LAND


METAL MASK DIMENSIONS FOR REFERENCE
THICKNESS: t0.12



INSTALLATION DIMENSIONS FOR REFERENCE




2 CONTACT AREA PIN ASSIGNMENT




NOTES

- 1 WRENCHING STRENGTH IN EACH DIRECTION IS STATED AS FOLLOWS.
BACKWARD AND FORWARD : 60N MIN.
RIGHT AND LEFT : 30MIN.
UP AND DOWN : 15N MIN. MOVING PART SHALL NOT BE COME OFF.
AFTER IT IS EXAMINATED 20 TIMES : 10N MIN.
- 2 PIN ASSIGNMENT IS AS SHOWN IN FIGURE.
PLEASE NOTE THE PIN ASSIGNMENT IS FOR MOUNTING AREA AND DIFFERENT FROM THAT FOR CONTACT AREA.


1 WRENCHING DIRECTION



REVISED CONFIGURATION



LOT No.




NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
4	STAINLESS STEEL			8	PP		CLEAR, TRAY
3	STAINLESS STEEL			7	STAINLESS STEEL		NICKEL PLATING : 0.1μm MIN.
2	PHOSPHOR BRONZE		CONTACT AREA : GOLD PLATING 0.2μm MIN. MOUNTING AREA : GOLD PLATING 0.03μm MIN. UNDER PLATING : NICKEL PLATING 1μm MIN.	6	POLYAMIDE		BLACK, UL94V-0
1	POLYAMIDE		BLACK, UL94V-0	5	STAINLESS STEEL		BOTH SIDE TIN PLATING 38μm MIN. UNDER PLATING NICKEL PLATING 125μm MIN.

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	DIS-E-004428	HN. ANDO	AH. KODAMA	12. 11. 14


APPROVED	DATE	DRAWING NO.
KN. ICHIKAWA	11. 01. 13	EDC3-127281-00
KN. ICHIKAWA	11. 01. 13	PART NO.
HN. ANDO	11. 01. 13	TM25RS-5CNA-88
HN. ANDO	11. 01. 13	CODE NO.
		CL222-2967-7-00

3 PACKING OF TRAY (FREE)


A TYPE 70 pcs./TRAY



A (1:1)




4 PACKING OF CARTON (FREE)



5 4 ACCUMULATION OF TRAY (FREE)

B TYPE 70 pcs./TRAY



CORRUGATED CARDBOARD

PP BAND

CORRUGATED CARDBOARD

EMPTY TRAY : 1 pcs.

TRAY : 7 pcs.

CONTENTS OF A LABEL

荷 札			
得意先名 (Customer Name)		納入場所 (Shipment to)	
注文番号 (P/O No.)	得意先品名 (Customer Part Name)	自販	
受注製番	1箱の入り数 (This box contains)	個 (Qty)	個 (Pcs)
搬出登録 (Delivery Register No.)	得意先数量 (Pcs)		
品目コード	仕様	HRS品名 (Hirose Part Number)	
仕様名			工事番号
特記事項			
二枚分岐	営業コード	MADE IN JAPAN	
ヒロセ電機株式会社 Hirose Electric Co., Ltd.			

NOTES 3 PACKING : 70 pcs./TRAY

4 THE PACKING SPECIFICATION CAN VARY WITH PACKING QUANTITIES.

5 2 SETS OF BANNED TRAYS ARE USED IN CARTON BOX WHEN PRODUCTS ARE STORED MAXIMUM.

HRS	DRAWING NO.	EDC3-127281-00
	PART NO.	TM25RS-5CNA-88
	CODE NO.	CL222-2967-7-00

3/2

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9