
COMBICON Plugs and Headers as a „high current“ (HC) Version for Currents up to 16 A, 5.0 or 5.08 mm Pitch

Tuning for the MSTB classic
The proven COMBICON MSTB plug connector is now available as a "high current" (HC) version for currents up to 16 A. On top of the familiar MSTB features, a double steel spring guarantees extra safety for higher power transmission.
The HC family is available with 2 to 12 positions and in pitches of 5.0 and 5.08 mm.
Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.




Headquarters: © Phoenix Contact GmbH & Co. KG• Flachsmarktstraße 8 • 32825 Blomberg • Germany
Phone +49-(0) 52 35-3-00 • Fax +49-(0) 52 35-3-4 12 0 • http://www.phoenixcontact.com

MSTB 2,5 HC/…-ST(-5,08)
5.0 or 5.08 mm Pitch

The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.



Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch					
color: green	2	5	**MSTB 2,5 HC/2-ST**	**19 11 85 5**	50
	3	10	**MSTB 2,5 HC/3-ST**	**19 11 86 8**	
	4	15	**MSTB 2,5 HC/4-ST**	**19 11 87 1**	
	5	20	**MSTB 2,5 HC/5-ST**	**19 11 88 4**	
	6	25	**MSTB 2,5 HC/6-ST**	**19 11 89 7**	
	7	30	**MSTB 2,5 HC/7-ST**	**19 11 90 7**	
	8	35	**MSTB 2,5 HC/8-ST**	**19 11 91 0**	
	9	40	**MSTB 2,5 HC/9-ST**	**19 11 92 3**	
	10	45	**MSTB 2,5 HC/10-ST**	**19 11 93 6**	
	11	50	**MSTB 2,5 HC/11-ST**	**19 11 94 9**	
	12	55	**MSTB 2,5 HC/12-ST**	**19 11 95 2**	
COMBICON HC plugs, 5.08 mm pitch					
color: green	2	5.08	**MSTB 2,5 HC/2-ST-5,08**	**19 11 96 5**	50
	3	10.16	**MSTB 2,5 HC/3-ST-5,08**	**19 11 97 8**	
	4	15.24	**MSTB 2,5 HC/4-ST-5,08**	**19 11 98 1**	
	5	20.32	**MSTB 2,5 HC/5-ST-5,08**	**19 11 99 4**	
	6	25.40	**MSTB 2,5 HC/6-ST-5,08**	**19 12 00 3**	
	7	30.48	**MSTB 2,5 HC/7-ST-5,08**	**19 12 01 6**	
	8	35.56	**MSTB 2,5 HC/8-ST-5,08**	**19 12 02 9**	
	9	40.64	**MSTB 2,5 HC/9-ST-5,08**	**19 12 03 2**	
	10	45.72	**MSTB 2,5 HC/10-ST-5,08**	**19 12 04 5**	
	11	50.80	**MSTB 2,5 HC/11-ST-5,08**	**19 12 05 8**	
	12	55.88	**MSTB 2,5 HC/12-ST-5,08**	**19 12 06 1**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		


Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MSTB 2,5 HC/…-STF(-5,08) with Srew Flange 5.0 or 5.08 mm Pitch

The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.



Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, with screw flange, color: green	2	5	**MSTB 2,5 HC/2-STF**	**19 12 07 4**	50
	3	10	**MSTB 2,5 HC/3-STF**	**19 12 08 7**	
	4	15	**MSTB 2,5 HC/4-STF**	**19 12 09 0**	
	5	20	**MSTB 2,5 HC/5-STF**	**19 12 10 0**	
	6	25	**MSTB 2,5 HC/6-STF**	**19 12 11 3**	
	7	30	**MSTB 2,5 HC/7-STF**	**19 12 12 6**	
	8	35	**MSTB 2,5 HC/8-STF**	**19 12 13 9**	
	9	40	**MSTB 2,5 HC/9-STF**	**19 12 14 2**	
	10	45	**MSTB 2,5 HC/10-STF**	**19 12 15 5**	
	11	50	**MSTB 2,5 HC/11-STF**	**19 12 16 8**	
	12	55	**MSTB 2,5 HC/12-STF**	**19 12 17 1**	
COMBICON HC plugs, 5.08 mm pitch, with screw flange, color: green	2	5.08	**MSTB 2,5 HC/2-STF-5,08**	**19 12 18 4**	50
	3	10.16	**MSTB 2,5 HC/3-STF-5,08**	**19 12 19 7**	
	4	15.24	**MSTB 2,5 HC/4-STF-5,08**	**19 12 20 7**	
	5	20.32	**MSTB 2,5 HC/5-STF-5,08**	**19 12 21 0**	
	6	25.40	**MSTB 2,5 HC/6-STF-5,08**	**19 12 22 3**	
	7	30.48	**MSTB 2,5 HC/7-STF-5,08**	**19 12 23 6**	
	8	35.56	**MSTB 2,5 HC/8-STF-5,08**	**19 12 24 9**	
	9	40.64	**MSTB 2,5 HC/9-STF-5,08**	**19 12 25 2**	
	10	45.72	**MSTB 2,5 HC/10-STF-5,08**	**19 12 26 5**	
	11	50.80	**MSTB 2,5 HC/11-STF-5,08**	**19 12 27 8**	
	12	55.88	**MSTB 2,5 HC/12-STF-5,08**	**19 12 28 1**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MSTBT 2,5 HC/…-ST
5.0 mm Pitch



The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.


Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.

Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, color: green	2	5	**MSTBT 2,5 HC/2-ST**	**19 26 35 8**	50
	3	10	**MSTBT 2,5 HC/3-ST**	**19 26 24 8**	
	4	15	**MSTBT 2,5 HC/4-ST**	**19 26 25 1**	
	5	20	**MSTBT 2,5 HC/5-ST**	**19 26 26 4**	
	6	25	**MSTBT 2,5 HC/6-ST**	**19 26 27 7**	
	7	30	**MSTBT 2,5 HC/7-ST**	**19 26 28 0**	
	8	35	**MSTBT 2,5 HC/8-ST**	**19 26 29 3**	
	9	40	**MSTBT 2,5 HC/9-ST**	**19 26 30 3**	
	10	45	**MSTBT 2,5 HC/10-ST**	**19 26 31 6**	
	11	50	**MSTBT 2,5 HC/11-ST**	**19 26 32 9**	
	12	55	**MSTBT 2,5 HC/12-ST**	**19 26 33 2**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		



MVSTBR 2,5 HC/…-ST(-5,08)
Vertical Plugs
5.0 or 5.08 mm Pitch



The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.

Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, plug-in direction vertical to the conductor axis, connection point facing the smooth wall (R) of the header, color: green	2	5	**MVSTBR 2,5 HC/2-ST**	**19 12 29 4**	50
	3	10	**MVSTBR 2,5 HC/3-ST**	**19 12 30 4**	
	4	15	**MVSTBR 2,5 HC/4-ST**	**19 12 31 7**	
	5	20	**MVSTBR 2,5 HC/5-ST**	**19 12 32 0**	
	6	25	**MVSTBR 2,5 HC/6-ST**	**19 12 33 3**	
	7	30	**MVSTBR 2,5 HC/7-ST**	**19 12 34 6**	
	8	35	**MVSTBR 2,5 HC/8-ST**	**19 12 35 9**	
	9	40	**MVSTBR 2,5 HC/9-ST**	**19 12 36 2**	
	10	45	**MVSTBR 2,5 HC/10-ST**	**19 12 37 5**	
	11	50	**MVSTBR 2,5 HC/11-ST**	**19 12 38 8**	
	12	55	**MVSTBR 2,5 HC/12-ST**	**19 12 39 1**	
COMBICON HC plugs, 5.08 mm pitch, plug-in direction vertical to the conductor axis, connection point facing the smooth wall (R) of the header, color: green	2	5.08	**MVSTBR 2,5 HC/2-ST-5,08**	**19 12 40 1**	50
	3	10.16	**MVSTBR 2,5 HC/3-ST-5,08**	**19 12 41 4**	
	4	15.24	**MVSTBR 2,5 HC/4-ST-5,08**	**19 12 42 7**	
	5	20.32	**MVSTBR 2,5 HC/5-ST-5,08**	**19 12 43 0**	
	6	25.40	**MVSTBR 2,5 HC/6-ST-5,08**	**19 12 44 3**	
	7	30.48	**MVSTBR 2,5 HC/7-ST-5,08**	**19 12 45 6**	
	8	35.56	**MVSTBR 2,5 HC/8-ST-5,08**	**19 12 46 9**	
	9	40.64	**MVSTBR 2,5 HC/9-ST-5,08**	**19 12 47 2**	
	10	45.72	**MVSTBR 2,5 HC/10-ST-5,08**	**19 12 48 5**	
	11	50.80	**MVSTBR 2,5 HC/11-ST-5,08**	**19 12 49 8**	
	12	55.88	**MVSTBR 2,5 HC/12-ST-5,08**	**19 12 50 8**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MVSTBR 2,5 HC/…-STF(-5,08)
Vertical Plugs
with Screw Flange
5.0 or 5.08 mm Pitch

The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.



Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, with screw flange, color: green, connection point facing the smooth wall (R) of the header	2	5	**MVSTBR 2,5 HC/2-STF**	**19 12 51 1**	50
	3	10	**MVSTBR 2,5 HC/3-STF**	**19 12 52 4**	
	4	15	**MVSTBR 2,5 HC/4-STF**	**19 12 53 7**	
	5	20	**MVSTBR 2,5 HC/5-STF**	**19 12 54 0**	
	6	25	**MVSTBR 2,5 HC/6-STF**	**19 12 55 3**	
	7	30	**MVSTBR 2,5 HC/7-STF**	**19 12 56 6**	
	8	35	**MVSTBR 2,5 HC/8-STF**	**19 12 57 9**	
	9	40	**MVSTBR 2,5 HC/9-STF**	**19 12 58 2**	
	10	45	**MVSTBR 2,5 HC/10-STF**	**19 12 59 5**	
	11	50	**MVSTBR 2,5 HC/11-STF**	**19 12 60 5**	
	12	55	**MVSTBR 2,5 HC/12-STF**	**19 12 61 8**	
COMBICON HC plugs, 5.08 mm pitch, with screw flange, color: green, connection point facing the smooth wall (R) of the header	2	5.08	**MVSTBR 2,5 HC/2-STF-5,08**	**19 12 62 1**	50
	3	10.16	**MVSTBR 2,5 HC/3-STF-5,08**	**19 12 63 4**	
	4	15.24	**MVSTBR 2,5 HC/4-STF-5,08**	**19 12 64 7**	
	5	20.32	**MVSTBR 2,5 HC/5-STF-5,08**	**19 12 65 0**	
	6	25.40	**MVSTBR 2,5 HC/6-STF-5,08**	**19 12 66 3**	
	7	30.48	**MVSTBR 2,5 HC/7-STF-5,08**	**19 12 67 6**	
	8	35.56	**MVSTBR 2,5 HC/8-STF-5,08**	**19 12 68 9**	
	9	40.64	**MVSTBR 2,5 HC/9-STF-5,08**	**19 12 69 2**	
	10	45.72	**MVSTBR 2,5 HC/10-STF-5,08**	**19 12 70 2**	
	11	50.80	**MVSTBR 2,5 HC/11-STF-5,08**	**19 12 71 5**	
	12	55.88	**MVSTBR 2,5 HC/12-STF-5,08**	**19 12 72 8**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MVSTBW 2,5 HC/…-ST(-5,08)
Vertical Plugs
5.0 or 5.08 mm Pitch

The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.



Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, plug-in direction vertical to the conductor axis, connection point facing the rippled wall (W) of the header, color: green	2	5	**MVSTBW 2,5 HC/2-ST**	**19 12 73 1**	50
	3	10	**MVSTBW 2,5 HC/3-ST**	**19 12 74 4**	
	4	15	**MVSTBW 2,5 HC/4-ST**	**19 12 75 7**	
	5	20	**MVSTBW 2,5 HC/5-ST**	**19 12 76 0**	
	6	25	**MVSTBW 2,5 HC/6-ST**	**19 12 77 3**	
	7	30	**MVSTBW 2,5 HC/7-ST**	**19 12 78 6**	
	8	35	**MVSTBW 2,5 HC/8-ST**	**19 12 79 9**	
	9	40	**MVSTBW 2,5 HC/9-ST**	**19 12 80 9**	
	10	45	**MVSTBW 2,5 HC/10-ST**	**19 12 81 2**	
	11	50	**MVSTBW 2,5 HC/11-ST**	**19 12 82 5**	
	12	55	**MVSTBW 2,5 HC/12-ST**	**19 12 83 8**	
COMBICON HC plugs, 5.08 mm pitch, plug-in direction vertical to the conductor axis, connection point facing the rippled wall (W) of the header, color: green	2	5.08	**MVSTBW 2,5 HC/2-ST-5,08**	**19 12 84 1**	50
	3	10.16	**MVSTBW 2,5 HC/3-ST-5,08**	**19 12 85 4**	
	4	15.24	**MVSTBW 2,5 HC/4-ST-5,08**	**19 12 86 7**	
	5	20.32	**MVSTBW 2,5 HC/5-ST-5,08**	**19 12 87 0**	
	6	25.40	**MVSTBW 2,5 HC/6-ST-5,08**	**19 12 88 3**	
	7	30.48	**MVSTBW 2,5 HC/7-ST-5,08**	**19 12 89 6**	
	8	35.56	**MVSTBW 2,5 HC/8-ST-5,08**	**19 12 90 6**	
	9	40.64	**MVSTBW 2,5 HC/9-ST-5,08**	**19 12 91 9**	
	10	45.72	**MVSTBW 2,5 HC/10-ST-5,08**	**19 12 92 2**	
	11	50.80	**MVSTBW 2,5 HC/11-ST-5,08**	**19 12 93 5**	
	12	55.88	**MVSTBW 2,5 HC/12-ST-5,08**	**19 12 94 8**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MVSTBW 2,5 HC/…-STF(-5,08)
Vertical Plugs
with Screw Flange
5.0 or 5.08 mm Pitch

The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.

Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.




Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC plugs, 5.0 mm pitch, with screw flange, color: green, connection point facing the rippled wall (W) of the header	2	5	**MVSTBW 2,5 HC/2-STF**	**19 12 95 1**	50
	3	10	**MVSTBW 2,5 HC/3-STF**	**19 12 96 4**	
	4	15	**MVSTBW 2,5 HC/4-STF**	**19 12 97 7**	
	5	20	**MVSTBW 2,5 HC/5-STF**	**19 12 98 0**	
	6	25	**MVSTBW 2,5 HC/6-STF**	**19 12 99 3**	
	7	30	**MVSTBW 2,5 HC/7-STF**	**19 13 00 2**	
	8	35	**MVSTBW 2,5 HC/8-STF**	**19 13 01 5**	
	9	40	**MVSTBW 2,5 HC/9-STF**	**19 13 02 8**	
	10	45	**MVSTBW 2,5 HC/10-STF**	**19 13 03 1**	
	11	50	**MVSTBW 2,5 HC/11-STF**	**19 13 04 4**	
	12	55	**MVSTBW 2,5 HC/12-STF**	**19 13 05 7**	
COMBICON HC plugs, 5.08 mm pitch, with screw flange, color: green, connection point facing the rippled wall (W) of the header	2	5.08	**MVSTBW 2,5 HC/2-STF-5,08**	**19 13 06 0**	50
	3	10.16	**MVSTBW 2,5 HC/3-STF-5,08**	**19 13 07 3**	
	4	15.24	**MVSTBW 2,5 HC/4-STF-5,08**	**19 13 08 6**	
	5	20.32	**MVSTBW 2,5 HC/5-STF-5,08**	**19 13 09 9**	
	6	25.40	**MVSTBW 2,5 HC/6-STF-5,08**	**19 13 10 9**	
	7	30.48	**MVSTBW 2,5 HC/7-STF-5,08**	**19 13 11 2**	
	8	35.56	**MVSTBW 2,5 HC/8-STF-5,08**	**19 13 12 5**	
	9	40.64	**MVSTBW 2,5 HC/9-STF-5,08**	**19 13 13 8**	
	10	45.72	**MVSTBW 2,5 HC/10-STF-5,08**	**19 13 14 1**	
	11	50.80	**MVSTBW 2,5 HC/11-STF-5,08**	**19 13 15 4**	
	12	55.88	**MVSTBW 2,5 HC/12-STF-5,08**	**19 13 16 7**	
(1) **Coding profile,** is inserted into the groove on the plug, red insulating material			**CP-MSTB**	**17 34 63 4**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data

Dimensions		see description on page 13		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	–		
Pin dimensions	[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	630
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / 2.5		
Maximum load current / cross section	[A]/[mm²]	16 / 2.5		
Capacity connection				
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.2 - 2.5 / 0.2 - 2.5 / 24 - 12		
Stranded with ferrule without / with plastic sleeve	[mm²]	0.25 - 2.5 / 0.25 - 2.5		
Multiple connection (2 conductors with same cross section)				
Solid / stranded	[mm²]	0.2 - 1 / 0.2 - 1.5		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 1		
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1.5		
Stripping length	[mm]	7		
Internal cylindrical gauge (IEC 60 947-1)		A 3		
Thread		M 3		
Torque	[Nm]	0.5 - 0.6		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		

MSTBA 2,5 HC/…-G(-5,08)
5.0 or 5.08 mm Pitch




The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.


Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.

Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.


Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC headers, 5.0 mm pitch, plug-in direction parallel to the p.c.b., color: green	2	5	**MSTBA 2,5 HC/2-G**	**19 23 75 9**	50
	3	10	**MSTBA 2,5 HC/3-G**	**19 23 76 2**	
	4	15	**MSTBA 2,5 HC/4-G**	**19 23 77 5**	
	5	20	**MSTBA 2,5 HC/5-G**	**19 23 78 8**	
	6	25	**MSTBA 2,5 HC/6-G**	**19 23 79 1**	
	7	30	**MSTBA 2,5 HC/7-G**	**19 23 80 1**	
	8	35	**MSTBA 2,5 HC/8-G**	**19 23 81 4**	
	9	40	**MSTBA 2,5 HC/9-G**	**19 23 82 7**	
	10	45	**MSTBA 2,5 HC/10-G**	**19 23 83 0**	
	11	50	**MSTBA 2,5 HC/11-G**	**19 23 84 3**	
	12	55	**MSTBA 2,5 HC/12-G**	**19 23 85 6**	
COMBICON HC headers, 5.08 mm pitch, plug-in direction parallel to the p.c.b., color: green	2	5.08	**MSTBA 2,5 HC/2-G-5,08**	**19 23 86 9**	50
	3	10.16	**MSTBA 2,5 HC/3-G-5,08**	**19 23 87 2**	
	4	15.24	**MSTBA 2,5 HC/4-G-5,08**	**19 23 88 5**	
	5	20.32	**MSTBA 2,5 HC/5-G-5,08**	**19 23 89 8**	
	6	25.40	**MSTBA 2,5 HC/6-G-5,08**	**19 23 90 8**	
	7	30.48	**MSTBA 2,5 HC/7-G-5,08**	**19 23 91 1**	
	8	35.56	**MSTBA 2,5 HC/8-G-5,08**	**19 23 92 4**	
	9	40.64	**MSTBA 2,5 HC/9-G-5,08**	**19 23 93 7**	
	10	45.72	**MSTBA 2,5 HC/10-G-5,08**	**19 23 94 0**	
	11	50.80	**MSTBA 2,5 HC/11-G-5,08**	**19 12 95 3**	
	12	55.88	**MSTBA 2,5 HC/12-G-5,08**	**19 12 96 6**	
(1) **Coding section,** inserted into the recess in the header, red insulating material			**CR-MSTB**	**17 34 40 1**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		

Technical data				
Dimensions		see description		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	1.4		
Pin dimensions	[mm]x[mm]	1 x 1		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	IIIa		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	400
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / –		
Maximum load current / cross section	[A]/[mm²]	16 / –		
Insulating material		PBT		
Inflammability class in acc. with UL 94		V0		





MSTBVA 2,5 HC/…-G(-5,08)
5.0 or 5.08 mm Pitch



The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.


Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.


Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC headers vertical,					
5.0 mm pitch, color: green,	2	5	**MSTBVA 2,5 HC/2-G**	**19 24 19 8**	50
plug-in direction vertical to the p.c.b.	3	10	**MSTBVA 2,5 HC/3-G**	**19 24 20 8**	
	4	15	**MSTBVA 2,5 HC/4-G**	**19 24 21 1**	
	5	20	**MSTBVA 2,5 HC/5-G**	**19 24 22 4**	
	6	25	**MSTBVA 2,5 HC/6-G**	**19 24 23 7**	
	7	30	**MSTBVA 2,5 HC/7-G**	**19 24 24 0**	
	8	35	**MSTBVA 2,5 HC/8-G**	**19 24 25 3**	
	9	40	**MSTBVA 2,5 HC/9-G**	**19 24 26 6**	
	10	45	**MSTBVA 2,5 HC/10-G**	**19 24 27 9**	
	11	50	**MSTBVA 2,5 HC/11-G**	**19 24 28 2**	
	12	55	**MSTBVA 2,5 HC/12-G**	**19 24 29 5**	
COMBICON HC headers vertical,					
5.08 mm pitch, color: green,	2	5.08	**MSTBVA 2,5 HC/2-G-5,08**	**19 24 30 5**	50
plug-in direction vertical to the p.c.b.	3	10.16	**MSTBVA 2,5 HC/3-G-5,08**	**19 24 31 8**	
	4	15.24	**MSTBVA 2,5 HC/4-G-5,08**	**19 24 32 1**	
	5	20.32	**MSTBVA 2,5 HC/5-G-5,08**	**19 24 33 4**	
	6	25.40	**MSTBVA 2,5 HC/6-G-5,08**	**19 24 34 7**	
	7	30.48	**MSTBVA 2,5 HC/7-G-5,08**	**19 24 35 0**	
	8	35.56	**MSTBVA 2,5 HC/8-G-5,08**	**19 24 36 3**	
	9	40.64	**MSTBVA 2,5 HC/9-G-5,08**	**19 24 37 6**	
	10	45.72	**MSTBVA 2,5 HC/10-G-5,08**	**19 24 38 9**	
	11	50.80	**MSTBVA 2,5 HC/11-G-5,08**	**19 24 39 2**	
	12	55.88	**MSTBVA 2,5 HC/12-G-5,08**	**19 24 40 2**	
(1) **Coding section,** inserted into the recess in the header, red insulating material			**CR-MSTB**	**17 34 40 1**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		


Technical data

Dimensions		see description		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	1.4		
Pin dimensions	[mm]x[mm]	1 x 1		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	400
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / –		
Maximum load current / cross section	[A]/[mm²]	16 / –		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		





MSTB 2,5 HC/…-GF(-5,08) with Screw Flange 5.0 or 5.08 mm Pitch



The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.


Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.


Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC headers,					
5.0 mm pitch, color: green,	2	5	**MSTB 2,5 HC/2-GF**	**19 23 97 9**	50
with threaded flange,	3	10	**MSTB 2,5 HC/3-GF**	**19 23 98 2**	
plug-in direction parallel to the p.c.b.	4	15	**MSTB 2,5 HC/4-GF**	**19 23 99 5**	
	5	20	**MSTB 2,5 HC/5-GF**	**19 24 00 4**	
	6	25	**MSTB 2,5 HC/6-GF**	**19 24 01 7**	
	7	30	**MSTB 2,5 HC/7-GF**	**19 24 02 0**	
	8	35	**MSTB 2,5 HC/8-GF**	**19 24 03 3**	
	9	40	**MSTB 2,5 HC/9-GF**	**19 24 04 6**	
	10	45	**MSTB 2,5 HC/10-GF**	**19 24 05 9**	
	11	50	**MSTB 2,5 HC/11-GF**	**19 24 06 2**	
	12	55	**MSTB 2,5 HC/12-GF**	**19 24 07 5**	
COMBICON HC headers,					
5.08 mm pitch, color: green,	2	5.08	**MSTB 2,5 HC/2-GF-5,08**	**19 24 08 8**	50
with threaded flange	3	10.16	**MSTB 2,5 HC/3-GF-5,08**	**19 24 09 1**	
plug-in direction parallel to the p.c.b.	4	15.24	**MSTB 2,5 HC/4-GF-5,08**	**19 24 10 1**	
	5	20.32	**MSTB 2,5 HC/5-GF-5,08**	**19 24 11 4**	
	6	25.40	**MSTB 2,5 HC/6-GF-5,08**	**19 24 12 7**	
	7	30.48	**MSTB 2,5 HC/7-GF-5,08**	**19 24 13 0**	
	8	35.56	**MSTB 2,5 HC/8-GF-5,08**	**19 24 14 3**	
	9	40.64	**MSTB 2,5 HC/9-GF-5,08**	**19 24 15 6**	
	10	45.72	**MSTB 2,5 HC/10-GF-5,08**	**19 24 16 9**	
	11	50.80	**MSTB 2,5 HC/11-GF-5,08**	**19 24 17 2**	
	12	55.88	**MSTB 2,5 HC/12-GF-5,08**	**19 24 18 5**	
(1) **Coding section,** inserted into the recess in the header, red insulating material			**CR-MSTB**	**17 34 40 1**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		


Technical data

Dimensions		see description		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	1.4		
Pin dimensions	[mm]x[mm]	1 x 1		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	IIIa		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	400
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / –		
Maximum load current / cross section	[A]/[mm²]	16 / –		
Insulating material		PBT		
Inflammability class in acc. with UL 94		V0		





MSTBV 2,5 HC/…-GF(-5,08) with Screw Flange 5.0 or 5.08 mm Pitch



The designation "HC" is printed in red to provide clear identification of "high current" plugs and headers.


Only the MSTB 2,5 HC headers provided are allowed to be used for carrying the higher current load of 16 A.


Note:
Only actuate COMBICON plug connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
COMBICON HC headers vertical,					
5.0 mm pitch, color: green,	2	5	**MSTBV 2,5 HC/2-GF**	**19 24 41 5**	50
with threaded flange,	3	10	**MSTBV 2,5 HC/3-GF**	**19 24 42 8**	
plug-in direction vertical to the p.c.b.	4	15	**MSTBV 2,5 HC/4-GF**	**19 24 43 1**	
	5	20	**MSTBV 2,5 HC/5-GF**	**19 24 44 4**	
	6	25	**MSTBV 2,5 HC/6-GF**	**19 24 45 7**	
	7	30	**MSTBV 2,5 HC/7-GF**	**19 24 46 0**	
	8	35	**MSTBV 2,5 HC/8-GF**	**19 24 47 3**	
	9	40	**MSTBV 2,5 HC/9-GF**	**19 24 48 6**	
	10	45	**MSTBV 2,5 HC/10-GF**	**19 24 49 9**	
	11	50	**MSTBV 2,5 HC/11-GF**	**19 24 50 9**	
	12	55	**MSTBV 2,5 HC/12-GF**	**19 24 51 2**	
COMBICON HC headers vertical,					
5.08 mm pitch, color: green,	2	5.08	**MSTBV 2,5 HC/2-GF-5,08**	**19 24 52 5**	50
with threaded flange	3	10.16	**MSTBV 2,5 HC/3-GF-5,08**	**19 24 53 8**	
plug-in direction vertical to the p.c.b.	4	15.24	**MSTBV 2,5 HC/4-GF-5,08**	**19 24 54 1**	
	5	20.32	**MSTBV 2,5 HC/5-GF-5,08**	**19 24 55 4**	
	6	25.40	**MSTBV 2,5 HC/6-GF-5,08**	**19 24 56 7**	
	7	30.48	**MSTBV 2,5 HC/7-GF-5,08**	**19 24 57 0**	
	8	35.56	**MSTBV 2,5 HC/8-GF-5,08**	**19 24 58 3**	
	9	40.64	**MSTBV 2,5 HC/9-GF-5,08**	**19 24 59 6**	
	10	45.72	**MSTBV 2,5 HC/10-GF-5,08**	**19 24 60 6**	
	11	50.80	**MSTBV 2,5 HC/11-GF-5,08**	**19 24 61 9**	
	12	55.88	**MSTBV 2,5 HC/12-GF-5,08**	**19 24 62 2**	
(1) **Coding section,** inserted into the recess in the header, red insulating material			**CR-MSTB**	**17 34 40 1**	100
(2) **Marker card,** with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			**SK 5/3,8 or SK 5,08/3,8** (see COMBICON catalog)		


Technical data

Dimensions		see description		
Pitch	[mm]	5 / 5.08		
Hole diameter	[mm]	1.4		
Pin dimensions	[mm]x[mm]	1 x 1		
Technical data in accordance with IEC/ DIN VDE				
Insulating material group	–	I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2
Rated voltage	[V]	250	320	400
Rated surge voltage	[kV]	4	4	4
Nominal current / cross section	[A]/[mm²]	16 / –		
Maximum load current / cross section	[A]/[mm²]	16 / –		
Insulating material		PA		
Inflammability class in acc. with UL 94		V0		







Descriptions




MSTB 2,5 HC/…-ST(-5,08)




MSTB 2,5 HC/…-STF(-5,08)




MVSTBR 2,5 HC/…-ST(-5.08)



MVSTBR 2,5 HC/…-STF(-5,08)



MVSTBW 2,5 HC/…-STF(-5,08)



MVSTBW 2,5 HC/…-STF(-5,08)

© PHOENIX CONTACT 15.03.01 TNR: 5099553-01 http://www.phoenixcontact.com

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9