


SINGLE BREAK, SNAP-ACTION, COMMERCIAL & MILITARY GRADES, SUBMINIATURE, TWO WIDTHS, INTEGRAL LEVERS



Shown are examples of available lever styles.

B2-5 Integral Lever Basic Switches

B2-5 series basic switches feature integral actuating levers. The lever is built-in so that the switch and actuator are one assembly.

Making the lever actuator an integral part of the basic switch case makes sense and saves money, too. Better precision, no auxiliary parts for you to assemble, and more variety add up to a cost saving proposition.

Lever Style	Catalog Number	STANDARD OPERATIONAL CHARACTERISTICS					
		Operating Force (max ounces)	Release Force (min ounces)	Pretravel (max inches)	Overtravel (min inches)	Move't Differ'l (max inches)	Operating Point (inches)
Short Lever	B2-500111	1.76	0.32	0.065	0.014	0.020	0.330 +/- 0.045
Medium Lever	B2-500211	1.10	0.18	0.115	0.025	0.035	0.330 +/- 0.045
Long Lever	B2-500311	0.71	0.11	0.185	0.046	0.060	0.330 +/- 0.045
Short Formed "U" Lever	B2-500411	2.10	0.39	0.050	0.010	0.015	0.553 +/- 0.035
Long Formed "U" Lever	B2-500511	1.10	0.18	0.105	0.022	0.035	0.572 +/- 0.070
Lever Style with Hole	B2-500611	1.10	0.18	0.115	0.025	0.035	0.330 +/- 0.045
Short "V" Lever	B2-501211	3.00	0.57	0.042	0.010	0.010	0.419 +/- 0.030
Roller Sleeve Sideways	B2-501611	2.29	0.43	0.065	0.008	0.020	0.560 +/- 0.045
Short "L" Lever	B2-501711	3.00	0.57	0.036	0.008	0.009	0.411 +/- 0.028
Short Flat "V" Lever	B2-501811	2.20	0.40	0.049	0.010	0.015	0.421 +/- 0.037
Roller Lever in Line	B2-501911	2.29	0.43	0.070	0.008	0.020	0.559 +/- 0.050
Long Roller Lever in Line	B2-502011	1.00	0.17	0.125	0.020	0.040	0.552 +/- 0.100

B2-5 PART NUMBER CODE

B2-5 X X X

Lever Style

- 001. Short Straight
- 002. Medium Straight
- 003. Long Straight
- 004. Short Formed "U"
- 005. Long Formed "U"
- 006. With Hole
- 012. Short "V"
- 016. Roller Sleeve Sideways
- 017. Short "L"
- 018. Short Flat "V"
- 019. Roller Lever in Line
- 020. Long Roller Lever in Line

Terminal Style or Wire Length

- 1. Single Solder Turret
- 2. Double Solder Turret
- 3. Quick Connect*
- 4. PC Pin 0.150" lg.
- 5. PC Pin 0.270" lg.
- 6. PC Pin 0.090" lg.
- 7. Right Angle PC Pin
- 9. Right Angle**
- A. With Wires 06.0" lg.
- B. With Wires 12.0" lg.
- C. With Wires 18.0" lg.
- D. With Wires 24.0" lg.
- E. With Wires 30.0" lg.

X

Contact Material



- 1. Silver/Gold - High Current
- 3. Silver/Gold - Low Current

* Mates with AMP .058" receptacles

** Opposite of 7


BASIC SWITCHES

TERMINAL STYLES AND WIRE LENGTHS




WIRE LENGTH FOR A, B, C, D & E


WIRE LENGTH CODE	DIM. "X"	DIM. "Y"
A	06.00±.38	06.09±.38
B	12.00±.50	12.09±.50
C	18.00±.50	18.09±.50
D	24.00±.50	24.09±.50
E	30.00±.75	30.09±.75




**TERMINAL STYLE 1
SINGLE SOLDER TURRET**




TERMINAL STYLE 2 DOUBLE SOLDER TURRET




**TERMINAL STYLE 3
QUICK CONNECT
MATES WITH AMP .058 INCH RECEPTACLES**





**TERMINAL STYLE 4
PRINTED CIRCUIT PIN 0.150" LONG**





**TERMINAL STYLE 5
PRINTED CIRCUIT PIN 0.270" LONG**



**TERMINAL STYLE 6
PRINTED CIRCUIT PIN 0.090" LONG**




**TERMINAL STYLE 7
RIGHT ANGLE PRINTED CIRCUIT PIN**



**TERMINAL STYLE 9
RIGHT ANGLE, OPPOSITE OF 7**

SINGLE BREAK, SNAP-ACTION, COMMERCIAL & MILITARY GRADES, SUBMINIATURE, TWO WIDTHS, INTEGRAL LEVERS

B2-5 LEVER STYLES









B2 BASICS WITH INTEGRAL LEVERS

B2-5
BASIC
SWITCHES

SINGLE BREAK, SNAP-ACTION, COMMERCIAL & MILITARY GRADES, SUBMINIATURE, TWO WIDTHS, INTEGRAL LEVERS

B2-5 LEVER STYLES

 OPERATE FORCE: 3.00 OZ. MAX. RELEASE FORCE: .57 OZ. MIN. PRETRAVEL: .042 MAX. OVERTRAVEL: .010 MIN. MOVE'T DIFFER'L: .010 MAX. TOP OF LOBE TO BE IN LINE WITH Ø(.088) MTG. HOLE ±.004 .090 W. X .015 THICK LEVER .419±.030 OPER. POINT LEVER STYLE 012 SHORT "V" C NO NC	 OPERATE FORCE 2.20 OZ. MAX. RELEASE FORCE: .40 OZ. MIN. PRETRAVEL: .049 MAX. OVERTRAVEL: .010 MIN. MOVE'T DIFFER'L: .015 MAX. .090 W. X .015 THICK LEVER .421±.037 OPER. POINT LEVER STYLE 018 SHORT FLAT "V" C NO NC
 OPERATE FORCE: 2.29 OZ. MAX. RELEASE FORCE: .43 OZ. MIN. PRETRAVEL: .065 MAX. OVERTRAVEL: .008 MIN. MOVE'T DIFFER'L: .020 MAX. .076 AT O.P. .560±.045 OPER. POINT Ø.188±.015 ALUM. ALLOY ROLLER LEVER STYLE 016 ROLLER SLEEVE SIDWAYS C NO NC	 OPERATE FORCE 2.29 OZ. MAX. RELEASE FORCE: .43 OZ. MIN. PRETRAVEL: .070 MAX. OVERTRAVEL: .008 MIN. MOVE'T DIFFER'L: .020 MAX. .069 AT O.P. .559±.050 OPER. POINT Ø.188±.015 ALUM. ALLOY ROLLER LEVER STYLE 019 ROLLER LEVER IN LINE C NO NC
 OPERATE FORCE: 3.00 OZ. MAX. RELEASE FORCE: .57 OZ. MIN. PRETRAVEL: .036 MAX. OVERTRAVEL: .008 MIN. MOVE'T DIFFER'L: .009 MAX. .090 W. X .015 THICK LEVER .411±.028 OPER. POINT .047 LEVER STYLE 017 SHORT "L" C NO NC	 OPERATE FORCE: 1.00 OZ. MAX. RELEASE FORCE: .17 OZ. MIN. PRETRAVEL: .125 MAX. OVERTRAVEL: .020 MIN. MOVE'T DIFFER'L: .040 MAX. .524 AT O.P. .552±.100 OPER. POINT Ø.188±.015 ALUM. ALLOY ROLLER LEVER STYLE 020 LONG ROLLER LEVER IN LINE C NO NC

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9