

## HT23-601C

NEMA 23 Step Motor with 10 Foot Shielded Cable



### Product Features

- 2-phase hybrid step motor
- High torque design
- Standard NEMA 23 dimensions
- Optimized for 24 – 48 VDC bus voltage
- Please call for pricing regarding encoder and encoder with cover options



## Description

### Product Description:

The HT23-601C two-phase stepper motor is designed for use with the ST5 and STR4 stepper drives and is suitable for a wide range of motion control applications. The motor is optimized for use with DC powered drives and comes with an integral 10 ft shielded cable.

Single and double shaft versions are available. The HT23-601DC-ZAC includes an optical encoder with 10 foot cable and rugged metal cover.











The motor is terminated with 8 motor leads plus a ground lead.

## Specifications

<b>Part Number:</b>	HT23-601C
<b>Frame Size:</b>	NEMA 23
<b>Motor Type:</b>	High torque
<b>Part Number w/Double Shaft:</b>	HT23-601DC
<b>Part Number w/Encoder:</b>	HT23-601DC-ZAA
<b>Part Number w/Encoder &amp; Cover:</b>	HT23-601DC-ZAC
<b>Motor Length:</b>	3.20 inches
<b>Number of Lead Wires:</b>	8
<b>Lead Wire Configuration:</b>	shielded cable, no connector
<b>Lead Wire/Cable Length:</b>	10 feet inches
<b>Lead Wire Gauge:</b>	22 AWG
<b>Unipolar Holding Torque:</b>	191 oz-in
<b>Bipolar Holding Torque:</b>	269 oz-in
<b>Step Angle:</b>	1.8 deg
<b>Bipolar Series Current:</b>	2.12 A/phase
<b>Bipolar Series Resistance:</b>	2.2 Ohms/phase
<b>Bipolar Series Inductance:</b>	6.8 mH/phase
<b>Bipolar Parallel Current:</b>	4.24 A/phase
<b>Bipolar Parallel Resistance:</b>	0.7 Ohms/phase
<b>Bipolar Parallel Inductance:</b>	1.7 mH/phase
<b>Unipolar Current:</b>	3.00 A/phase
<b>Unipolar Resistance:</b>	1.1 Ohms/phase
<b>Unipolar Inductance:</b>	1.7 mH/phase
<b>Rotor Inertia:</b>	0.0064 oz-in-sec <sup>2</sup>
<b>Integral Gearhead:</b>	No
<b>Weight:</b>	2.2 lbs

<b>Weight:</b>	2.2 lbs
<b>Storage Temperature:</b>	-30 +70 °C
<b>Operating Temperature:</b>	-20 +50 °C
<b>Insulation Class:</b>	B
<b>Shaft Run Out:</b>	0.002 inch T.I.R. max
<b>Radial Play:</b>	0.001 inch max w/ 1.1 lb load
<b>End Play:</b>	0.003 inch max w/ 1.1 lb load
<b>Perpendicularity:</b>	0.004 inches
<b>Concentricity:</b>	0.002 inches

## Downloads

<b>Datasheet:</b>	<a href="http://s3.amazonaws.com/applied-motion-pdf/HT23-601C.pdf">http://s3.amazonaws.com/applied-motion-pdf/HT23-601C.pdf</a>
<b>2D Drawing:</b>	<a href="#"> HT23-601C_RevC.pdf</a> <a href="#"> HT23-601DC_RevC.pdf</a> <a href="#"> HT23-601DC-ZAA_RevA.pdf</a> <a href="#"> HT23-601DC-ZAC_RevA.pdf</a>
<b>3D Drawing:</b>	<a href="#"> HT23-601C.igs</a> <a href="#"> HT23-601DC.igs</a> <a href="#"> HT23-601DC-ZAA.igs</a> <a href="#"> HT23-601DC-ZAC.igs</a>
<b>Speed-Torque Curves:</b>	<a href="#"> ST_speed-torque.pdf</a> <a href="#"> STR_speed-torque.pdf</a> <a href="#"> STR2_speed-torque.pdf</a>

## Products in the Series *Cabled Step Motors*

Part Number	Frame Size	Length	Holding Torque	Series Current	Parallel Current	Rotor Inertia
<a href="#">HT23-552</a>	NEMA 23	1.71	84.4	0.71	1.41	1.70E-03
<a href="#">HT23-553</a>	NEMA 23	2.17	167	0.71	1.41	4.25E-03
<a href="#">HT23-554</a>	NEMA 23	3.05	255	0.71	1.41	6.80E-03
<a href="#">HT23-598C</a>	NEMA 23	2.35	158	2.12	4.24	0.0036
<a href="#">HT23-601C</a>	NEMA 23	3.20	269	2.12	4.24	0.0064
<a href="#">HT34-495</a>	NEMA 34	3.11	555	2.15	4.30	2.27E-02
<a href="#">HT34-496</a>	NEMA 34	4.63	1110	2.05	4.10	4.53E-02
<a href="#">HT34-497</a>	NEMA 34	6.14	1694	2.55	5.10	6.80E-02
<a href="#">HT34-506C</a>	NEMA 34	4.94	1260	2.8	5.6	0.0387
<a href="#">HT34-696</a>	NEMA 34	4.59	1110	2.05	4.1	3.87E-02
<a href="#">HW23-598</a>	NEMA 23	2.34	158	2.12	4.24	3.68E-03
<a href="#">HW23-601</a>	NEMA 23	3.21	269	2.12	4.24	6.51E-03
<a href="#">HW23-753</a>	NEMA 23	2.19	153	0.71	1.41	3.12E-03
<a href="#">HW23-754</a>	NEMA 23	3.23	227	0.71	1.41	6.51E-03
<a href="#">HW24-108</a>	NEMA 24	3.72	354	NA	4.0	1.27E-02
<a href="#">HW34-506</a>	NEMA 34	5.0	1260	2.8	5.6	3.87E-02
<a href="#">HW34-696</a>	NEMA 34	4.59	1062	2.03	4.06	3.87E-02

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9