

LOW-PEAK®

Dual-Element, Time-Delay Fuses
Class RK1 – 250 Volt

LPN-RK

 $\frac{1}{10}$ -60A

Catalog Symbol: LPN-RK_SP

Dual-Element, Time-Delay – 10 seconds (minimum) at 500% rated current (8 seconds for 0-30A sizes)

Current-Limiting

Ampere Rating: $\frac{1}{10}$ to 60AVoltage Rating: 250Vac (or less)
125Vdc (or less)

Interrupting Rating:

AC: 300,000A RMS Sym.

DC: 100,000 Amperes

Agency Information:

UL Listed – Special Purpose*, Guide JFHR, File E56412

CSA Certified (200,000AIR), Class 1422-02, File 53787

Class RK1 per CSA C22.2, No. 248.12

*Meets all performance requirements of UL Standard 248-12 for Class RK1 fuses.

Catalog Numbers


LPN-RK- $\frac{1}{10}$ SP	LPN-RK-2SP	LPN-RK-9SP
LPN-RK- $\frac{1}{100}$ SP	LPN-RK-2 $\frac{1}{4}$ SP	LPN-RK-10SP
LPN-RK- $\frac{2}{10}$ SP	LPN-RK-2 $\frac{1}{2}$ SP	LPN-RK-12SP
LPN-RK- $\frac{3}{10}$ SP	LPN-RK-2 $\frac{3}{10}$ SP	LPN-RK-15SP
LPN-RK- $\frac{4}{10}$ SP	LPN-RK-3SP	LPN-RK-17 $\frac{1}{2}$ SP
LPN-RK- $\frac{1}{2}$ SP	LPN-RK-3 $\frac{1}{10}$ SP	LPN-RK-20SP
LPN-RK- $\frac{6}{10}$ SP	LPN-RK-3 $\frac{1}{2}$ SP	LPN-RK-25SP
LPN-RK- $\frac{8}{10}$ SP	LPN-RK-4SP	LPN-RK-30SP
LPN-RK-1SP	LPN-RK-4 $\frac{1}{2}$ SP	LPN-RK-35SP
LPN-RK-1 $\frac{1}{4}$ SP	LPN-RK-5SP	LPN-RK-40SP
LPN-RK-1 $\frac{1}{2}$ SP	LPN-RK-5 $\frac{1}{10}$ SP	LPN-RK-45SP
LPN-RK-1 $\frac{3}{10}$ SP	LPN-RK-6SP	LPN-RK-50SP
LPN-RK-1 $\frac{6}{10}$ SP	LPN-RK-6 $\frac{1}{2}$ SP	LPN-RK-60SP
LPN-RK-1 $\frac{9}{10}$ SP	LPN-RK-8SP	—

Carton Quantity and Weight

Ampere Ratings	Carton Qty.	Weight**	
		Lbs.	Kg.
0-30	10	0.5	0.227
35-60	10	1.2	0.544

**Weight per carton.

Dimensional Data




Features:

- Current-limitation for maximum short-circuit protection.
- Type 2 protection for IEC and NEMA starters when properly sized.
- High inrush current motor protection.
- Time-delay permits 130% FLA sizing for back-up motor protection.
- Protection against single-phase motor damage.
- Low watt loss power consumption.
- Electrically isolated end caps.
- 125Vdc, UL Listed.

Fuse Reducers For Class R Fuses

Equipment Fuse Clips	Desired Fuse (Case) Size	Catalog Number (Pairs) 250V
60A	30A	No. 263-R
100A	30A	No. 213-R
	60A	No. 216-R
200A	60A	No. 226-R

Recommended fuseblocks for
Class R 250V fuses
See Data Sheet: 1110

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.



LOW-PEAK®

Dual-Element, Time-Delay Fuses
Class RK1 – 250 Volt


LPN-RK

 $\frac{1}{10}$ -60A

Time-Current Characteristic Curves—Average Melt



Current-Limitation Curves



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9