

ACE-925AP-U



High reliability magnetic bearing cooling system features low noise, high operating temperature and longer MTBF

Specifications


Input	Voltage	90 ~ 265 VAC Full Range			
	Frequency	47 ~ 63 Hz			
Output	Voltage	+5 V	+12 V	-5 V	-12 V
	Max. load	22 A	11 A	0.5 A	0.7 A
General	MTBF	100,000 hours			
	Temperature	Operating: 0°C ~ 50°C Storage: -25°C ~ 70°C			
	Dimensions	140 x 150 x 86 (mm)			
	Output Connector	1 x P8+P9, 4 x HDD/CDROM, 2 x FDD, 2 x SATA			

Ordering Information

Part No.	Description
ACE-925AP-U-RS	250 W AC-DC PS/2 AT Power Supply, with PFC

PS/2 DC Input ATX Type

ACE-828C



Specifications

Input Type	18 ~ 32 VDC				
Input Current	20 A (RMS)@24VDC		Inrush Current	5A Max for 24VDC	
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V
	8 A	25 A (2 A min.)	7 A (0.1 min.)	0.5 A	1 A
Ripple & Noise	+5 V, +3.3 V output are less than 50mV				
	+12 V, -5 V, -12 V, +5 Vsb output are less than 100mV				
Overvoltage Protection	+5 V: 5.7 V ~ 7.0 V				
Short Circuit Protection	Yes	Overload Protection		Yes	
Efficiency	65%				
Temperature	-20°C ~ 70°C (Operating), -40°C ~ 75°C (Storage)				
MTBF (hrs)	120,000				
Power Good Signal	Turn on delay time 100 ms to 500 ms				
Output Connector	1 x P8+P9, 1 x Extra +5V (P10), 4 x HDD/CDROM, 2 x FDD				

Ordering Information

Part No.	Description
ACE-828C-RS	250 W 24V DC input PS/2 Type ATX Power Supply

ACE-925A



Specifications


Input Type	85 ~ 265VAC Full Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		22 A (1A min.)	7 A (0.1A min.)	0.5 A	0.7 A	
Efficiency	68%					
Temperature	0°C ~ 50°C (Operating), -40°C ~ 75°C (Storage)					
MTBF (hrs)	130,000					
Output Connector	1 x P8+P9, 5 x HDD/CDROM, 2 x FDD					

Ordering Information

Part No.	Description
ACE-925A-RS	200 W AC-DC PS/2 AT Power Supply

PS/2 DC Input AT Type

ACE-932T



Specifications

Input Type	-40 ~ -70 VDC					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		33 A (1A min.)	8 A	0.5 A	3 A	
Efficiency	70%					
Temperature	-20°C ~ 70°C (Operating), -40°C ~ 75°C (Storage)					
MTBF (hrs)	140,000					
Output Connector	1 x P8+P9, 1 x Extra +5V (P10), 4 x HDD/CDROM, 2 x FDD					

Ordering Information

Part No.	Description
ACE-932T-RS	300W -48 V DC input PS/2 Type AT Power Supply

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9