

FEATURES

- HCMOS Output
- Optional Voltage Control for Frequency Tuning [VCTCXO]
- 7.0mm x 5.0mm Surface Mount Package
- Frequency Range 5 – 52 MHz
- Fundamental Crystal Design
- Operating Voltage, +3.0Vdc, +3.3Vdc or +5.0Vdc
- Overall Frequency Stability ± 4.6 ppm
- Operating Temperature to -40°C to $+85^{\circ}\text{C}$
- Tape & Reel Packaging Standard, EIA-418
- **RoHS/Green Compliant [6/6]**



APPLICATIONS

The Model 589, a quartz based analog TCXO with HCMOS output and optional frequency tuning, is suitable for applications requiring Stratum 3 performance such as base stations, Microcells, Femtocells, 1588 and Synchronous Ethernet timing, wireless communications, test and measurement.

ORDERING INFORMATION



* Frequency vs. Temperature Only

1] Only available with temperature range code "C".

**Not all performance combinations and frequencies may be available.
Contact your local CTS Representative or CTS Customer Service for availability.**

ELECTRICAL CHARACTERISTICS

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNIT | | |
|--------------------------------|---------------------------------|--|---------------------|--------------------|---------------------|--------|---|------|
| Maximum Supply Voltage | V _{CC} | - | -0.6 | - | 6.0 | V | | |
| Maximum Control Voltage | V _C | - | -0.5 | - | V _{CC} | V | | |
| Storage Temperature | T _{STG} | - | -40 | - | +100 | °C | | |
| Operating Temperature | T _A | - | -20 | +25 | +70 | °C | | |
| Order Code 'C' | | | -40 | | +85 | | | |
| Order Code 'I' | | | | | | | | |
| Frequency Range | f ₀ | - | 5 | - | 52 | MHz | | |
| Supply Voltage | V _{CC} | ±5% | 2.85 | 3.0 | 3.15 | V | | |
| Order Code 'R' | | | 3.14 | 3.3 | 3.47 | | | |
| Order Code 'L' | | | 4.75 | 5.0 | 5.25 | | | |
| Order Code 'S' | | | | | | | | |
| Supply Current | I _{CC} | - | - | - | 6.0 | mA | | |
| Frequency Stability | Δf/f ₀ | Reference to f ₀ , Including 20 years aging @ +25°C, at time of shipment | - | - | 4.60 | ± ppm | | |
| Overall Frequency Stability | | | - | - | 1.00 | | | |
| vs. Initial Calibration | | | - | - | 0.28 | | | |
| vs. Operating Temperature | | | - | - | 0.14 | | | |
| vs. Supply Voltage | | | Δf/f ₂₅ | ±5% change @ +25°C | - | | - | 0.40 |
| vs. Load | | | - | ±5% change | - | | - | 0.10 |
| vs. Aging | - | 20 years @ +40°C | - | - | 2.80 | | | |
| Holdover | Δf/f ₀ | [Fmax. - Fmin.]/2, over 24 hours | - | - | 0.32 | | | |
| Control Voltage | V _C | - | 0.5 | 1.5 | 2.5 | V | | |
| Frequency Tuning [VCTCXO Only] | - | V _C = 1.5V ±1.0V, monotonic positive | | 5 - 8 | | ± ppm | | |
| V _C Input Impedance | Z _{V_C} | - | 100 | - | - | kOhm | | |
| Output Waveform | | HCMOS | | | | | | |
| Output Voltage Levels | | | | | | | | |
| Logic '1' Level | V _{OH} | HCMOS Load | 0.9*V _{CC} | - | - | V | | |
| Logic '0' Level | V _{OL} | HCMOS Load | - | - | 0.1*V _{CC} | | | |
| Output Load | C _L | - | - | - | 15 | pF | | |
| Rise and Fall Time | T _R , T _F | @ 20% - 80% Levels | - | 3.0 | 6.0 | ns | | |
| Output Duty Cycle | SYM | @ 50% Level | 45 | - | 55 | % | | |
| Start Up Time | T _S | - | - | - | 2 | ms | | |
| Enable Function | | | | | | | | |
| Enable Input Voltage | V _{IH} | Pin 8 Logic '1', Output Enabled | 0.7*V _{CC} | - | - | V | | |
| Disable Input Voltage | V _{IL} | Pin 8 Logic '0', Output Disabled [High Imp] | - | - | 0.3*V _{CC} | | | |
| Phase Noise ¹ | - | - | | | | dBc/Hz | | |

ELECTRICAL PARAMETERS

Notes:
1. Phase Noise performance may vary based on output frequency. See example plot at 10 MHz below.



TEST CIRCUIT – HCMOS LOAD



MECHANICAL SPECIFICATIONS

PACKAGE DRAWING



MARKING INFORMATION

1. M589 – CTS Model Series.
2. ● – Pin 1 identifier.
3. C – CTS identifier.
4. D – Date code. See Table II for codes.
5. xxx – Frequency Code.
6. Refer to document 016-1454-0, Frequency Code Tables.

NOTES

1. DO NOT make connections to non-labeled pins or castellations as they may have internal connections used in the manufacturing process.
2. Termination pads (e4); barrier plating is nickel [Ni] with gold [Au] flash plate.
3. Reflow conditions per JEDEC J-STD-020, 260°C maximum.
4. MSL = 1.

SUGGESTED SOLDER PAD GEOMETRY



D.U.T. PIN ASSIGNMENTS

| PIN | SYMBOL | DESCRIPTION |
|-----|----------|-----------------------------------|
| 1 | V_C | Control Voltage – VCTCXO [Note 1] |
| | | GND - TCXO |
| 2 | GND | Circuit & Package Ground |
| 3 | Output | HCMOS Output |
| 4 | V_{CC} | Supply Voltage |

NOTES

1. Connect to ground for TCXO [no AFC] option.

TABLE II – DATE CODE

| YEAR | | MONTH | | | | | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOV | DEC |
|------|------|-------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | | 2001 | 2005 | 2009 | 2013 | 2017 | | | | | | | | | | | | |
| 2001 | 2005 | 2009 | 2013 | 2017 | A | B | C | D | E | F | G | H | J | K | L | M | | |
| 2002 | 2006 | 2010 | 2014 | 2018 | N | P | Q | R | S | T | U | V | W | X | Y | Z | | |
| 2003 | 2007 | 2011 | 2015 | 2019 | a | b | c | d | e | f | g | h | j | k | l | m | | |
| 2004 | 2008 | 2012 | 2016 | 2020 | n | p | q | r | s | t | u | v | w | x | y | z | | |

PACKAGING INFORMATION [reference]

Device quantity is 1k pcs. maximum per 180mm reel.



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9