

## Snap-in markers - US-EMP (27X15) YE - 0828848

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Snap-in markers, Card, yellow, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: snapped into marker carrier, Lettering field: 27 x 15 mm



The illustration shows a version of the product

### Product Features

- The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The US-EMP ... UniSheet labeling range includes markers that can be fitted into existing CARRIER EMP ... label frames
- The perforated markers are easy to separate and can be easily fitted
- The sheets provide space for including function texts



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 16.0 g   |
| Custom tariff number                 | 39204910 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 26.9 mm |
| Width (a)  | 14.9 mm |
| Height     | 0.5 mm  |

#### Ambient conditions

|                                 |                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------|
| Ambient temperature (operation) | -30 °C ... 80 °C                                                                      |
| Recommended storage conditions  | 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended. |

#### General

## Snap-in markers - US-EMP (27X15) YE - 0828848

### Technical data

#### General

|                                                                     |                                  |
|---------------------------------------------------------------------|----------------------------------|
| Color                                                               | yellow                           |
| Components                                                          | Silicone-free                    |
| Flammability rating according to UL 94                              | V0                               |
| Material                                                            | PVC                              |
|                                                                     | PVC                              |
| Wipe resistance                                                     | DIN EN 61010-1 (VDE 0411-1)      |
| Number of individual labels                                         | 27                               |
| Number of individual labels per row                                 | 3                                |
| RoHS compliant                                                      | Yes                              |
| Printability                                                        | Thermal transfer                 |
| Device                                                              | 5146464 THERMOMARK CARD          |
|                                                                     | 5146451 THERMOMARK CARD-US-MAG1  |
| Ink ribbon                                                          | 0801371 THERMOMARK-RIBBON 110-TC |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02             |
| Result                                                              | Test passed                      |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03     |
| Test duration                                                       | 96 h                             |
| Wipe resistance test result                                         | Test passed                      |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02        |
| Test duration                                                       | 96 h                             |
| Salt spray testing result                                           | Test passed                      |
| Alternating condensation climate with SO2 test specification        | following DIN 50018:2013-05      |
| Climate level                                                       | AHT 1.0 S                        |
| Cycles                                                              | 2                                |
| Condensation test result                                            | Test passed                      |
| Wipe resistance of test specification inscriptions                  | IEC 61010-1:2010-06              |
| Result                                                              | Test passed                      |
| Foil strength                                                       | 500 µm                           |
| Marking mounting type                                               | snapped into marker carrier      |

#### Standards and Regulations

|                                        |                             |
|----------------------------------------|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0                          |

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
|------------|----------|

## Snap-in markers - US-EMP (27X15) YE - 0828848

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

##### Cover

Cover - CARRIER-EMP (1000X15) COVER - 0829520



Cover, transparent, unlabeled, Mounting type: Screws, rivets, Lettering field: 1000 x 15 mm

#### Magazine

## Snap-in markers - US-EMP (27X15) YE - 0828848

### Accessories

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards

---

### Marker carriers

Marker carriers - CARRIER-EMP (1000X15) GY - 0829366



Profile, for screwing or riveting, 1000 mm long, for accommodating UC und US materials, height: 15 mm

---

Marker carriers - CARRIER-EMP (1000X15) TR - 0829530



Marker carriers, transparent, unlabeled, Mounting type: Screws, rivets, Lettering field: 1000 x 15 mm

---

Marker carriers - CARRIER/L-EMP (1000X15) GY - 0829559



Profile, self-adhesive, 1000 mm long, for accommodating UC and US materials, height: 15 mm

---

Marker carriers - CARRIER/L-EMP (1000X15) TR - 0829560



Marker carriers, transparent, unlabeled, Mounting type: Adhesive, Lettering field: 1000 x 15 mm

## Snap-in markers - US-EMP (27X15) YE - 0828848

### Accessories

Marker carriers - CARRIER-EMP 22 (27X15) - 0827447



Marker carriers, black, unlabeled, Mounting type: Screws, rivets, Diameter: 22 mm, Lettering field: 27 x 15 mm

---

Marker carriers - CARRIER-EMLP 22 (27X15) - 0828986



Marker carriers, black, unlabeled, Mounting type: Screws, rivets, Diameter: 22 mm, Lettering field: 27 x 15 mm

---

Marker carriers - CARRIER-EMP (27X15) - 0827451



Marker carriers, black, unlabeled, Mounting type: Screws, rivets, Lettering field: 27 x 15 mm

---

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9