


# RWF Series

- High ripple capability
- Endurance with ripple current : 5,000 hours at 85°C
- Wide range of case sizes from  $\phi 50$  to  $\phi 100$
- RoHS Compliant




## SPECIFICATIONS

| Items                           | Characteristics                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                             |              |                                       |                 |                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|-----------------------------|--------------|---------------------------------------|-----------------|-------------------------------|
| Category                        | -25 to +85°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                    |                             |              |                                       |                 |                               |
| Temperature Range               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                             |              |                                       |                 |                               |
| Rated Voltage Range             | 350 to 450V <sub>dc</sub>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                    |                             |              |                                       |                 |                               |
| Capacitance Tolerance           | ±20% (M) (at 20°C, 120Hz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                    |                             |              |                                       |                 |                               |
| Leakage Current                 | I=0.02CV or 5mA, whichever is smaller.<br>Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 5 minutes)                                                                                                                                                                                                                                                                                                                                                                                           |                    |                             |              |                                       |                 |                               |
| Dissipation Factor (tan δ)      | 0.25 max. (at 20°C, 120Hz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                    |                             |              |                                       |                 |                               |
| Low Temperature Characteristics | Capacitance change $C(-25^{\circ}\text{C})/C(+20^{\circ}\text{C}) \geq 0.7$ (at 120Hz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                    |                             |              |                                       |                 |                               |
| Insulation Resistance           | When measured between the terminals that are connected to each other and to the mounting clamp on the insulating sleeve covering the case by using an insulation resistance meter of 500V <sub>dc</sub> , the insulation resistance shall not be less than 100MΩ.                                                                                                                                                                                                                                                                                       |                    |                             |              |                                       |                 |                               |
| Insulation Withstanding Voltage | When a voltage of 2,000V <sub>ac</sub> is applied for 1 minute between the terminals that are connected to each other and to the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.                                                                                                                                                                                                                                                                                                                       |                    |                             |              |                                       |                 |                               |
| Endurance                       | The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 5,000 hours at 85°C. <table border="1"> <tr> <td>Capacitance change</td> <td>≤ ±20% of the initial value</td> </tr> <tr> <td>D.F. (tan δ)</td> <td>≤ 200% of the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>≤ The initial specified value</td> </tr> </table>                                       | Capacitance change | ≤ ±20% of the initial value | D.F. (tan δ) | ≤ 200% of the initial specified value | Leakage current | ≤ The initial specified value |
| Capacitance change              | ≤ ±20% of the initial value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                    |                             |              |                                       |                 |                               |
| D.F. (tan δ)                    | ≤ 200% of the initial specified value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    |                             |              |                                       |                 |                               |
| Leakage current                 | ≤ The initial specified value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                    |                             |              |                                       |                 |                               |
| Shelf Life                      | The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours at 85°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4. <table border="1"> <tr> <td>Capacitance change</td> <td>≤ ±20% of the initial value</td> </tr> <tr> <td>D.F. (tan δ)</td> <td>≤ 200% of the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>≤ The initial specified value</td> </tr> </table> | Capacitance change | ≤ ±20% of the initial value | D.F. (tan δ) | ≤ 200% of the initial specified value | Leakage current | ≤ The initial specified value |
| Capacitance change              | ≤ ±20% of the initial value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                    |                             |              |                                       |                 |                               |
| D.F. (tan δ)                    | ≤ 200% of the initial specified value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    |                             |              |                                       |                 |                               |
| Leakage current                 | ≤ The initial specified value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                    |                             |              |                                       |                 |                               |

## DIMENSIONS (Screw-Mount) [mm]

● Terminal Code : LG



φ50 & φ63.5 : G=6  
φ76.2 & φ89 : G=5  
φ100 : G=10


<Screw specifications>

to φ89 Plus hexagon-headed screw : M5×0.8×10  
Maximum screw tightening torque : 3.23Nm

φ100 Cross-recessed head (phillips) screw : M8×1.25×16  
Spring washer, Washer  
Maximum screw tightening torque : 6.31Nm


\* The screw and the mounting clamp are separately supplied and not attached to the product.

● Mounting Clamp Code : B




| φD   | A     | B    | W    | F    |
|------|-------|------|------|------|
| 50   | 78.0  | 64.0 | 68.0 | 22.4 |
| 63.5 | 90.0  | 76.0 | 80.0 | 28.0 |
| 76.2 | 104.5 | 90.0 | 93.5 | 31.5 |

● Mounting Clamp Code : C



| φD   | E    | K    | F    | J    |
|------|------|------|------|------|
| 50   | 32.5 | 37.0 | 22.4 | 14.0 |
| 63.5 | 38.1 | 43.5 | 28.0 | 14.0 |
| 76.2 | 44.5 | 50.0 | 31.5 | 14.0 |
| 89   | 50.8 | 56.5 | 31.5 | 16.0 |
| 100  | 56.5 | 63.4 | 41.5 | 18.0 |

## PART NUMBERING SYSTEM



Please refer to "Product code guide (screw-mount terminal type)"

◆ **STANDARD RATINGS**

| WV<br>(V <sub>dc</sub> ) | Cap<br>(μF) | Case size<br>φD×L(mm) | tan δ | Rated ripple<br>current<br>(Arms/<br>85°C, 120Hz) | Part No.           | WV<br>(V <sub>dc</sub> ) | Cap<br>(μF) | Case size<br>φD×L(mm) | tan δ | Rated ripple<br>current<br>(Arms/<br>85°C, 120Hz) | Part No.           |
|--------------------------|-------------|-----------------------|-------|---------------------------------------------------|--------------------|--------------------------|-------------|-----------------------|-------|---------------------------------------------------|--------------------|
| 350                      | 1,200       | 50 × 60               | 0.25  | 4.90                                              | ERWF351LGC122MC60M | 400                      | 5,600       | 63.5 × 190            | 0.25  | 18.2                                              | ERWF401LGC562MDK0M |
|                          | 1,800       | 50 × 75               | 0.25  | 6.50                                              | ERWF351LGC182MC75M |                          | 5,600       | 76.2 × 130            | 0.25  | 16.9                                              | ERWF401LGC562MED0M |
|                          | 2,200       | 50 × 85               | 0.25  | 7.50                                              | ERWF351LGC222MC85M |                          | 6,800       | 76.2 × 155            | 0.25  | 20.2                                              | ERWF401LGC682MEF5M |
|                          | 2,200       | 50 × 96               | 0.25  | 7.70                                              | ERWF351LGC222MC96M |                          | 8,200       | 76.2 × 170            | 0.25  | 22.8                                              | ERWF401LGC822MEH0M |
|                          | 2,700       | 50 × 115              | 0.25  | 9.30                                              | ERWF351LGC272MCB5M |                          | 10,000      | 89 × 155              | 0.25  | 26.6                                              | ERWF401LGC103MFF5M |
|                          | 3,300       | 50 × 130              | 0.25  | 10.8                                              | ERWF351LGC332MCD0M |                          | 12,000      | 89 × 170              | 0.25  | 30.0                                              | ERWF401LGC123MFH0M |
|                          | 3,900       | 63.5 × 115            | 0.25  | 12.1                                              | ERWF351LGC392MDB5M |                          | 15,000      | 100 × 190             | 0.25  | 33.7                                              | ERWF401LGC153MGK0M |
|                          | 4,700       | 63.5 × 130            | 0.25  | 14.0                                              | ERWF351LGC472MDD0M |                          | 18,000      | 100 × 220             | 0.25  | 37.4                                              | ERWF401LGC183MGN0M |
|                          | 5,600       | 63.5 × 155            | 0.25  | 16.6                                              | ERWF351LGC562MDF5M | 450                      | 820         | 50 × 60               | 0.25  | 4.00                                              | ERWF451LGC821MC60M |
|                          | 5,600       | 76.2 × 115            | 0.25  | 16.1                                              | ERWF351LGC562MEB5M |                          | 1,000       | 50 × 75               | 0.25  | 4.80                                              | ERWF451LGC102MC75M |
|                          | 6,800       | 63.5 × 190            | 0.25  | 20.0                                              | ERWF351LGC682MDK0M |                          | 1,200       | 50 × 85               | 0.25  | 5.60                                              | ERWF451LGC122MC85M |
|                          | 6,800       | 76.2 × 130            | 0.25  | 18.6                                              | ERWF351LGC682MED0M |                          | 1,200       | 50 × 96               | 0.25  | 5.70                                              | ERWF451LGC122MC96M |
|                          | 8,200       | 76.2 × 155            | 0.25  | 22.2                                              | ERWF351LGC822MEF5M |                          | 1,500       | 50 × 96               | 0.25  | 6.30                                              | ERWF451LGC152MC96M |
|                          | 10,000      | 76.2 × 170            | 0.25  | 25.2                                              | ERWF351LGC103MEH0M |                          | 1,800       | 50 × 115              | 0.25  | 7.60                                              | ERWF451LGC182MCB5M |
|                          | 12,000      | 89 × 155              | 0.25  | 29.1                                              | ERWF351LGC123MFF5M |                          | 2,200       | 50 × 130              | 0.25  | 8.80                                              | ERWF451LGC222MCB5M |
|                          | 15,000      | 89 × 190              | 0.25  | 35.7                                              | ERWF351LGC153MFK0M |                          | 2,700       | 63.5 × 115            | 0.25  | 10.1                                              | ERWF451LGC272MDB5M |
|                          | 18,000      | 100 × 190             | 0.25  | 36.9                                              | ERWF351LGC183MGK0M |                          | 3,300       | 63.5 × 130            | 0.25  | 11.7                                              | ERWF451LGC332MDD0M |
|                          | 22,000      | 100 × 250             | 0.25  | 46.1                                              | ERWF351LGC223MGR0M |                          | 3,900       | 63.5 × 155            | 0.25  | 13.8                                              | ERWF451LGC392MDF5M |
| 400                      | 1,000       | 50 × 60               | 0.25  | 4.40                                              | ERWF401LGC102MC60M |                          | 3,900       | 76.2 × 115            | 0.25  | 13.4                                              | ERWF451LGC392MEB5M |
|                          | 1,500       | 50 × 75               | 0.25  | 5.90                                              | ERWF401LGC152MC75M |                          | 4,700       | 63.5 × 190            | 0.25  | 16.7                                              | ERWF451LGC472MDK0M |
|                          | 1,800       | 50 × 85               | 0.25  | 6.80                                              | ERWF401LGC182MC85M |                          | 4,700       | 76.2 × 130            | 0.25  | 15.5                                              | ERWF451LGC472MED0M |
|                          | 1,800       | 50 × 96               | 0.25  | 7.00                                              | ERWF401LGC182MC96M |                          | 5,600       | 76.2 × 155            | 0.25  | 18.3                                              | ERWF451LGC562MEF5M |
|                          | 2,200       | 50 × 105              | 0.25  | 8.00                                              | ERWF401LGC222MCA5M |                          | 6,800       | 76.2 × 170            | 0.25  | 20.7                                              | ERWF451LGC682MEH0M |
|                          | 2,700       | 50 × 130              | 0.25  | 9.80                                              | ERWF401LGC272MCD0M |                          | 8,200       | 89 × 155              | 0.25  | 24.1                                              | ERWF451LGC822MFF5M |
|                          | 3,300       | 63.5 × 115            | 0.25  | 11.1                                              | ERWF401LGC332MDB5M |                          | 10,000      | 89 × 170              | 0.25  | 27.8                                              | ERWF451LGC103MFH0M |
|                          | 3,900       | 63.5 × 130            | 0.25  | 12.7                                              | ERWF401LGC392MDD0M |                          | 12,000      | 100 × 190             | 0.25  | 29.3                                              | ERWF451LGC123MGK0M |
|                          | 4,700       | 63.5 × 155            | 0.25  | 15.2                                              | ERWF401LGC472MDF5M |                          | 15,000      | 100 × 250             | 0.25  | 37.0                                              | ERWF451LGC153MGR0M |
|                          | 4,700       | 76.2 × 115            | 0.25  | 14.7                                              | ERWF401LGC472MEB5M |                          |             |                       |       |                                                   |                    |

◆ **RATED RIPPLE CURRENT MULTIPLIERS**

● Frequency Multipliers

| Frequency (Hz) | 50  | 120 | 300 | 1k  | 3k  |
|----------------|-----|-----|-----|-----|-----|
| Coefficient    | 0.8 | 1.0 | 1.1 | 1.3 | 1.4 |

Note : The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5 to 10°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced. Also, for the RWF series capacitors, using them at operating voltage less than their rated voltage can extend their lifetime. For details, please contact a representative of Nippon Chemi-Con.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9