

**BYT56AGP THRU BYT56MGP**


**SINTERED GLASS JUNCTION  
FAST SWITCHING PLASTIC RECTIFIER  
VOLTAGE:50 TO 1000V CURRENT: 3.0A**

**FEATURE**

High temperature metallurgically bonded construction  
Sintered glass cavity free junction  
Capability of meeting environmental standard of  
MIL-S-19500  
High temperature soldering guaranteed  
350°C /10sec/0.375"lead length at 5 lbs tension  
Operate at Ta =55°C with no thermal run away  
Typical Ir<0.1μA

**MECHANICAL DATA**

Terminal: Plated axial leads solderable per  
MIL-STD 202E, method 208C  
Case: Molded with UL-94 Class V-0 recognized Flame  
Retardant Epoxy  
Polarity: color band denotes cathode  
Mounting position: any

**DO-201AD**

Dimensions in inches and (millimeters)

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)






	SYMBOL	BYT56 AGP	BYT56 BGP	BYT56 DGP	BYT56 GGP	BYT56 JGP	BYT56 KGP	BYT56 MGP	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	Vrms	35	70	140	280	420	560	700	V
Maximum DC blocking Voltage	Vdc	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	If(av)					3.0			A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm					125			A
Maximum Forward Voltage at rated Forward Current and 25°C	Vf				1.4				V
non-repetitive reverse avalanche energy (I <sub>(BR)R</sub> =0.4A)	E <sub>R</sub>				10				mJ
Maximum full load reverse current full cycle average at 55°C Ambient	Ir(av)				100				μA
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	Ir				5.0				μA
Maximum Reverse Recovery Time (Note 1)	Trr				100				μA
Typical Junction Capacitance (Note 2)	C <sub>j</sub>				60				pF
Typical Thermal Resistance (Note 3)	R(ja)				20				°C/W
Storage and Operating Junction Temperature	T <sub>stg</sub> , T <sub>j</sub>				-65 to +175				°C

Note: 1.Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A

2.Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc

3.Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

## RATINGS AND CHARACTERISTIC CURVES BYT56AGP THRU BYT56MGP



**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Распределительные склады, находящиеся в России, Европе и в Китае, позволяют нам оперативно поставить необходимые компоненты в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям ISO 9001:2011

#### **Офис по работе с юридическими лицами:**

107023, г.Москва, Семеновский переулок, д.6, Бизнес-центр «ABC»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru\_3

moschip.ru\_6

moschip.ru\_4

moschip.ru\_7

moschip.ru\_11

moschip.ru\_8

moschip.ru\_12

moschip.ru\_9