


Surface Mount Transformers/Inductors, Gapped and Ungapped, Custom Configurations Available



ELECTRICAL SPECIFICATIONS

(Multiple winds are connected in parallel)

Inductance Range: 10 μ H to 150 000 μ H, measured at 0.10 V RMS at 10 kHz without DC current, using an HP 4263 or HP 4284A impedance analyzer


DC Resistance Range: 0.02 Ω to 46.2 Ω , measured at + 25 °C \pm 5 °C

Rated Current Range: 3.20 amps to 0.17 amps

Dielectric Withstanding Voltage: 500 V RMS, 60 Hz, 5 seconds



RoHS COMPLIANT





NOTE: Pad layout guidelines per MIL-STD- 275E (printed wiring for electronic equipment). Tolerances: xx \pm 0.01" [\pm 0.25 mm], xxx \pm 0.005" [\pm 0.12 mm].

STANDARD ELECTRICAL SPECIFICATIONS						
MODEL	IND. (μ H)	IND. TOL.	SCHEMATIC LETTER	DCR MAX. (Ohms)	MAX. RATED* DC CURRENT (Amps)	SATURATING CURRENT** (Amps)
Ungapped Models						
LPE-6855-151NA	150	\pm 30 %	A	0.28	0.84	N/A
LPE-6855-221NA	220	\pm 30 %	A	0.34	0.76	N/A
LPE-6855-331NA	330	\pm 30 %	A	0.41	0.69	N/A
LPE-6855-471NA	470	\pm 30 %	A	0.49	0.63	N/A
LPE-6855-681NA	680	\pm 30 %	A	0.59	0.57	N/A
LPE-6855-102NA	1000	\pm 30 %	A	0.72	0.52	N/A
LPE-6855-152NA	1500	\pm 30 %	A	0.88	0.47	N/A
LPE-6855-222NA	2200	\pm 30 %	A	1.07	0.43	N/A
LPE-6855-332NA	3300	\pm 30 %	A	1.31	0.39	N/A
LPE-6855-472NA	4700	\pm 30 %	A	1.56	0.35	N/A
LPE-6855-682NA	6800	\pm 30 %	A	1.88	0.32	N/A
LPE-6855-103NA	10 000	\pm 30 %	A	7.17	0.16	N/A
LPE-6855-153NA	15 000	\pm 30 %	A	8.78	0.15	N/A
LPE-6855-223NA	22 000	\pm 30 %	A	10.6	0.14	N/A
LPE-6855-333NA	33 000	\pm 30 %	A	13.0	0.12	N/A
LPE-6855-473NA	47 000	\pm 30 %	A	15.5	0.11	N/A
LPE-6855-683NA	68 000	\pm 30 %	A	18.7	0.10	N/A
LPE-6855-104NA	100 000	\pm 30 %	A	37.7	0.07	N/A
LPE-6855-154NA	150 000	\pm 30 %	A	46.2	0.06	N/A
Gapped Models						
LPE-6855-100MB	10	\pm 20 %	B	0.02	3.21	3.375
LPE-6855-150MB	15	\pm 20 %	BB	0.03	2.90	2.790
LPE-6855-220MB	22	\pm 20 %	BB	0.04	2.64	2.325
LPE-6855-330MB	33	\pm 20 %	BB	0.05	2.12	1.910
LPE-6855-470MB	47	\pm 20 %	BB	0.08	1.73	1.610
LPE-6855-680MB	68	\pm 20 %	B	0.12	1.41	1.350
LPE-6855-101MB	100	\pm 20 %	B	0.15	1.28	1.120
LPE-6855-151MB	150	\pm 20 %	C	0.23	1.02	0.915
LPE-6855-221MB	220	\pm 20 %	D	0.35	0.83	0.757
LPE-6855-331MB	330	\pm 20 %	D	0.55	0.67	0.620
LPE-6855-471MB	470	\pm 20 %	D	0.82	0.54	0.520
LPE-6855-681MB	680	\pm 20 %	E	1.23	0.45	0.433
LPE-6855-102MB	1000	\pm 20 %	E	1.89	0.36	0.358
LPE-6855-152MB	1500	\pm 20 %	E	2.90	0.29	0.292
LPE-6855-222MB	2200	\pm 20 %	E	4.50	0.23	0.242
LPE-6855-332MB	3300	\pm 20 %	E	5.50	0.21	0.197
LPE-6855-472MB	4700	\pm 20 %	E	8.30	0.17	0.166

* DC current that will create a maximum temperature rise of 30 °C when applied at + 25 °C ambient. ** DC current that will typically reduce the initial inductance by 20 %. **UNGAPPED MODELS:** Highest possible inductance with the lowest DCR and highest Q capability. Beneficial in filter, impedance matching and line coupling devices. **GAPPED MODELS:** Capable of handling large amounts of DC current, tighter inductance tolerance with better temperature stability than ungapped models. Beneficial in DC to DC converters or other circuits carrying DC currents or requiring inductance stability over a temperature range.

DESCRIPTION						
LPE	6855	1000 μ H	\pm 30 %	A	ER	e2
MODEL	SIZE	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	CORE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD





NOTE: Schematic A is for Ungapped LPE Series

ENVIRONMENTAL PERFORMANCE	
TEST	CONDITIONS
Thermal Cycling	Withstands - 55 °C to + 125 °C
Operating Temperature	- 55 °C to + 125 °C
High Humidity	85 %
Soldering Heat	Tested to + 230 °C
Mechanical Shock	Per MIL-STD-202, Method 213 (100G)
Vibration	Per MIL-STD-202, Method 204 (20G)
Solderability	Per industry standards

* Must be checked in end use application

PART MARKING
<ul style="list-style-type: none"> - Vishay Dale - Date code - Marking code (Suffix of model #) - Pin 1 indicator

PACKAGING									
<p>TAPE SPECIFICATIONS: Carrier Tape Type: Conductive Cover Tape Type: Anti-static Cover Tape Adhesion to Carrier: 40 ± 30 grams</p> <p>REEL SPECIFICATIONS: Diameter (flange): 13" [330.2 mm] Maximum Width (over flanges): 1.197" [30.4 mm]</p>	<p>STANDARDS: All embossed carrier tape packaging will be accomplished in compliance with latest revision of EIA-481 "Taping of Surface Mount Components for Automatic Placement".</p> <table border="1"> <thead> <tr> <th>MODEL</th> <th>TAPE WIDTH</th> <th>COMPONENT PITCH</th> <th>UNITS PER 13 INCH REEL</th> </tr> </thead> <tbody> <tr> <td>LPE-6855</td> <td>32 mm</td> <td>20 mm</td> <td>450</td> </tr> </tbody> </table>	MODEL	TAPE WIDTH	COMPONENT PITCH	UNITS PER 13 INCH REEL	LPE-6855	32 mm	20 mm	450
MODEL	TAPE WIDTH	COMPONENT PITCH	UNITS PER 13 INCH REEL						
LPE-6855	32 mm	20 mm	450						
<p>Tape and Reel Orientation</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Pin 1 Indicator</p> <p>USER DIRECTION OF FEED</p> </div> <div style="text-align: center;"> <p>Label Area</p> <p>Cover Tape</p> <p>Carrier Tape</p> <p>Embossed Cavity</p> </div> </div>									



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9