



Ideal for Class 2 applications including petrochemical, factory-automation and commercial-vehicle equipment, Brad® Micro-Change® M12 Harsh-Duty Receptacles offer a sealed connection with superior EMI/RFI shielding in high-vibration systems

Brad® Micro-Change® M12 Harsh-Duty Receptacles are designed to withstand harsh commercial and industrial environments. Their superior design ensures a reliable connection for control elements in commercial vehicle equipment, factory automation equipment and petrochemical markets. Receptacles are tooled for network connectivity in both Ethernet and Controller-Area Network (CAN bus) protocols, as well as passive applications such as discreet and analog sensor applications.


Receptacles are available in 4-pole D-code and 5-pole A-code configurations; additional pole count and code variations can be developed upon request. Heavy-duty diecast construction provides 360° EMI/RFI shielding in the rugged receptacle while keeping costs to a minimum.

Brad Micro-Change M12 Harsh-Duty Receptacles are designed to interface with numerous Molex cordsets, including Series 130048, 120108, 130027 and 130028.

For more information on Molex's broad portfolio of industrial and power products for harsh-duty applications, visit: www.molex.com/product/bradproducts.html

Brad® Micro-Change® M12 Harsh-Duty Receptacles

130299 Harsh-Duty
Receptacles



- A. 4-pole right-angle receptacle with coupling nut (Series 130299)
- B. 4-pole right-angle receptacle with O-ring (Series 130299)
- C. 4-pole right-angle receptacle, back view (Series 130299)
- D. Coupling nut (130299)

Features and Benefits

Robust housing with heavy-duty die-cast construction and IEC 61076-2-101 compliant design	Provides superior Electro Magnetic Interference (EMI) and Radio Frequency Interference (RFI) protection. Meets CE industry requirements
Waterproof sealed and IP67, IP69K compliant	Able to withstand high-pressure wash down
Rated to 250V AC/DC, up to 4.0A	Ideal for Class 2 power and network circuit applications
Receptacle designed with a vibration-resistant mounting nut	Withstands vibration for chassis applications
Tooled for Ethernet and Controller-Area Network (CAN bus) protocols and passive applications including discreet and analog sensors	Meet high-speed data bus requirements
Receptacle pull-strength of 1.5N initial-mate torque resistance and 34kg intermittent side-load withstand rating	Durable for harsh environments, exceeding twice the strength of standard M12 receptacles. Reduces chance of pin bending during mating
Receptacles available in right-angle and straight configurations and 5-Pole A-, 4-pole D-code keyway options	Provides a full range of options for design flexibility. Keyed for poka-yoke manufacturing processes (end-of-line rework)



Specifications

Reference Information

Packaging: 10 pack sleeve

RoHS: Yes

D-Code receptacle:

UL File No. E200650 Pending

A-Code receptacle:

UL File No. E152210 Pending

CSA File No. LR6837 Pending

Electrical

Voltage (max.): 250V AC

Current (max.): 4.0A

Contact Resistance: <10 milliohms

Dielectric Withstanding Voltage:

1500V AC

Insulation Resistance:


20 Megohms min.

Mechanical


Durability: 500 cycles



Left-to-right: Brad® Micro-Change® 4-pole straight receptacle, Micro-Change® 4-pole cordset



Robust shell isolates PCB poles; Right-Angle Receptacle for Ethernet Applications



Offset keying option example



4-pole straight receptacle with O-Ring

Applications

Commercial Vehicle Transportation

- Controllers and telematics
- Sensors, navigation devices
- Construction, agriculture, forestry machinery

Industrial Machinery

- Packaging, robot, welding, material handling device manufacturers

Harsh Commercial Products

- Outdoor displays, signs
- Carwashes

Marine

- Boats
- Large vessels

Military/Aerospace

- Tactical vehicles
- C4ISR systems
- Military shelters



Truck



GPS



Harvesting Machinery

Ordering Information

Order No.	Poles	Code	Orientation
130299-0100	4	D	Right Angle
130299-0200			Straight
130299-0300	5	A	Right Angle
130299-0400			Straight

www.molex.com/link/m12.html

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9