





SECTION F-F



FCIconnect.com


Copyright FCI

[illegible]



ADD-IN CARD EDGE-FINGER DIMENSIONS


mat'l. code				surface 58	tolerance	projection	product family			
-				ISO 1302	ISO 406	ISO 1101	PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances unless otherwise specified			title			
H	-	-	-	angles	linear	MM	PCI_EXPRESS_CARD_EDGE ASSEMBLY(SMT)			
				0°±2°		scale 2				
				dr	MAGGIE_WU	06'/6/21	dwg no		sheet 2 of 6	size
				enr	RICHARD_CHIU	06'/6/21	10061913			A4
				chr	PAUL_WANG	06'/6/21				
				app	JOSEPH_HSIA	06'/6/21	type		CUSTOMER Drawing	
sheet index	revision									
	sheet									




RECOMMENDED PCB LAYOUT, PAD TYPE

DIMENSIONS								
POSITION	A	B ± 0.15 -0.05	C ± 0.20	D ± 0.23	E ± 0.20	H ± 0.10	J	K ± 0.10
36	6.00	7.65	9.15	25.00	27.00	28.00	6.00	9.15
64	20.00	21.65	23.15	39.00	41.00	42.00	20.00	23.15
98	37.00	38.65	40.15	56.00	58.00	59.00	37.00	40.15
164	70.00	71.65	73.15	89.00	91.00	92.00	70.00	73.15

POSTION OF CAP



POSTION OF MYLAR



mat'l. code				surface 58	tolerance	projection	product family			
-				ISO 1302	ISO 406	ISO 1101	PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances unless otherwise specified			title			
H	-	-	-	angles	linear	MM	PCI_EXPRESS_CARD_EDGE ASSEMBLY(SMT)			
				0°±2°		scale 2				
				dr	MAGGIE_WU	06'/6/21	dwg no		sheet 3 of 6	size
				engr	RICHARD_CHIU	06'/6/21	10061913			A4
				chr	PAUL_WANG	06'/6/21				
				app	JOSEPH_HSIA	06'/6/21	type		CUSTOMER Drawing	
sheet index	revision									
	sheet									

NOTES:

1.MATERIAL:

HOUSING: NYLON, GLASS FILLED UL94V-0 RATE, SUITABLE FOR I.R SOLDERING.

TERMINAL: COPPER ALLOY

PLATING: 50u" NICKEL UNDERPLATE ALL OVER
CONTACT AREA PLATING - SEE PRODUCT NUMBER CODE
SOLDER TAIL: TIN 100u" OVER 50u" NICKEL

METAL PADS: COPPER ALLOY
FINISH: 100u" TIN OVER 50u" NICKEL

2.PRODUCT SPECIFICATION: GS-12-390

③THE HORIZONTAL AXIS FOR THE PAD PATTERN IS ESTABLISHED BY

A LINE THROUGH THE CENTER OF THE TWO Ø1.0 HOLES.

THE VERTICAL AXIS IS 90° TO THE HORIZONTAL AXIS, THROUGH THE CENTER OF DATUM $\square Z$

④NO TIE BAR PERMITTED FROM CARD EDGE TO LEADING EDGE OF PAD FOR PINS A1.

⑤CHAMFER EDGES MUST BE FREE OF CUTTING BURRS.

7.RoHS COMPATIBLE PRODUCT SPECIFICATIONS

a - PLATING:

- "LF" MEANS THE PRODUCT IS LEAD-FREE, 2um MINIMUM MATTE TIN OVER 1.27um MINIMUM NICKEL UNDERPLATE.

b - MANUFACTURING PROCESS COMPATIBILITY

- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C±5°C PEAK TEMPERATURE FOR 5 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.

PRODUCT NUMBER CODE

10061913-X X X X L F

HOUSING COLOR OPTIONS

0-WHITE
1-BLACK

LEAD FREE

PACKAGING OPTIONS

T-TRAY PACKAGING WITHOUT CAP
R-TAPE & REEL PACKING WITHOUT CAP OR MYLAR (FOR 36P & 64P OPTION ONLY)
P-TAPE & REEL PACKING WITH CAP (FOR 36P & 64P OPTION ONLY)
C-TRAY PACKAGING WITH CAP
M-TAPE & REEL PACKING WITH MYLAR (FOR 36P & 64P OPTION ONLY)
N-TRAY PACKAGING WITH MAYLAR
Y-HARD TRAY (FOR 164P ONLY)
Z-HARD TRAY PACKAGING WITH MAYLAR (FOR 164P ONLY)





TERMINAL PLATING OPTIONS

0-50u" Ni UNDERPLATE
30u" Au CONTACT AREA
100u" TIN TAIL AREA ----- COMPATIBLE RoHS
1-50u" Ni UNDERPLATE
15u" Au CONTACT AREA
100u" TIN TAIL AREA ----- COMPATIBLE RoHS
2-50u" Ni UNDERPLATE
GOLD FLASH CONTACT AREA
100u" TIN TAIL AREA ----- COMPATIBLE RoHS

POS OPTIONS

0-36
1-64
2-98
3-164

mat'l. code				surface 58/ISO 1302		tolerance ISO 406 ISO		projection		product family			
-				ISO 1302		ISO 406 ISO		1101		PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances unless otherwise specified		specified		MM		title			
H	-	-	-	angles linear		.X±.2		MM		PCI_EXPRESS_CARD_EDGE ASSEMBLY(SMT)			
				0°±2°		.XX±.13		scale 2					
				dr		MAGGIE_WU		06'/6/21		dwg no		sheet 4 of 6	size
				engr		RICHARD_CHIU		06'/6/21		10061913		A4	
				chr		PAUL_WANG		06'/6/21					
				app		JOSEPH_HSIA		06'/6/21		type		CUSTOMER Drawing	
sheet index		revision sheet											



TAPE AND REEL
PACKAGING PRESENTED
WITH 36PINS

DIMENSIONS					
POSITIONS	A	B	C	D REF.	E REF.
36	44.00	40.40	20.20	44.5	50.5
64	56.00	52.60	26.30	56.4	60.4

mat'l. code				surface 58/ISO 1302		tolerance ISO 406 ISO 1101		projection		product family			
-				ISO 1302		ISO 406		1101		PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances unless otherwise specified						title			
H	-	-	-							PCI_EXPRESS_CARD_EDGE ASSEMBLY(SMT)			
				angles	linear	.X±.3		MM		dwg no 10061913 sheet 5 of 6 size A4			
						.XX±.20							
				0°±2°		XXX±.10		scale 1					
				dr	MAGGIE_WU	06'/6/21							
				enr	RICHARD_CHIU	06'/6/21					type CUSTOMER Drawing		
				chr	PAUL_WANG	06'/6/21							
				app	JOSEPH_HSIA	06'/6/21							
sheet index	revision sheet												

1 TAPE & REEL PACKING FOR PCI EXPRESS SMT TYPE 36P.

2. Material :

2.1 Reel :

2.1.1 Plastic hub : High Impact Polystyrene

2.1.2 Cover tape : PE

2.1.3 Carrier tape : ABS

2.2 Waterproof bag : PE

2.3 Desiccative : Silica Gel

2.4 Carton : Corrugated paper

2.5 Baffle : E.P.E

2.6 Angle paperboard : Corrugated paper

3. Dimension :

3.1 Reel :

3.1.1 Plastic hub : $\phi 330 \times T50.5$ mm

3.1.2 Cover tape : 5690(L) x 37.4(W) mm

3.1.3 Carrier tape : 5640(L) x 44(W)mm

3.2 Waterproof bag : 600(H) x 465(W) x 0.06(T) mm

3.3 Desiccative : 25 gram / Package

3.4 Carton : 380(L) x 380(W) x 300(H) mm

3.5 Baffle (1): 370(L) x 370(W) x 15(H) mm


3.6 Baffle (2): 355(L) x 252(W) x 15(H) mm

3.7 Angle paperboard : 252(H)

4. Quantity :

4.1 250 Pcs / Reel

4.2 1,250 Pcs / Carton



mat'l. code				surface 58	tolerance	projection	product family			
-				ISO 1302	ISO 406 ISO	1101	PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances	unless otherwise	specified	title			
H	-	-	-	angles	linear	MM	PCI_EXPRESS_CARD_EDGE ASSEMBLY(SMT)			
				0°±2°	.X±.3	scale 1	dwg no			
					.XX±.20		sheet 6 of 6			
				dr	MAGGIE_WU	06'/6/21	10061913			
				engr	RICHARD_CHIU	06'/6/21	A4			
				chr	PAUL_WANG	06'/6/21	type			
				app	JOSEPH_HSIA	06'/6/21	CUSTOMER Drawing			
sheet index	revision									
	sheet									

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9