MPM20 Kool-Tab[®] Power Film Resistors


"Pure Tin Free" design for High Performance Industrial and Military Applications TO-220 Style Power Package with Metal Mounting Tab

MPM20 Kool-Tab[®] Power Film Resistors introduce a "Pure Tin Free" design for High Performance Applications. Our proven Micronox[®] resistance film system is utilized in the widely accepted TO-220 Power Package to provide a compact 20 watt heat sink mountable resistor. The non-inductive design makes this resistor ideal in high frequency communications, power switching circuits and snubbers. The special performance features of the series MPM20 Kool-Tab[®] Power Film Resistors include:

- Up to 20 Watt power rating at +25°C case temperature.
- · Resistance values as low as 0.020 ohm for current sense applications.
- · Non-Inductive Design.
- · Single screw mounting simplifies resistor attachment to the heat sink.
- · Low profile provides an easier fit in tight places.
- · A molded case for environmental protection.
- · Resistor element is electrically isolated from the metal heat sink tab.

Use your thermal design experience with power semiconductors in TO-220 style power packages. This experience will help you get the most out of this unique family of power resistors. The thermal design issues are the same where power handling capability is based on the case temperature which is maintained in your design.

| | Model No. | Resistance | | Power | Max. | Thermal Resistance R _{θ,IC} | Dielect. Strength | Leadwire |
|---|--------------|------------|--------|------------|---------|--------------------------------------|---------------------|------------|
| ı | | Min. | Max. | Rating | Voltage | Film (J) to Case (c) | V _{RMS} AC | Loudiviio |
| ı | MPM20 | 0.020 Ω | 10.0 K | 20 Watts * | 300 | 7.50°C/Watt | 1,500 | Solderable |



* Derating Using Case Temperature (T_C):

All power and associated overload ratings are derated based upon case temperature using the derating curve. The case temperature is measured at the center of the metal mounting surface, with the part properly mounted and under electrical load. Without a heat sink, when in free air at +25°C, the MPM20 is rated for 2.25 watts.


The thermal design should satisfy the following equation:


Case Temperature (T_C) + [Thermal Resistance (R_{θ JC)} x power applied (Watts)] \leq T_{MAX} considering the full operating temperature range of the application.

Mounting Note: Mount on a smooth, clean and flat heat sink surface with a thermal interface material, such as thermal grease. The entire exposed metal backface portion must be in thermal contact with the heat sink. When screw mounting, use a compression washer which provides a mounting force of 150 to 300 pounds (665 to 1330 N). This will provide sufficient pressure on the package over time and through large temperature variations to maintain the maximum power dissipation capability. Mounting torque to avoid package damage is 8 in-lins (0.90 N-m)

For additional applications information regarding mounting and pulse handling see the Caddock Applications Notes at caddock.com or contact Applications Engineering.

Non-Inductive Design: MPM20 Kool-Tab[®] Power Film Resistors are constructed with our Micronox[®] resistance film fired onto a flat substrate which is thermally bonded to the copper heat sink tab. The resistor body is then molded to finish the TO-220 style package. The lead wire attachment and resistance element geometry are configured to provide outstanding non-inductive performance.





Specifications:

Temperature Coefficient:

TC referenced to $+25^{\circ}$ C, Δ R taken at $+175^{\circ}$ C 5.00 ohms and above, -20 to +50 ppm/°C 1.00 ohm to 4.99 ohms, -20 to +80 ppm/°C 0.050 ohm to 0.99 ohm, 0 to +200 ppm/°C 0.020 ohm to 0.049 ohm, 0 to +300 ppm/°C

Resistance Tolerance: ±1% (±0.5% is available for most resistance values).

Insulation Resistance: 10,000 Megohms, min. Resitor element is electrically isolated from the mounting surface.

Terminal Strength: Mil-Std-202, Method 211, Cond. A (Pull Test) 5 lbs., $\Delta R \pm (0.2 \text{ percent} + 0.001 \text{ ohm}) \text{ max.}$

Thermal Shock: Mil-Std-202, Method 107, Cond.F, $\Delta R \pm (0.3 \text{ percent} + 0.001 \text{ ohm}) \text{ max}.$

Momentary Overload: 2 times rated power with applied voltage not to exceed 1.5 times maximum continuous operating voltage for 5 seconds, $\Delta R \pm (0.3 \text{ percent} + 0.001 \text{ ohm}) \text{ max.}$

Moisture Resistance: Mil-Std-202, Method 106,

 Δ R ±(0.5 percent + 0.001 ohm) max. **Load Life:** 2,000 hours at rated power, Δ R ±(1.0 percent + 0.001 ohm) max. Power rating dependence

dent upon case temperature. See derating curve. **Shock:** 100G, Mil-Std-202, Method 213, Cond. I, $\Delta R \pm (0.2 \text{ percent} + 0.001 \text{ ohm}) \text{ max}.$

Vibration, High Frequency: Mil-Std-202, Method 204, Cond. D, ΔR ±(0.2 percent + 0.001 ohm) max.

Measurement Note: For these specifications, resistance measurement shall be made at a point 0.2 inch (5 mm) from the resistor body.

Ordering Information:



Applications Engineering 17271 North Umpqua Hwy. Roseburg, Oregon 97470-9422 Phone: (541) 496-0700 Fax: (541) 496-0408

CADDOCK ELECTRONICS, INC.

e-mail: caddock@caddock.com • web: www.caddock.com For Caddock Distributors listed by country see caddock.com/contact/dist.html Sales and Corporate Office 1717 Chicago Avenue Riverside, California 92507-2364 Phone: (951) 788-1700 Fax: (951) 369-1151

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9