

Features

- Surge withstand IEC 61000-4-5 1.2/50 µs
- Low thermal resistant ceramic core
- E24 resistance values
- RoHS compliant*
- Wide power range (1~8 W)
- Coating material meets UL 94V-0 requirements

Applications

- Smart meters
- Renewable energy
- Industrial
- Power supplies/chargers
- Lighting
- Instruments/gauges
- White goods

WS Series High Surge Withstand Wirewound Resistor

Electrical Characteristics

Resistance Range ..... See Popular Resistance Values Table
Power Rating @ 70 °C
- WS1M, WS1A ..... 1 W
- WS2M, WS2A ..... 2 W
- WS3M, WS3A ..... 3 W
- WS5M, WS5A ..... 5 W
- WS7M, WS7A ..... 7 W
- WS8M ..... 8 W

Tolerance ..... 5 %
Operating Temperature ..... -55 °C to +200 °C
Temperature Coefficient ..... ±200 ppm/°C
Maximum Voltage ..... $\sqrt{P*R}$

Popular Resistance Values

Code	R Value
15R0	15 Ω
20R0	20 Ω
22R0	22 Ω
33R0	33 Ω
47R0	47 Ω

Code	R Value
68R0	68 Ω
1500	150 Ω
1001	1K Ω
3301	3.3K Ω

Other E24 resistance values available upon request.

Physical Characteristics

Resistor ..... Low thermal resistant ceramic core
Lead Wire ..... Tin-plated copper wire
Coating Material ..... Meets UL 94V-0 requirements

How to Order

WS 3 M 22R0 J

Product Series
- WS = Wirewound, High Surge Withstand

Power Rating
- 1 = 1 Watt
- 2 = 2 Watts
- 3 = 3 Watts
- 5 = 5 Watts
- 7 = 7 Watts
- 8 = 8 Watts

Pin Style
- A = Axial Standard Version
- M = Axial Miniaturized Version

Resistance Code
- R<100 ohms: "R" represents decimal point (example: 22R0 = 22 ohms)
- R≥100 ohms: First three digits are significant, fourth digit represents number of zeros to follow (example: 1001 = 1K ohms)

Resistance Tolerance
- J = ±5 %

Environmental Characteristics

Test	Conditions	Specification
Short Time Overload	10 times rated power for 5 seconds.	ΔR≤±(5 % ± 0.05 Ω)
Solderability	245 ±3 °C for 2.5 ±0.5 seconds.	Over 95 % coverage
Resistance to Solder Heat	260 ±5 °C for 10 ± 1 seconds.	ΔR≤±(1 % + 0.05 Ω)
Temperature Cycle	5 cycles, -55 °C ±3 °C for 30 minutes, Room temperature for 15 minutes, +155 ±2°C for 30 minutes, Room temperature for 15 minutes	ΔR≤±(2 % + 0.05 Ω)
Dielectric Strength	Test voltage >500 Vrms for >1 minute.	Pass
Insulation Resistance	Test voltage >500 Vrms for 1 minute.	>10^9 Ω
Load Life Humidity	Rated continuous voltage for 1000 hours, 1.5 hours ON and 0.5 hours OFF at 90~95 % relative humidity and test temperature of 40 °C ±2 °C.	ΔR≤ ±(5 % + 0.05 Ω)
Load Life	Rated continuous voltage for 1000 hours, 1.5 hours ON and 0.5 hours OFF at a test temperature of 70 °C ±2 °C. 1000 hours at rated power.	ΔR≤±(5 % + 0.05 Ω)
Surge	IEC 61000-4-5 1.2/50 µs exponential.	ΔR≤ ±(5 % + 0.05 Ω)

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

WS Series High Surge Withstand Wirewound Resistor

BOURNS®

Product Dimensions



DIMENSIONS: MM / (INCHES)

Model	Dimensions			
	L*	D	W	T
WS1M	9.5 ± 1.0 (.374 ± .004)	4.5 ± 1.0 (.177 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.65 ± 0.05 (.026 ± .002)
WS1A	11.5 ± 1.0 (.453 ± .004)	5.0 ± 1.0 (.197 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.65 ± 0.05 (.026 ± .002)
WS2M	11.5 ± 1.0 (.453 ± .004)	5.0 ± 1.0 (.197 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.65 ± 0.05 (.026 ± .002)
WS2A	15.5 ± 1.0 (.610 ± .004)	5.5 ± 1.0 (.217 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS3M	15.5 ± 1.0 (.610 ± .004)	5.5 ± 1.0 (.217 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS3A	17.5 ± 1.0 (.689 ± .004)	6.5 ± 1.0 (.256 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS5M	17.5 ± 1.0 (.689 ± .004)	6.5 ± 1.0 (.256 ± .004)	28.0 ± 3.0 (1.102 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS5A	24.5 ± 1.0 (.965 ± .004)	8.5 ± 1.0 (.335 ± .004)	38.0 ± 3.0 (1.496 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS7M	24.5 ± 1.0 (.965 ± .004)	8.5 ± 1.0 (.335 ± .004)	38.0 ± 3.0 (1.496 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS7A	29.5 ± 1.0 (1.161 ± .004)	8.5 ± 1.0 (.335 ± .004)	38.0 ± 3.0 (1.496 ± .118)	0.75 ± 0.05 (.030 ± .002)
WS8M	29.5 ± 1.0 (1.161 ± .004)	8.5 ± 1.0 (.335 ± .004)	38.0 ± 3.0 (1.496 ± .118)	0.75 ± 0.05 (.030 ± .002)

Typical Part Marking

Resistors shall be marked with color coding. Colors shall be in accordance with JIS C 0802.



Color	1st Band	2nd Band	Multi-plier	Tol.
Black	0	0	1 Ω	
Brown	1	1	10 Ω	±1 %
Red	2	2	100 Ω	±2 %
Orange	3	3	1K Ω	
Yellow	4	4	10K Ω	
Green	5	5	100K Ω	±0.5 %
Blue	6	6	1M Ω	±0.25 %
Violet	7	7	10M Ω	±0.10 %
Grey	8	8		±0.05 %
White	9	9		
Gold			0.1 Ω	±5 %
Silver			0.01 Ω	±10 %

Power Derating Curve



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Packaging Specifications





Model	O	P	A	B	C	Pkg. Style	Min. Order Qty. (Pcs.)	Pcs./ Box
WS1M	58 ± 1 (2.283 ± .039)	5 ± 0.3 (.197 ± .112)	75 ± 5 (2.953 ± .197)	70 ± 5 (2.756 ± .197)	255 ± 5 (10.039 ± .197)	Ammo Pack	5,000	1,000 pcs.
WS1A, WS2M	58 ± 1 (2.283 ± .039)	5 ± 0.3 (.197 ± .112)	80 ± 5 (3.150 ± .197)	82 ± 5 (3.228 ± .197)	255 ± 5 (10.039 ± .197)			
WS2A, WS3M	65 ± 5 (2.559 ± .197)	10 ± 0.3 (.393 ± .112)	90 ± 5 (3.543 ± .197)	119 ± 5 (4.685 ± .197)	255 ± 5 (10.039 ± .197)			
WS3A, WS5M	65 ± 5 (2.559 ± .197)	10 ± 0.3 (.393 ± .112)	90 ± 5 (3.543 ± .197)	88 ± 5 (3.465 ± .197)	255 ± 5 (10.039 ± .197)		2,000	500 pcs.
WS5A, WS7M	90 ± 5 (3.543 ± .197)	10 ± 0.3 (.393 ± .112)	115 ± 5 (4.528 ± .197)	124 ± 5 (4.882 ± .197)	500 ± 5 (19.685 ± .197)			

For WS7A and WS8M packaging specifications, please contact factory.

Surge Performance - 1.2/50 μs Pulse Withstanding Curve



BOURNS®

Asia-Pacific:
Tel: +886-2 2562-4117
Fax: +886-2 2562-4116

EMEA:
Tel: +36 88 520 390
Fax: +36 88 520 211

The Americas:
Tel: +1-951 781-5500
Fax: +1-951 781-5700

www.bourns.com

03/15

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9