


SPECIFICATION CONTROL DRAWING					SCD		82A1811					
TitleONE CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, FLEXIBLE, 600 VOLT					Date2-3-16		RevisionA					
This specification sheet forms a part of the latest issue of Raychem Specification 80.												
COMPONENT WIRE - 82A0811									SHIELD - TIN-COATED COPPER		JACKET - RADIATION-CROSSLINKED, MODIFIED FLEXIBLE ETFE	
												
CABLE CONSTRUCTION DETAILS												
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (inch)		OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)					
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM						
82A1811-24-*	24	38	.005	.007	.075	.080	6.6					
82A1811-22-*	22	38	.005	.007	.085	.090	8.5					
82A1811-20-*	20	38	.006	.008	.097	.102	11.0					
82A1811-18-*	18	38	.006	.008	.109	.114	14.7					
82A1811-16-*	16	38	.007	.009	.127	.133	20.2					
82A1811-14-*	14	38	.008	.010	.153	.161	29.9					
82A1811-12-*	12	38	.008	.010	.174	.183	40.2					
82A1811-10-*	10	38	.009	.012	.228	.239	67.7					
82A1811-8-*	8	38	.011	.014	.275	.289	100.					
82A1811-6-*	6	36	.011	.015	.328	.344	151.					
82A1811-4-*	4	36	.014	.018	.416	.437	234.					
82A1811-2-*	2	34	.016	.021	.501	.526	349.					
82A1811-1-*	1	34	.017	.023	.560	.588	426.					
82A1811-0-*	0	34	.019	.025	.634	.666	534.					
CABLE RATINGS AND ADDITIONAL REQUIREMENTS												
TEMPERATURE RATING: 150°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level CROSSLINKING PROOF TEST: 300 ± 3°C for 7 hours DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz JACKET COLOR: White preferred JACKET ELONGATION AND TENSILE STRENGTH: Elongation, 100% (minimum) Tensile Strength, 3000 lbf/in² (minimum) JACKT FLAWS: Spark Test, 1500 volts (rms) Impulse Dielectric Test, 6.0 kV (peak)					SECANT MODULUS (Test per ASTM D 882): 4.0 x 10⁴ lbf/in² (maximum), 2% strain, 2 inch jaw separation, 0.2 inch/minute SHIELD COVERAGE: 85% (minimum) VOLTAGE WITHSTAND (Post Environmental): 1000 volts (rms), 60 Hz, 1 minute							
					1/ PART NUMBER: The "*" in the part numbers above shall be replaced by color code designators with a dash separating the component wire color from the jacket color. Example: AWG 22, white component wire; white jacket: 82A1811-22-9-9							
NOTE: Nominal values are for information only. Nominal values are not requirements.												
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.												
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.												
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.					 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297						
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL											
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.											

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9