
Single and Dual Row Solder Pin Tails
Collet Socket – Series 518

FEATURES

- Collet Sockets available in Single or Dual Rows
- Cuttable to the number of pins desired to fit the application
- Side-to-side and end-to-end stackable



GENERAL SPECIFICATIONS

- **BODY MATERIAL**: Black UL 94V-0 Glass-filled 4/6 Nylon
- **PIN BODY**: Brass 360 1/2-hard per UNS C36000 ASTM B16/B16M-05
- **PIN BODY PLATING**: 10µ [0.25µ] min. Au per MIL-G-45204 **–OR–** 200µ [5.08µ] min. 93/7 Sn/Pb per ASTM B545 or 200µ [5.08µ] min. Sn per ASTM B545 Type 1 over 100µ [2.54µ] min. Ni per SAE AMS-QQ-N-290B
- **4-FINGER COLLET CONTACT**: BeCu per UNS C17200 ASTM B194-08
- **CONTACT PLATING**: 200µ [5.08µ] min. 93/7 Sn/Pb per ASTM B545 **–OR–** 200µ [5.08µ] min. Sn per ASTM B545 Type 1 or 10µ [0.25µ] Au per MIL-G-45204 over 50µ [1.27µ] min. [1.27µ] Ni per SAE AMS-QQ-N-290 Heavy 30µ [0.76µ]
- **CONTACT CURRENT RATING**: 3 amps
- **INSERTION FORCE**: 180g/pin, based on 0.018 [0.46] dia. test lead
- **WITHDRAWAL FORCE**: 90g/pin, based on 0.018 [0.46] dia. test lead
- **NORMAL FORCE**: 140g/pin, based on 0.018 [0.46] dia. test lead
- **OPERATING TEMPERATURE**: -67°F to 221°F [-55°C to 105°C] for Sn plating; -67°F to 257°F [-55°C to 125°C] for Au plating
- **INSERTION FORCE**: 180g/pin, based on 0.018 [0.46] dia. test lead
- **WITHDRAWAL FORCE**: 90g/pin, based on 0.018 [0.46] dia. test lead
- **NORMAL FORCE**: 140g/pin, based on 0.018 [0.46] dia. test lead
- **ACCEPTS LEADS**: 0.015-0.025 [0.38-0.64] dia.
- **LEAD LENGTHS**: from 0.100 [2.54] min.

ORDERING INFORMATION

XX X 518-1 XX XX

Additional Options
H = Heavy Au on Collet Shell
T = Sn Collet, Sn Shell
TL = Sn/Pb Collet & Shell
E = Extra Long Solder Pin Tail

Plating
0 = Au Collet, RoHS Shell
0TL = Au Collet, Sn/Pb Shell
1 = Au Collet & Shell

Solder Pin Tail


Series


No. of Rows
0 = Single
1 = Dual

No. of Pins per Socket
1 Row – 1 to 40 Pins
2 Rows – 2 to 66 Pins

MOUNTING CONSIDERATIONS

- **SUGGESTED PCB HOLE SIZE**: 0.030 ±0.002 [0.76 ±0.05] dia.





"A"= NO. OF PINS PER ROW x 0.100 [2.54]
"B"= (NO. OF PINS PER ROW -1) x 0.100 [2.54]

ALL DIMENSIONS: INCHES [MILLIMETERS]
ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED
FOR SOCKET STRIPS WITH WIRE WRAP PINS, SEE DATA SHEETS 12021
CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

CUSTOMIZATION: ARIES SPECIALIZES IN CUSTOM DESIGN AND PRODUCTION. SPECIAL MATERIALS, PLATINGS, SIZES, AND CONFIGURATIONS CAN BE FURNISHED, DEPENDING ON QUANTITY.

ARIES RESERVES THE RIGHT TO CHANGE PRODUCT GENERAL SPECIFICATIONS WITHOUT NOTICE

PRINTOUTS OF THIS DOCUMENT MAY BE OUT-OF-DATE AND SHOULD BE CONSIDERED UNCONTROLLED

ARIES ELECTRONICS, INC.
2609 Bartram Road • Bristol, PA 19007-6810 USA
TEL 215-781-9956 • FAX 215-781-9845
WWW.ARIESELEC.COM • INFO@ARIESELEC.COM

RoHS Compliant

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9