


## “Half Bridge” IGBT MTP (Warp 2 Speed IGBT), 70 A


**MTP**

**RoHS**  
COMPLIANT

**FEATURES**

- NPT warp 2 speed IGBT technology with positive temperature coefficient
- HEXFRED® antiparallel diodes with ultrasoft reverse recovery
- SMD thermistor (NTC)
- Al<sub>2</sub>O<sub>3</sub> BDC
- Very low stray inductance design for high speed operation
- UL pending
- Speed 60 kHz to 150 kHz
- UL approved file E78996
- Designed and qualified for industrial level
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

**BENEFITS**

- Optimized for welding, UPS and SMPS applications
- Lower conduction losses and switching losses
- Low EMI, requires less snubbing
- Direct mounting to heatsink
- PCB solderable terminals

PRODUCT SUMMARY	
V <sub>CES</sub>	600 V
V <sub>CE(on)</sub> typical at V <sub>GE</sub> = 15 V	2.1 V
I <sub>C</sub> at T <sub>C</sub> = 78 °C	70 A
Package	MTP
Circuit	Half bridge

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	V <sub>CES</sub>		600	V
Continuous collector current	I <sub>C</sub>	T <sub>C</sub> = 25 °C	100	A
		T <sub>C</sub> = 78 °C	70	
Pulsed collector current	I <sub>CM</sub>		300	
Peak switching current	I <sub>LM</sub>		300	
Diode continuous forward current	I <sub>F</sub>	T <sub>C</sub> = 78 °C	53	
Peak diode forward current	I <sub>FM</sub>		200	
Gate to emitter voltage	V <sub>GE</sub>		± 20	V
RMS isolation voltage	V <sub>ISOL</sub>	Any terminal to case, t = 1 min	2500	
Maximum power dissipation, IGBT	P <sub>D</sub>	T <sub>C</sub> = 25 °C	347	W
		T <sub>C</sub> = 100 °C	139	



<b>ELECTRICAL SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{(BR)CES}$	$V_{GE} = 0\text{ V}, I_C = 500\text{ }\mu\text{A}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}, I_C = 70\text{ A}$	-	2.1	2.4	V
		$V_{GE} = 15\text{ V}, I_C = 140\text{ A}$	-	2.8	3.4	
		$V_{GE} = 15\text{ V}, I_C = 70\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	2.7	3	
Gate threshold voltage	$V_{GE(th)}$	$I_C = 0.5\text{ mA}$	3	-	6	
Collector to emitter leaking current	$I_{CES}$	$V_{GE} = 0\text{ V}, I_C = 600\text{ V}$	-	-	0.7	mA
		$V_{GE} = 0\text{ V}, I_C = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	-	10	
Gate to emitter leakage current	$I_{GES}$	$V_{GE} = \pm 20\text{ V}$	-	-	$\pm 250$	nA

<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total gate charge (turn-on)	$Q_g$	$I_C = 70\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = 15\text{ V}$	-	460	690	nC
Gate to emitter charge (turn-on)	$Q_{ge}$		-	160	250	
Gate to collector charge (turn-on)	$Q_{gc}$		-	70	130	
Turn-on switching loss	$E_{on}$	$R_g = 10\text{ }\Omega$ $I_C = 70\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}, L = 200\text{ }\mu\text{H}$ Energy losses include tail and diode reverse recovery, $T_J = 25\text{ }^\circ\text{C}$	-	1.1	-	mJ
Turn-off switching loss	$E_{off}$		-	0.9	-	
Total switching loss	$E_{ts}$		-	2	-	
Turn-on switching loss	$E_{on}$	$R_g = 10\text{ }\Omega$ $I_C = 70\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}, L = 200\text{ }\mu\text{H}$ Energy losses include tail and diode reverse recovery, $T_J = 150\text{ }^\circ\text{C}$	-	1.27	-	mJ
Turn-off switching loss	$E_{off}$		-	1.13	-	
Total switching loss	$E_{ts}$		-	2.4	-	
Turn-on delay time	$td_{on}$	$R_g = 10\text{ }\Omega$ $I_C = 70\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}, L = 200\text{ }\mu\text{H}$ Energy losses include tail and diode reverse recovery	-	314	-	ns
Rise time	$t_r$		-	49	-	
Turn-off delay time	$td_{off}$		-	308	-	
Fail time	$t_f$	$R_g = 10\text{ }\Omega$ $I_C = 70\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}, L = 200\text{ }\mu\text{H}$ Energy losses include tail and diode reverse recovery, $T_J = 150\text{ }^\circ\text{C}$	-	68	-	ns
Turn-on delay time	$td_{on}$		-	312	-	
Rise time	$t_r$		-	50	-	
Turn-off delay time	$td_{off}$	$R_g = 10\text{ }\Omega$ $I_C = 70\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}, L = 200\text{ }\mu\text{H}$ Energy losses include tail and diode reverse recovery, $T_J = 150\text{ }^\circ\text{C}$	-	320	-	ns
Fail time	$t_f$		-	78	-	
Input capacitance	$C_{ies}$	$V_{GE} = 0\text{ V}$ $V_{CC} = 30\text{ V}$ $f = 1.0\text{ MHz}$	-	8000	-	pF
Output capacitance	$C_{oes}$		-	790	-	
Reverse transfer capacitance	$C_{res}$		-	110	-	
Reverse BIAS safe operating area	RBSOA	$T_J = 150\text{ }^\circ\text{C}, I_C = 300\text{ A}$ $V_{CC} = 400\text{ V}, V_P = 600\text{ V}$ $R_g = 22\text{ }\Omega, V_{GE} = +15\text{ V to }0\text{ V}$	Fullsquare			



**THERMISTOR SPECIFICATIONS**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Resistance	R <sub>0</sub> <sup>(1)</sup>	T <sub>0</sub> = 25 °C	-	30	-	kΩ
Sensitivity index of the thermistor material	β <sup>(1)(2)</sup>	T <sub>0</sub> = 25 °C T <sub>1</sub> = 85 °C	-	4000	-	K

**Notes**

(1) T<sub>0</sub>, T<sub>1</sub> are thermistor's temperatures


(2)  $\frac{R_0}{R_1} = \exp\left[\beta\left(\frac{1}{T_0} - \frac{1}{T_1}\right)\right]$ , temperature in Kelvin

**DIODE SPECIFICATIONS (T<sub>J</sub> = 25 °C unless otherwise specified)**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Diode forward voltage drop	V <sub>FM</sub>	I <sub>C</sub> = 70 A, V <sub>GE</sub> = 0 V	-	1.64	2.1	V
		I <sub>C</sub> = 140 A, V <sub>GE</sub> = 0 V	-	2.1	2.4	
		I <sub>C</sub> = 70 A, V <sub>GE</sub> = 0 V, T <sub>J</sub> = 150 °C	-	1.69	1.9	
Diode reverse recovery time	t <sub>rr</sub>	V <sub>CC</sub> = 200 V, I <sub>C</sub> = 70 A di/dt = 200 A/μs	-	96	126	ns
Diode peak reverse current	I <sub>rr</sub>		-	9.4	12.8	A
Diode recovery charge	Q <sub>rr</sub>		-	440	750	nC
Diode reverse recovery time	t <sub>rr</sub>	V <sub>CC</sub> = 200 V, I <sub>C</sub> = 70 A di/dt = 200 A/μs T <sub>J</sub> = 125 °C	-	140	194	ns
Diode peak reverse current	I <sub>rr</sub>		-	14	19	A
Diode recovery charge	Q <sub>rr</sub>		-	950	1700	nC


**THERMAL AND MECHANICAL SPECIFICATIONS**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Operating junction temperature range	IGBT, Diode	T <sub>J</sub>	- 40	-	150	°C
	Thermistor		- 40	-	125	
Storage temperature range	T <sub>Stg</sub>		- 40	-	125	
Junction to case	IGBT	R <sub>thJC</sub>	-	-	0.36	°C/W
	Diode		-	-	0.8	
Case to sink per module	R <sub>thCS</sub>	Heatsink compound thermal conductivity = 1 W/mK	-	0.06	-	
Mounting torque to heatsink		A mounting compound is recommended and the torque should be checked after 3 hours to allow for the spread of the compound. Lubricated threads.	3 ± 10 %			Nm
Weight			66			g




94469\_01 **V<sub>CE</sub> - Collector to Emitter Voltage (V)**

Fig. 1 - Typical Output Characteristics




94469\_04 **O<sub>G</sub> - Total Gate Charge (nC)**

Fig. 4 - Typical Gate Charge vs. Gate to Emitter Voltage




94469\_02 **Maximum DC Collector Current (A)**

Fig. 2 - Maximum Collector Current vs. Case Temperature




94469\_05 **V<sub>FM</sub> - Forward Voltage Drop (V)**

Fig. 5 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current




94469\_03 **T<sub>J</sub> - Junction Temperature (°C)**

Fig. 3 - Typical Collector to Emitter Voltage vs. Junction Temperature




94469\_06 **V<sub>CES</sub> - Collector to Emitter Voltage (V)**

Fig. 6 - Typical Zero Gate Voltage Collector Current




94469\_07

Fig. 7 - Typical Gate Threshold Voltage




94469\_10

Fig. 10 - Reverse BIAS SOA,  $T_J = 150\text{ }^\circ\text{C}$




94469\_08

Fig. 8 - Typical Energy Losses vs.  $I_C$  ( $T_J = 150\text{ }^\circ\text{C}$ )




94469\_11

Fig. 11 - Typical Reverse Recovery Time vs.  $di_F/dt$




94469\_09

Fig. 9 - Switching Time vs.  $I_C$




94469\_12

Fig. 12 - Typical Reverse Recovery Current vs.  $di_F/dt$




94469\_13

Fig. 13 - Typical Stored Charge vs.  $di_F/dt$



94469\_14

Fig. 14 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (IGBT)



94469\_15

Fig. 15 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (Diode)




Fig. 16 - Electrical Diagram





Fig. 17 - Functional Diagram

**ORDERING INFORMATION TABLE**

Device code

<b>VS-</b>	<b>70</b>	<b>MT</b>	<b>060</b>	<b>W</b>	<b>H</b>	<b>T</b>	<b>A</b>	<b>PbF</b>
①	②	③	④	⑤	⑥	⑦	⑧	⑨


- 1** - Vishay Semiconductors product
- 2** - Current rating (70 = 70 A)
- 3** - Essential part number
- 4** - Voltage rating (060 = 600 V)
- 5** - Speed/type (W = Warp IGBT)
- 6** - Circuit configuration (H = Half bridge)
- 7** - T = Thermistor
- 8** - A = Al<sub>2</sub>O<sub>3</sub> DBC substrate
- 9** - Lead (Pb)-free

**CIRCUIT CONFIGURATION**

**LINKS TO RELATED DOCUMENTS**

Dimensions	<a href="http://www.vishay.com/doc?95175">www.vishay.com/doc?95175</a>
------------	--

## MTP

**DIMENSIONS** in millimeters



**Note**

- Unused terminals are not assembled in the package





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9