






D



ELECTRICAL RATINGS					
10 AMP CONT.					
A.C. VOLTAGE					POWER FACTOR
	SINGLE POLE		DOUBLE POLE		
	MAKE	BREAK	MAKE	BREAK	
120	60	6	30	3	.35
240	30	3	15	1.5	.35
480	15	1.5	7.5	.75	.35
600	12	1.2	6	.6	.35
A300/120V	N/A	N/A	60	6	.30
A300/240V	N/A	N/A	30	3	.30

D.C. VOLTAGE	MAKE & BREAK INDUCTIVE	RESISTIVE
120	0.25	0.80
240	0.15	0.40
Q300/125V	0.55	N/A
Q300/250V	0.27	N/A

D

C

C

B

B

A

A


D

C


B

A

SIDE ROTARY




OPERATING DATA - SIDE ROTARY




OPERATING CHARACTERISTICS	BXA MOMENTARY		BXR MOMENTARY LOW TORQUE		BXN MAINTAINED	BXP MOMENTARY LOW PRETRAVEL & DIFFERENTIAL TRAVEL		BXH MOMENTARY LOW PRETRAVEL & LOW TORQUE		BXL SEQUENCE DOUBLE POLE ONLY		BXM CENTRAL NEUTRAL DOUBLE POLE ONLY	
PRE-TRAVEL (MAX)	15°		15°		65°	9°		9°		1ST STEP 15° 2ND STEP 10° ADDITIONAL		18°	
OVERTRAVEL (MIN)	60°		60°		20°	68°		68°		48°		57°	
DIFFERENTIAL TRAVEL (MAX)	SINGLE POLE 5°	DOUBLE POLE 7°	SINGLE POLE 5°	DOUBLE POLE 7°	40°	SINGLE POLE 3°	DOUBLE POLE 4°	SINGLE POLE 3°	DOUBLE POLE 4°	5°		10°	
TOTAL TRAVEL (REF)	75°		75°		90°	75°		75°		75°		75°	
OPERATING TORQUE (MAX)	.454 N/M 4 IN. LBS		.193 N/M 4 IN. LBS		.454 N/M 4 IN. LBS	.454 N/M 4 IN. LBS		.193 N/M 1.7 IN. LBS		.454 N/M 4 IN. LBS		.454 N/M 4 IN. LBS	
FULL TRAVEL TORQUE (MAX)	.454 N/M 4 IN. LBS		.193 N/M 4 IN. LBS		-	.454 N/M 4 IN. LBS		.193 N/M 1.7 IN. LBS		.454 N/M 4 IN. LBS		.454 N/M 4 IN. LBS	

TOP ROTARY



	SINGLE POLE	DOUBLE POLE
PRETRAVEL MAX	35°	35°
OVERTRAVEL MAX	100°	100°
DIFFERENTIAL TRAVEL MAX	8°	12°
OPERATING TORQUE MAX	.283 N/M 2.5 IN. LBS	.283 N/M 2.5 IN. LBS
TOTAL TRAVEL (REF)	135°	135°



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

Honeywell					REV
SIZE	TYPE	CAGE CODE	DRAWING NAME		14
D	I	-	BX SERIES CHART 1		
SCALE	1:1		SHEET		3 OF 6



D

C

B

A

↓







SIDE PLUNGER TYPES

CHARACTERISTICS	BXE PLUNGER	BXF ROLLER PLUNGER	BXW ADJUSTABLE PLUNGER	SEQUENCE BASIC		
				BXE	BXF	BXW
PRE-TRAVEL (MAX)	2.54 / .100	2.54 / .100	2.54 / .100	1ST STEP 2.54 / .100 2ND STEP .51 / .020 MIN. ADDITIONAL.		
DIFFERENTIAL TRAVEL (MAX)	1.14 / .045	1.14 / .045	1.14 / .045	.64 / .025 EACH STEP		
OVERTRAVEL (MIN)	4.83 / .190	4.83 / .190	4.83 / .190	4.32 / .170		
OPERATING FORCE (MAX)	26.79 N / 6 LBS	26.79 N / 6 LBS	26.79 N / 6 LBS	26.79 N 6 LBS		
OPERATING POINT	33.02 ± .76 / 1.300 ± .030	44.07 ± 1.02 / 1.735 ± .040	41.02 / 1.615 MIN 47.37 / 1.665 MAX	1ST STEP		
				33.27±.76/1.310±.030	44.32 ±1.02/ 1.745±.040	41.28/1.625 MIN. 47.63/1.875 MAX.
FULL OVERTRAVEL FORCE (MAX)	26.79 N / 6 LBS	26.79 N / 6 LBS	26.79 N / 6 LBS	26.79 N 6 LBS		

SIZE	TYPE	CAGE CODE	DRAWING NAME	REV
D	I	-	BX SERIES CHART 1	14
SCALE	1 : 1		SHEET	4 OF 6

PLUNGER TYPE TOP





* TYPE BXV (3&7) 1/2 -14 NPT CONDUIT
TYPE BXV (1&4) 3/4 - 14 NPT CONDUIT
TYPE BX3V (1 THRU 4) PG 13.5 CONDUIT
TYPE BX4V (1 THRU 4) 20 MM CONDUIT
TYPE BX5V (1 THRU 4) PF 1/2 CONDUIT

* TYPE BX (C OR G) (3&7) 1/2 -14 NPT CONDUIT
TYPE BX (C OR G) (1&4) 3/4 - 14 NPT CONDUIT
TYPE BX3 (C OR G) (1 THRU 4) PG 13.5 CONDUIT
TYPE BX4 (C OR G) (1 THRU 4) 20 MM CONDUIT
TYPE BX5 (C OR G) (1 THRU 4) PF 1/2 CONDUIT

OPERATING POINT GIVEN
IN RELATION TO TOP MOUNTING HOLES

TOP PLUNGER TYPES

CHARACTERISTICS	BXC PLUNGER		BXD ROLLER PLUNGER		BXV ADJUSTABLE PLUNGER		SEQUENCE BASIC			BXG
							BXC	BXD	BXV	
PRETRAVEL(MAX)	1.79 / .070		1.79 / .070		1.79 / .070		1ST STEP 1.79/.070 2ND STEP .41/.015 MIN ADDITIONAL.			1.79 / .070
DIFFERENTIAL TRAVEL (MAX)	SINGLE POLE .38/.015	DOUBLE POLE 0.51 / .020	SINGLE POLE 0.38/.015	DOUBLE POLE .51/.020	SINGLE POLE	DOUBLE POLE	.38/.01 EACH STEP			.51 / .020
OVERTRAVEL(MIN)	4.83 / .190		4.83 / .190		4.83 / .190		4.32 / .170			4.83 / .190
OPERATING FORCE (MAX)	17.86 N / 4 LBS		17.86 N / 4 LBS		17.86 N / 4 LBS		17.86 N / 4 LBS			17.86 N / 4 LBS
OPERATING POINT	58.55 ±.76 / 2.305±.030		68.58±1.02 / 2.700±.040		65.66/2.585 MIN 72.01/2.835 MAX		1ST STEP			58.55 ± .76 / 2.305 ± .030
							46.10±.76/1.815±.030 53.21/2.095 MIN. 56.13 ±1.02/2.210±.040 59.56/ 2.345 MAX.			
FULL OVERTRAVEL FORCE(MAX)	31.25 N / 7 LBS		31.25 N / 7 LBS		31.25 N / 7 LBS		31.25 N / 7 LBS			31.25 N / 7 LBS



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9