November 1998

FDG6321C
Dual N & P Channel Digital FET

General Description


These dual N & P-Channel logic level enhancement mode field effect transistors are produced using Fairchild's proprietary, high cell density, DMOS technology. This very high density process is especially tailored to minimize on-state resistance. This device has been designed especially for low voltage applications as a replacement for bipolar digital transistors and small signal MOSFETS. Since bias resistors are not required, this dual digital FET can replace several different digital transistors, with different bias resistor values.

Features


- N-Ch 0.50 A, 25 V, $R_{DS(ON)}$ = 0.45 Ω @ V_{GS}= 4.5V.
  $R_{DS(ON)}$ = 0.60 Ω @ V_{GS}= 2.7 V.
- P-Ch -0.41 A, -25 V,$R_{DS(ON)}$ = 1.1 Ω @ V_{GS}= -4.5V.
  $R_{DS(ON)}$ = 1.5 Ω @ V_{GS}= -2.7V.
- Very small package outline SC70-6.
- Very low level gate drive requirements allowing direct operation in 3 V circuits($V_{GS(th)}$ < 1.5 V).
- Gate-Source Zener for ESD ruggedness (>6kV Human Body Model).



SC70-6 | SOT-23 | SuperSOT™-6 | SOT-8 | SO-8 | SOIC-14



SC70-6



Absolute Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	N-Channel	P-Channel	Units
V_{DSS}	Drain-Source Voltage	25	-25	V
V_{GSS}	Gate-Source Voltage	8	-8	V
I_D	Drain Current - Continuous	0.5	-0.41	A
	- Pulsed	1.5	-1.2	
P_D	Maximum Power Dissipation (Note 1)	0.3		W
T_J,T_{STG}	Operating and Storage Temperature Ranger	-55 to 150		°C
ESD	Electrostatic Discharge Rating MIL-STD-883D Human Body Model (100pf / 1500 Ohm)	6		kV
THERMAL CHARACTERISTICS				
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	415		°C/W

© 1998 Fairchild Semiconductor Corporation

Electrical Characteristics (T_A = 25 °C unless otherwise noted)

Symbol	Parameter	Conditions	Type	Min	Typ	Max	Units
OFF CHARACTERISTICS							
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_D = 250 µA	N-Ch	25			V
		V_{GS} = 0 V, I_D = -250 µA	P-Ch	-25			
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	I_D = 250 µA, Referenced to 25 °C	N-Ch		26		mV/°C
		I_D = -250 µA, Referenced to 25 °C	P-Ch		-22		
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 20 V, V_{GS} = 0 V	N-Ch			1	µA
		T_J = 55°C				10	
I_{GSS}	Gate - Body Leakage Current	V_{DS} = -20 V, V_{GS} = 0 V	P-Ch			-1	µA
		T_J = 55°C				-10	
I_{GSS}	Gate - Body Leakage Current	V_{GS} = 8 V, V_{DS} = 0 V	N-Ch			100	nA
		V_{GS} = -8 V, V_{DS} = 0 V	P-Ch			-100	nA
ON CHARACTERISTICS (Note 2)							
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250 µA	N-Ch	0.65	0.8	1.5	V
		V_{DS} = V_{GS}, I_D = -250 µA	P-Ch	-0.65	-0.82	-1.5	
$\Delta V_{GS(th)}/\Delta T_J$	Gate Threshold Voltage Temp. Coefficient	I_D = 250 µA, Referenced to 25 °C	N-Ch		-2.6		mV/ °C
		I_D = -250 µA, Referenced to 25 °C	P-Ch		2.1		
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS} = 4.5 V, I_D = 0.5 A	N-Ch		0.34	0.45	Ω
		T_J =125°C			0.55	0.72	
		V_{GS} = 2.7 V, I_D = 0.2 A			0.44	0.6	
		V_{GS} = -4.5 V, I_D = -0.41 A	P-Ch		0.85	1.1	
		T_J =125°C			1.2	1.8	
		V_{GS} = -2.7 V, I_D = -0.25 A			1.15	1.5	
$I_{D(ON)}$	On-State Drain Current	V_{GS} = 4.5 V, V_{DS} = 5 V	N-Ch	0.5			A
		V_{GS} = -4.5 V, V_{DS} = -5 V	P-Ch	-0.41			
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 0.5 A	N-Ch		1.45		S
		V_{DS} = -5 V, I_D = -0.41 A	P-Ch		0.9		
DYNAMIC CHARACTERISTICS							
C_{iss}	Input Capacitance	N-Channel	N-Ch		50		pF
		V_{DS} = 10 V, V_{GS} = 0 V,	P-Ch		62		
C_{oss}	Output Capacitance	f = 1.0 MHz	N-Ch		28		
		P-Channel	P-Ch		34		
C_{rss}	Reverse Transfer Capacitance	V_{DS} = -10 V, V_{GS} = 0V,	N-Ch		9		
		f = 1.0 MHz	P-Ch		10		

Electrical Characteristics (continued)

SWITCHING CHARACTERISTICS (Note 2)

Symbol	Parameter	Conditions	Type	Min	Typ	Max	Units
$t_{D(on)}$	Turn - On Delay Time	N-Channel	N-Ch		3	6	nS
		V_{DD} = 5 V, I_D = 0.5 A,	P-Ch		7	15	
t_r	Turn - On Rise Time	V_{GS} = 4.5 V, R_{GEN} = 50 Ω	N-Ch		8.5	18	nS
			P-Ch		8	16	
$t_{D(off)}$	Turn - Off Delay Time	P-Channel	N-Ch		17	30	nS
		V_{DD} = -5 V, I_D = -0.5 A,	P-Ch		55	80	
t_f	Turn - Off Fall Time	V_{GS} = -4.5 V, R_{GEN} = 50 Ω	N-Ch		13	25	nS
			P-Ch		35	60	
Q_g	Total Gate Charge	N-Channel	N-Ch		1.64	2.3	nC
		V_{DS} = 5 V, I_D = 0.5 A,	P-Ch		1.1	1.5	
Q_{gs}	Gate-Source Charge	V_{GS} = 4.5 V	N-Ch		0.38		nC
		P- Channel	P-Ch		0.31		
Q_{gd}	Gate-Drain Charge	V_{DS} = -5 V, I_D = -0.41 A,	N-Ch		0.45		nC
		V_{GS} = -4.5 V	P-Ch		0.29		
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS							
I_S	Maximum Continuous Drain-Source Diode Forward Current		N-Ch			0.25	A
			P-Ch			-0.25	
V_{SD}	Drain-Source Diode Forward Voltage	V_{GS} = 0 V, I_S = 0.5 A (Note 2)	N-Ch		0.8	1.2	V
		V_{GS} = 0 V, I_S = -0.5 A (Note 2)	P-Ch		-0.85	-1.2	

Notes:

1. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. $R_{\theta JA}$ = 415°C/W on minimum mounting pad on FR-4 board in still air.
2. Pulse Test: Pulse Width ≤ 300µs, Duty Cycle ≤ 2.0%.

Typical Electrical Characteristics: N-Channel




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Electrical Characteristics: N-Channel (continued)




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.

Typical Electrical Characteristics: P-Channel




Figure 11. On-Region Characteristics.




Figure 12. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 13. On-Resistance Variation with Temperature.




Figure 14. On-Resistance Variation with Gate-to-Source Voltage.




Figure 15. Transfer Characteristics.




Figure 16. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Electrical Characteristics: P-Channel (continued)




Figure 17. Gate Charge Characteristics.




Figure 18. Capacitance Characteristics.




Figure 19. Maximum Safe Operating Area.




Figure 20. Single Pulse Maximum Power Dissipation.

Typical Thermal Characteristics: N & P-Channel (continued)




Figure 21. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in note 1.
Transient thermalresponse will change depending on the circuit board design.

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
CoolFET™
CROSSVOLT™
E^2CMOS^{TM}
FACT™
FACT Quiet Series™
FAST®
FASTr™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
POP™
PowerTrench™
QFET™
QS™
Quiet Series™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9