



CY3688

MoBL-USB™ TX2UL Development Kit Guide

Doc. # 001-46448 Rev. *C

Cypress Semiconductor
198 Champion Court
San Jose, CA 95134-1709
Phone (USA): 800.858.1810
Phone (Intl): 408.943.2600
<http://www.cypress.com>

Copyright © 2008-2012 Cypress Semiconductor Corporation. All rights reserved.

MoBL-USB™ is a trademark of Cypress Semiconductor Corporation. All other trademarks or registered trademarks referenced herein are the property of their respective owners.

The information in this document is subject to change without notice and should not be construed as a commitment by Cypress. While reasonable precautions have been taken, Cypress assumes no responsibility for any errors that may appear in this document. No part of this document may be copied or reproduced in any form or by any means without the prior written consent of Cypress. Made in the U.S.A.

Disclaimer

CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Flash Code Protection

Cypress products meet the specifications contained in their particular Cypress Data Sheets. Cypress believes that its family of products is one of the most secure families of its kind on the market today, regardless of how they are used. There may be methods, unknown to Cypress, that can breach the code protection features. Any of these methods, to our knowledge, would be dishonest and possibly illegal. Neither Cypress nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Cypress is willing to work with the customer who is concerned about the integrity of their code. Code protection is constantly evolving. We at Cypress are committed to continuously improving the code protection features of our products.

Contents



1. Introduction	5
1.1 Kit Components	5
1.2 Development Board	5
1.2.1 Connector and Jumper Definition on the Development Board	5
1.2.2 Power Supply	6
1.2.3 ULPI Interface	6
1.2.4 CS_N and RESET	6
1.2.5 Testing and Accessibility	7
1.2.6 Specification	7
1.3 Document Revision History	8
1.4 Documentation Conventions	8
A. Appendix	9
A.1 TX3 DVK Board Schematic	9

1. Introduction



The CY3688 MoBL-USB™ TX2UL Development Kit (DVK) is a combination of hardware and documentation, which can be used to evaluate the MoBL-USB TX2UL device and to integrate it to existing development platforms with ULPI interface.

The Cypress MoBL-USB TX2UL is a low-voltage high-speed and full-speed compatible USB 2.0 ULPI Transceiver. The TX2UL is specifically designed for mobile handset applications by offering tiny package options and low power consumption.

Due to the requirement for backward compatibility in the USB 2.0 specification, the USB 2.0 ULPI PHY functions with either a Full-Speed (12 Mbits/sec) USB host or a High-Speed (480 Mbits/sec) USB host.

1.1 Kit Components

- Development board
- Quick start guide
- CD ROM
- Power supply
- USB A to B cable

1.2 Development Board

The board can be used to interconnect to a development platform with ULPI Link. After the TX2UL device is configured, the link enumerates to the USB host PC and runs traffic. USB signal quality testing is done to confirm the quality of TX2UL eye diagram. Board schematic and layout are included in the CD ROM.

1.2.1 Connector and Jumper Definition on the Development Board

J1: 100-pin T&MT connector

D3, D6, D8: Power indication


U2: USB Type B connector

J11: VBATT power supply selector

J4: Jumper for CS_N inversion for links with active high operation

J5: Jumper for RESET_N inversion for links with active high operation

Figure 1-1. Block Diagram



1.2.2 Power Supply

The TX2UL device VDD and VIO power supplies are expected to be supplied from the ULPI connector. VBATT power supply can be supplied from VBUS or the external power supply included with the kit. To power the board using VBUS, connect pin 2 and 3 of J11. Make sure the USB cable is connected to a host USB port. The other option is to use the included power supply and connect 1 and 2 of J11 (default configuration).

The system is equipped with a method to check the power consumption of the TX2UL device. Measure the voltage drop across R7, R13, and R12, this is the current consumed by VDD, VIO, and VBATT consecutively.

1.2.3 ULPI Interface

UTMI+ Low Pin Interface (ULPI) is a standard interface developed to interface a link to a USB 2.0 PHY. It supports an 8-bit wide SDR data path. The primary I/Os of this block support multirange LVCMOS signaling from 1.8 V to 3.3 V. The level used is automatically selected by the voltage applied to VIO and can be set at any voltage between 1.8 V and 3.3 V.

The ULPI interface is mapped to J1 for interconnection to development platforms. The connector pinout is as specified by the ULPI specification, page 92. Use the schematic attached in the CD/DVD ROM as a reference.


1.2.4 CS_N and RESET

The TX2UL device uses CS_N and RESET_N as active low inputs. In case this system is used with a link with active high GPIO operation, an option is available to invert these signals. The default is J4 and J5; connect 1 and 2 for direct connection from link. Connecting 2 and 3 will invert these signals.

1.2.5 Testing and Accessibility

J2 and J14 shown in the following figure are test points for debugging purposes. It can be used to connect a logic analyzer to observe the ULPI bus timing.

Figure 2. Testing and Accessibility



1.2.6 Specification

The following specifications are useful when developing with the TX2UL USB 2.0 ULPI PHY. These specifications are also found at <http://www.usb.org>.

- UTMI+ Low Pin Interface (ULPI) Specification, V1.1
- USB 2.0 Specification, USB Implementers Forum (USB-IF)

1.3 Document Revision History

Rev.	PDF Creation Date	Origin of Change	Description of Change
**	05/20/2008	AESA	New Guide.
*A	09/15/2009	AESA	Changed Part Number to TX2UL.
*B	05/05/2011	EYZ	Added schematic
*C	03/29/2012	HBM	Updated Chapter Title in Cover page as "CY3688 MoBL-USB™ TX2UL Development Kit Guide". Updated Chapter Title in Chapter 1 as "Introduction".

1.4 Documentation Conventions


Table 1. Documentation Conventions for User Guides

Convention	Usage
Courier New	Displays file locations, user entered text, and source code: <code>C:\...cd\icc\</code>
Italics	Displays file names and reference documentation: Read about the <i>sourcefile.hex</i> file in the <i>PSoC Designer User Guide</i> .
[Bracketed, Bold]	Displays keyboard commands in procedures: [Enter] or [Ctrl] [C]
File > Open	Represents menu paths: File > Open > New Project
Bold	Displays commands, menu paths, and icon names in procedures: Click the File icon and then click Open .
Times New Roman	Displays an equation: $2 + 2 = 4$
No text, gray table cell	Represents a reserved bit in register tables.

A. Appendix



A.1 TX3 DVK Board Schematic



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9