


## Edgeboard Connectors, Dual Readout, 0.100" (2.54 mm) C-C, Standard and Right Angle Terminals



### ELECTRICAL SPECIFICATIONS

**Current Rating:** 3 A

**Test Voltage Between Contacts:**

At sea level: 650 V<sub>RMS</sub>

At 70 000 feet (21 336 meters): 275 V<sub>RMS</sub>

**Insulation Resistance:** 5000 MΩ minimum at 500 V<sub>DC</sub> potential

**Contact Resistance:** 30 mV maximum at rated current (with gold plating)

**Operating Temperature:** - 65 °C to + 125 °C

**Humidity:** 96 h at 90 % relative humidity at + 40 °C, dried at room temperature for 3 h minimum, insulation resistance was greater than 5000 MΩ

**Durability:** After 500 cycles of insertion and withdrawal of a 0.070" (1.78 mm) thick steel test board, contact resistance less than 0.030 V at 3 A on gold plated contacts and individual contact pair separation force when measured with a 0.054" (1.37 mm) thick steel test blade was greater than ½ oz.

**Shock:** Three 50G shocks in each of 3 mutually perpendicular planes with no loss of continuity

**Vibration:** 2 h in each of 3 mutually perpendicular planes, frequency sweep 10 cps to 55 cps at 0.06 double amplitude with no loss of continuity

### FEATURES

- Grid Patterns: 0.100" C-C x 0.150" (2.54 mm x 3.81 mm) and 0.100" C-C x 0.200" (2.54 mm x 5.08 mm)
- Standard and right angle terminals
- Greater design latitude:  
4 body materials: Diallyl phthalate, phenolic, glass-filled polyester and glass-filled polyphenylene sulfied  
7 contact termination styles - 3 standard, 4 right angle  
20 body sizes and 6 mounting styles
- Selective gold plating
- Accepts PC board thickness of 0.054" to 0.071" (1.37 mm to 1.80 mm)
- Polarization between contact positions in all sizes.  
Between contact polarization permits polarizing without loss of contact position.
- Recognized under the Component Program of Underwriters Laboratories, Inc. listed under file E65524, project 77CH3889**

### APPLICATIONS

For use with 0.0625" (1.59 mm) printed circuit boards requiring an edgeboard type connector on 0.100" (2.54 mm) centers

### MATERIAL SPECIFICATIONS

#### Body Material:

"1" glass-filled diallyl phthalate per MIL-M-14, Type SDG-F green, flame retardant (UL 94 V-0)

"2" glass-filled phenolic per MIL-M-14, Type MFH dark green, flame retardant (UL 94 V-0)

"3" thermoplastic polyester, glass-filled, black, flame retardant (UL 94 V-0)

"5" thermoplastic polyphenylene sulfied, glass filled, brown, flame retardant (UL 94 V-0)

**Contacts:** Phosphor bronze (See Ordering Information)

**Polarizing Key:** Glass reinforced nylon, flame retardant (UL 94H-B)

**Plating:** Gold (See Ordering Information)





### ORDERING INFORMATION

| EB4   | 3                                      | K                            | 20                                  | SG                                                                                                                | X                   | 15                                                                                                                                                                                                                                                        |
|-------|----------------------------------------|------------------------------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MODEL | BODY MATERIAL                          | STANDARD TERMINAL VARIATIONS | CONTACTS PER SIDE                   | CONTACT PLATING                                                                                                   | MOUNTING VARIATIONS | POLARIZING KEY POSITIONS                                                                                                                                                                                                                                  |
|       | 1 = Diallyl Phthalate                  | C, D, K,                     | 6, 10, 12, 15, 18, 20,              | SG = Selective gold plating (0.00003" (0.000762 mm) minimum thick) on contact area with gold flash on terminal.   |                     | Key(s) are located to right of position(s) designated. Use odd-numbered contact for ordering: -1, -3, -5, etc. Required only when polarizing keys are to be factory installed.<br><b>Note:</b> To order polarizing keys individually, specify model PK-4. |
|       | 2 = Phenolic                           | 1R, 2R,                      | 22, 25, 28,                         | SGF = Selective gold plating (0.000010" (0.000254 mm) minimum thick) on contact area with gold flash on terminal. |                     |                                                                                                                                                                                                                                                           |
|       | 3 = Glass-filled Polyester             | 3R, 4R                       | 30, 31, 35, 36, 40, 43, 44, 48, 49, | All gold plating over 0.00005" (0.00127 mm) minimum nickel underplate.                                            |                     |                                                                                                                                                                                                                                                           |
|       | 5 = Glass-filled Polyphenylene Sulfied |                              | 50, 60, and 65                      | Contact factory for additional plating options.                                                                   |                     |                                                                                                                                                                                                                                                           |
|       |                                        |                              |                                     |                                                                                                                   |                     |                                                                                                                                                                                                                                                           |

# Edgeboard Connectors, Dual Readout, 0.100" (2.54 mm) C-C, Standard and Right Angle Terminals


Vishay Dale

## DIMENSIONS in inches (millimeters)



### Polarizing Key:

When ordering polarizing keys individually, specify by the Model Number:  
PK-4 between contacts. Hand insertion tool, TPK-4, provided upon request.



| # OF CONTACT POSITIONS PER SIDE | A              | B              | C              | D              | E              |
|---------------------------------|----------------|----------------|----------------|----------------|----------------|
| 6                               | 1.435 (36.45)  | 1.175 (29.85)  | 0.700 (17.78)  | 0.860 (21.84)  | 0.750 (19.05)  |
| 10                              | 1.835 (46.61)  | 1.575 (40.00)  | 1.100 (27.94)  | 1.260 (32.00)  | 1.150 (29.21)  |
| 12                              | 2.035 (51.69)  | 1.775 (45.08)  | 1.300 (33.02)  | 1.460 (37.08)  | 1.350 (34.29)  |
| 15                              | 2.335 (59.31)  | 2.075 (52.70)  | 1.600 (40.64)  | 1.760 (44.70)  | 1.650 (41.91)  |
| 18                              | 2.635 (66.93)  | 2.375 (60.32)  | 1.900 (48.26)  | 2.060 (52.32)  | 1.950 (49.53)  |
| 20                              | 2.835 (72.01)  | 2.575 (65.40)  | 2.100 (53.34)  | 2.260 (57.40)  | 2.150 (54.61)  |
| 22                              | 3.035 (77.09)  | 2.775 (70.48)  | 2.300 (58.42)  | 2.460 (62.48)  | 2.350 (59.69)  |
| 25                              | 3.335 (84.71)  | 3.075 (78.10)  | 2.600 (66.04)  | 2.760 (70.10)  | 2.650 (67.31)  |
| 28                              | 3.635 (92.33)  | 3.375 (85.72)  | 2.900 (73.66)  | 3.060 (77.72)  | 2.950 (74.93)  |
| 30                              | 3.835 (97.41)  | 3.575 (90.80)  | 3.100 (78.74)  | 3.260 (82.80)  | 3.150 (80.01)  |
| 31                              | 3.935 (99.95)  | 3.675 (93.34)  | 3.200 (81.28)  | 3.360 (85.34)  | 3.250 (82.55)  |
| 35                              | 4.335 (110.11) | 4.075 (103.50) | 3.600 (91.44)  | 3.760 (95.50)  | 3.650 (92.71)  |
| 36                              | 4.435 (112.65) | 4.175 (106.04) | 3.700 (93.98)  | 3.860 (98.04)  | 3.750 (95.25)  |
| 40                              | 4.835 (122.81) | 4.575 (116.20) | 4.100 (104.14) | 4.260 (108.20) | 4.150 (105.41) |
| 43                              | 5.135 (130.43) | 4.875 (123.82) | 4.400 (111.76) | 4.560 (115.82) | 4.450 (113.03) |
| 44                              | 5.235 (132.97) | 4.975 (126.36) | 4.500 (114.30) | 4.660 (118.36) | 4.550 (115.57) |
| 48                              | 5.635 (143.13) | 5.375 (136.52) | 4.900 (124.46) | 5.060 (128.52) | 4.950 (125.73) |
| 49                              | 5.735 (145.67) | 5.475 (139.06) | 5.000 (127.00) | 5.160 (131.06) | 5.050 (128.27) |
| 50                              | 5.835 (148.21) | 5.575 (141.60) | 5.100 (129.54) | 5.260 (133.60) | 5.150 (130.81) |
| 60                              | 6.835 (173.61) | 6.575 (167.00) | 6.100 (154.94) | 6.260 (159.00) | 6.150 (156.21) |
| 65                              | 7.335 (186.31) | 7.075 (179.70) | 6.600 (167.64) | 6.760 (171.70) | 6.650 (168.91) |

# Vishay Dale Edgeboard Connectors, Dual Readout, 0.100" (2.54 mm) C-C, Standard and Right Angle Terminals

## PHYSICAL SPECIFICATIONS

**Contact Type:** Bifurcated cantilever beam

**Number of Contacts:** 10, 12, 15, 18, 20, 22, 25, 28, 30, 31, 35, 36, 40, 43, 44, 48, 49, 50, 60 and 65 per side

**Contact Terminal Variation:** Standard terminals

**Type "C"** - dip solder, 0.025" (0.635 mm) square terminals, 0.175" (4.44 mm) nominal terminal length below standoffs

**Type "D"** - dip solder, 0.025" (0.635 mm) square terminals, 0.115" (2.92 mm) nominal terminal length below standoffs

**Type "K"** - Wire Wrap™, 0.025" (0.635 mm) square terminals, 0.570" (14.48 mm) nominal terminal length below standoffs

**Contact Terminal Variation:** Right angle terminals

**Type "1R"** - dip solder, 0.025" (0.635 mm) square terminals, 0.120" (3.05 mm) nominal terminal length x 0.150" (3.81 mm) nominal terminal row spacing

**Type "2R"** - dip solder, 0.025" (0.635 mm) square terminals, 0.120" (3.05 mm) nominal terminal length x 0.200" (5.08 mm) nominal terminal row spacing

**Type "3R"** - dip solder, 0.025" (0.635 mm) square terminals, 0.180" (4.57 mm) nominal terminal length x 0.150" (3.81 mm) nominal terminal row spacing

**Type "4R"** - dip solder, 0.025" (0.635 mm) square terminals, 0.180" (4.57 mm) nominal terminal length x 0.200" (5.08 mm) nominal terminal row spacing

**Contact Spacing:** 0.100" (2.54 mm) center to center

**Contact Terminal Row Spacing:** Standard - 0.200" (5.08 mm) nominal. Right angle - 0.200" (5.08 mm) nominal and 0.150" (3.81 mm) nominal

**Card Thickness:** 0.054" to 0.071" (1.37 mm to 1.80 mm)


**Card Slot Depth:** 0.300" (7.62 mm)

**Connector Polarization:** Between contact polarization key(s) are located to the right of the contact position(s) designated


### Note

- High temperature burn-in, edgeboard connectors, with 0.100" (2.54 mm) center to center are on [www.vishay.com/doc?36006](http://www.vishay.com/doc?36006)

## MOUNTING VARIATIONS in inches (millimeters)



## TERMINAL VARIATIONS in inches (millimeters)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9