Blackhawk ™XDS560v2 System Trace for TI Devices

TI Devices: C6000, C5000, C2000, OMAP, DAVINCI, SITARA, TMS470, TMS570, ARM 7/9, ARM Cortex A8/R4/M3 and more Compatible Operating Systems: Windows® (2000/XP/Vista/7) and Linux (RedHat/Fedora/Ubuntu/SUSE, etc.) 32 and 64-bit editions Part Number: BH-XDS-560v2-BP (bus-powered) Part Number: BH-XDS-560v2 (PoE Model)

The Blackhawk XDS560v2 System Trace Emulator (BH560v2) is based on the new Texas Instruments XDS560v2 JTAG emulator reference design (XDS560v2). The XDS560v2 design is the next-generation of the high-performance XDS560-class technology first made available by Blackhawk with the USB560/LAN560 and XDS560 Trace. The XDS560v2 design includes both high-speed USB 2.0 and 10/100Mbit Ethernet host interfaces, multi-color state and activity LEDs and a flexible ribbonized coax JTAG cable. The XDS560v2 adds support for IEEE1149.7 and the system trace

XOSSGO System Trace
Pert :: 6HX05560A

module (STM), an interface on the TI heterogeneous multi-core (ARM + DSP) devices. If you are familiar with the Blackhawk LAN560 product, you will already be familiar with this new design.

Blackhawk Emulators are available from a world wide network of

The BH560v2 meets all of the TI XDS560v2 reference design features and requirements and extends (improves) capabilities by offering the following enhanced features.

- POWER: This is the first and most important feature enhancement. The BH560v2 has the option to be powered from either the USB or POE (power over Ethernet) connectors. Yes, the unit can be powered solely from the USB; a great feature for road warriors. And for LAN operation, the BH560v2 offers a 802.11af POE connector that can be powered from a POE enabled switch or available POE injector supply.
- INDICATORS: We also added dedicated power and USB activity LEDs, which are found on the current Blackhawk USB560m and LAN560 models.
- CONFIGURATION & TEST: The BH560v2 includes a graphical user interface application that allows users to find, update, configure and test Bh560v2 devices on the local area network (LAN). You can even name the units, configure DHCP or fixed IP and more.

Blackhawk XDS560v2 Enhanced Feature Set

- Power Over USB Standard
- Power Over Ethernet Option
- Additional Dedicated LEDs for Power and USB
- LAN and USB Graphical Configuration & Diagnostic Tool

Standard Features of TI XDS560v2 and Blackhawk XDS560v2

- Supports Code Composer Studio v4.2 or later and all Ctools enabled devices
- Flexible 12.5 inch JTAG cable with native 60-pin MIPI HSPT Target Cable
- Includes 20-pin compact TI (cTI), 14-pin standard TI and 20-pin ARM Adapters
- Supports JTAG 1149.1 and 1149.7
- Auto-Adaptive T-clock (TCLK) up to 50MHz
- Auto Sensing Target voltage range from 1.2v to 4.1v
- JTAG Debug Isolation, JTAG loop-back Modes and Boot Mode EMU0 & EMU1
- Supports 1-4 pin System Trace with 128 Mbytes of System Trace Buffer
- Up to 100MHz export clock compliant to MIPI STP
- Auto compensating calibration for edge jitter, channel skew and duty cycle
- Adaptive receiver for setup/hold times up to 1.5ns
- High-Speed USB 2.0 port @ 480Mbit/sec and 10/100 Ethernet port
- Supports Mobile Industry Processor Interface (MIPI)
- Supports System Trace Protocol (STP) and High-speed Parallel Trace (HSPT)
- Eight (8) tri-color status, state and activity LEDs

Blackhawk ™ JTAG Blackhawk Powering DSP Developm Emulators AND DEVELOPMENT TOOLS FOR TEXAS INSTRUMENTS DSPS INSTRUMENTS INSTRUMEN



123 Gaither Drive ● Mt. Laurel, NJ 08054 ● 877-983-4514 ● www.blackhawk-dsp.com

Items Included in the Box

- 1. XDS560v2 System Trace Emulator Pod
- 2. System Trace Coax JTAG Cable
- 3. MIPI60 buffer board
- 4. Pin Converters (4): TI14, TI20, TI60 trace, and ARM20 targets
- 5. USB Cable
- 6. Product Registration Card
- 7. Quick Start Guide
- 8. CDROM
- POE Injector power supply and wall cords (PoE Model)
- 10. Ethernet Cables (2) (PoE Model)

ABOUT BLACKHAWK

EWA Technologies, Inc. is a major global player in the application of the IEEE 1149.x standards (known as boundary-scan or JTAG) to state-of-the-art products that will support the design, prototyping and production of the next generation of complex technology products. EWA Technologies consists of two operating units: the Blackhawk™ division in Mount Laurel, NJ, and Corelis, Inc. in Cerritos, CA. The Blackhawk™ division is a leader in providing hardware and software for the rapid development of digital signal processor-based (DSP) applications for a wide variety of vertical markets. Blackhawk™ is a Texas Instruments® (TI) DSP Third Party provider for development hardware, advanced JTAG emulators, Real-Time Operating Systems, design services and consulting.

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru 4 moschip.ru 9