

Complies with the following standards

- IEC 61000-4-2 level 4:
 - 15 kV (air discharge)
 - 8 kV (contact discharge)
- IEC 61000-4-5
- MIL STD 883G, method 3015-7: class 3B:
 - 25 kV HBM (human body model)
- UL 497B, file number: QVGG2.E136224
- Resin meets UL 94, V0
- MIL-STD-750, method 2026 solderability
- EIA STD RS-481 and IEC 60286-3 packing
- IPC 7531 footprint

Features

- Peak pulse power:
 - 600 W (10/1000 μ s)
 - 4 kW (8/20 μ s)
- Stand-off voltage range: from 6.8 V to 220 V
- Unidirectional and bidirectional types
- Low leakage current:
 - 0.2 μ A at 25 °C
 - 1 μ A at 85 °C
- Operating T_j max: 150 °C
- High power capability at T_j max.:
 - 515 W (10/1000 μ s)
- JEDEC registered package outline

Description

The SM6T Transil series are designed to protect sensitive equipment against electrostatic discharges according to IEC 61000-4-2 and MIL STD 883, method 3015, and electrical overstress according to IEC 61000-4-4 and 5. These devices are more generally used against surges below 600 W (10/1000 μ s).

The Planar technology makes it suitable for high-end equipment and SMPS where low leakage current and high junction temperature are required to provide reliability and stability over time.

SM6T are packaged in SMB (SMB footprint in accordance with IPC 7531 standard).

1 Characteristics

Table 1: Absolute maximum ratings (T_{amb} = 25 °C)

| Symbol | Parameter | | Value | Unit |
|------------------|--|---|-------------|------|
| P _{PP} | Peak pulse power dissipation ⁽¹⁾ | T _j initial = T _{amb} | 600 | W |
| T _{stg} | Storage temperature range | | -65 to +150 | °C |
| T _j | Operating junction temperature range | | -55 to +150 | °C |
| T _L | Maximum lead temperature for soldering during 10 s | | 260 | °C |

Notes:

(1)For a surge greater than the maximum values, the diode will fail in short-circuit.

Table 2: Thermal resistance

| Symbol | Parameter | Value | Unit |
|----------------------|--|-------|------|
| R _{th(j-l)} | Junction to leads | 20 | °C/W |
| R _{th(j-a)} | Junction to ambient on printed circuit on recommended pad layout | 100 | °C/W |

Figure 1: Electrical characteristics - parameter definitions




Figure 2: Pulse definition for electrical characteristics




Table 3: Electrical characteristics parameter values ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

| Order code | I_{RM} max at V_{RM} | | | V_{BR} at $I_R^{(1)}$ | | | | 10 / 1000 μs | | | 8 / 20 μs | | | $\alpha T^{(2)}$ |
|-------------|--------------------------|--------------------------|------|-------------------------|------|------|----|-------------------------|------------------|----------|----------------------|----------|----------|--|
| | 25 $^{\circ}\text{C}$ | 85 $^{\circ}\text{C}$ | | Min. | Typ. | Max. | | V_{CL} | I_{PP} | R_D | V_{CL} | I_{PP} | R_D | |
| | | | | | | | | Max. | | Max. | Max. | | | Max. |
| | μA | | V | V | | | mA | V ⁽³⁾ | A ⁽⁴⁾ | Ω | V | A | Ω | 10 ⁻⁴ $^{\circ}\text{C}$ |
| SM6T6V8A/CA | 20 | 50 | 5.8 | 6.45 | 6.8 | 7.14 | 10 | 10.5 | 57 | 0.059 | 14.4 | 275 | 0.027 | 5.7 |
| SM6T7V5A/CA | 20 | 50 | 6.4 | 7.13 | 7.5 | 7.88 | 10 | 11.3 | 53 | 0.065 | 15.2 | 266 | 0.027 | 6.1 |
| SM6T10A/CA | 20 | 50 | 8.55 | 9.5 | 10.0 | 10.5 | 1 | 14.5 | 41 | 0.098 | 18.6 | 215 | 0.038 | 7.3 |
| SM6T12A/CA | 0.2 | 1 | 10.2 | 11.4 | 12 | 12.6 | 1 | 16.7 | 36 | 0.114 | 21.7 | 184 | 0.049 | 7.8 |
| SM6T15A/CA | 0.2 | 1 | 12.8 | 14.3 | 15 | 15.8 | 1 | 21.2 | 28 | 0.193 | 27.2 | 147 | 0.078 | 8.4 |
| SM6T18A/CA | 0.2 | 1 | 15.3 | 17.1 | 18 | 18.9 | 1 | 25.2 | 24 | 0.263 | 32.5 | 123 | 0.111 | 8.8 |
| SM6T22A/CA | 0.2 | 1 | 18.8 | 20.9 | 22 | 23.1 | 1 | 30.6 | 20 | 0.375 | 39.3 | 102 | 0.159 | 9.2 |
| SM6T24A/CA | 0.2 | 1 | 20.5 | 22.8 | 24 | 25.2 | 1 | 33.2 | 18 | 0.444 | 42.8 | 93 | 0.189 | 9.4 |
| SM6T27A/CA | 0.2 | 1 | 23.1 | 25.7 | 27 | 28.4 | 1 | 37.5 | 16 | 0.569 | 48.3 | 83 | 0.240 | 9.6 |
| SM6T30A/CA | 0.2 | 1 | 25.6 | 28.5 | 30 | 31.5 | 1 | 41.5 | 14.5 | 0.690 | 53.5 | 75 | 0.293 | 9.7 |
| SM6T33A/CA | 0.2 | 1 | 28.2 | 31.4 | 33 | 34.7 | 1 | 45.7 | 13.1 | 0.840 | 59.0 | 68 | 0.357 | 9.8 |
| SM6T36A/CA | 0.2 | 1 | 30.8 | 34.2 | 36 | 37.8 | 1 | 49.9 | 12 | 1.01 | 64.3 | 62 | 0.427 | 9.9 |
| SM6T39A/CA | 0.2 | 1 | 33.3 | 37.1 | 39 | 41.0 | 1 | 53.9 | 11.1 | 1.16 | 69.7 | 57 | 0.504 | 10.0 |
| SM6T56A/CA | 0.2 | 1 | 47.6 | 53.2 | 56 | 58.8 | 1 | 76.6 | 7.8 | 2.28 | 100 | 40 | 1.030 | 10.0 |
| SM6T68A/CA | 0.2 | 1 | 58.1 | 64.6 | 68 | 71.4 | 1 | 92 | 6.5 | 3.17 | 121 | 33 | 1.503 | 10.4 |
| SM6T75A/CA | 0.2 | 1 | 64.1 | 71.3 | 75 | 78.8 | 1 | 103 | 5.8 | 4.17 | 134 | 30 | 1.84 | 10.5 |
| SM6T100A/CA | 0.2 | 1 | 85.5 | 95.0 | 100 | 105 | 1 | 137 | 4.4 | 7.27 | 178 | 22.5 | 3.24 | 10.6 |
| SM6T150A/CA | 0.2 | 1 | 128 | 143 | 150 | 158 | 1 | 207 | 2.9 | 16.9 | 265 | 15 | 7.13 | 10.8 |
| SM6T200A/CA | 0.2 | 1 | 171 | 190 | 200 | 210 | 1 | 274 | 2.2 | 29.1 | 353 | 11.3 | 12.7 | 10.8 |
| SM6T220A/CA | 0.2 | 1 | 188 | 209 | 220 | 231 | 1 | 328 | 2 | 48.5 | 388 | 10.3 | 15.2 | 10.8 |

Notes:⁽¹⁾Pulse test: $t_p < 50\text{ ms}$ ⁽²⁾To calculate V_{BR} or V_{CL} versus junction temperature, use the following formulas:

- V_{BR} at $T_J = V_{BR}$ at $25\text{ }^{\circ}\text{C} \times (1 + \alpha T \times (T_J - 25))$ V_{CL} at $T_J = V_{CL}$ at $25\text{ }^{\circ}\text{C} \times (1 + \alpha T \times (T_J - 25))$

⁽³⁾To calculate maximum clamping voltage at other surge level, use the following formula:

- $V_{CLmax} = V_{BRmax} + R_D \times I_{PPappli}$ where $I_{PPappli}$ is the surge current in the application

⁽⁴⁾Surge capability given for both directions for unidirectional and bidirectional types.

1.1 Characteristics (curves)






Figure 6: Capacitance versus reverse applied voltage for unidirectional types (typical values)




Figure 7: Capacitance versus reverse applied voltage for bidirectional types (typical values)




Figure 8: Peak forward voltage drop versus peak forward current (typical values)




Figure 9: Relative variation of thermal impedance junction to ambient versus pulse duration




Figure 10: Thermal resistance junction to ambient versus copper surface under each lead





Figure 11: Leakage current versus junction temperature (typical values)



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

- Case: JEDEC DO214-AA molded plastic over planar junction
- Terminals: solder plated, solderable per MIL-STD-750, method 2026
- Polarity: for unidirectional types the band indicates cathode.
- Flammability: epoxy is rated UL94V-0
- RoHS package

2.1 SMB package information

Figure 12: SMB package outline





Table 4: SMB package mechanical data


| Ref. | Dimensions | | | |
|------|-------------|------|--------|--------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A1 | 1.90 | 2.45 | 0.0748 | 0.0965 |
| A2 | 0.05 | 0.20 | 0.0020 | 0.0079 |
| b | 1.95 | 2.20 | 0.0768 | 0.0867 |
| c | 0.15 | 0.40 | 0.0059 | 0.0157 |
| D | 3.30 | 3.95 | 0.1299 | 0.1556 |
| E | 5.10 | 5.60 | 0.2008 | 0.2205 |
| E1 | 4.05 | 4.60 | 0.1594 | 0.1811 |
| L | 0.75 | 1.50 | 0.0295 | 0.0591 |

Figure 13: SMB recommended footprint



Note: Marking layout can vary according to assembly location.

Figure 14: Marking layout



3 Ordering information

Figure 15: Ordering information scheme




Table 5: Ordering information

| Order code | Marking | Package | Weight | Base qty. | Delivery mode |
|----------------------------|--|---------|--------|-----------|---------------|
| SM6TxxxA/CA ⁽¹⁾ | See Table 6: "Marking" . | SMB | 0.11 g | 2500 | Tape and reel |

Notes:

⁽¹⁾Where xxx is nominal value of V_{BR} and A or CA indicates unidirectional or bidirectional version. See [Table 3: "Electrical characteristics parameter values \(T_{amb} = 25 °C, unless otherwise specified\)"](#) for list of available devices and their order codes.

Table 6: Marking

| Order code | Marking | Order code | Marking |
|------------|---------|------------|---------|
| SM6T6V8A | DE | SM6T6V8CA | LE |
| SM6T7V5A | DG | SM6T7V5CA | LG |
| SM6T10A | DP | SM6T10CA | LP |
| SM6T12A | DT | SM6T12CA | LT |
| SM6T15A | DX | SM6T15CA | LX |
| SM6T18A | EE | SM6T18CA | ME |
| SM6T22A | EK | SM6T22CA | MK |
| SM6T24A | EM | SM6T24CA | MM |
| SM6T27A | EP | SM6T27CA | MP |
| SM6T30A | ER | SM6T30CA | MR |
| SM6T33A | ET | SM6T33CA | MT |
| SM6T36A | EV | SM6T36CA | MV |
| SM6T39A | EX | SM6T39CA | MX |
| SM6T56A | FL | SM6T56CA | NL |
| SM6T68A | FQ | SM6T68CA | NQ |
| SM6T75A | FS | SM6T75CA | NS |
| SM6T100A | FY | SM6T100CA | NY |
| SM6T150A | GL | SM6T150CA | OL |
| SM6T200A | GU | SM6T200CA | OU |
| SM6T220A | GW | SM6T220CA | OW |

4 Revision history

Table 7: Document revision history

| Date | Revision | Changes |
|-------------|----------|--|
| Aug-2001 | 4A | Previous update. |
| 15-Sep-2004 | 5 | 1. Types table parameters on page 2: I_{RM} @ $T_j = 85\text{ }^\circ\text{C}$ condition added 2. IRM max values changed |
| 26-Mar-2009 | 6 | Reformatted to current standard. SMB dimensions and footprint updated. Maximum junction temperature replaced with operating junction temperature range in Table 1. |
| 25-May-2009 | 7 | Reformatted to current standard. Added standards compliance information on page 1. Added device SM6T56 to Table 3. Updated all characteristic curves. |
| 17-Sep-2009 | 8 | Document updated for low leakage current. |
| 20-Oct-2009 | 9 | Updated Figure 13. |
| 10-Jan-2018 | 10 | Updated Table 3: "Electrical characteristics parameter values ($T_{amb} = 25\text{ }^\circ\text{C}$, unless otherwise specified)" . |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9