



## Metal Oxide Resistors, Special Purpose, High Voltage



#### **FEATURES**

Low TCR:  $\pm$  200 ppm/°C standard;  $\pm$  100 ppm/°C,  $\pm$  50 ppm/°C available Tolerance:  $\pm$  1 %;  $\pm$  2 %;  $\pm$  5 %;  $\pm$  10 %

High Voltage (up to 45 kV)
For oil bath or open air operation

Matched sets available

Special testing available upon request Material categorization:
For definitions of compliance please www.vishay.com/doc?99912 SEE COMPLIANT

Note

Lead (Pb)-containing terminations are not RoHS-compliant. Exemptions may apply.


O I AILD	ARD ELECTR		WER RAT		MAXIMUM		1		
GLOBAL MODEL	HISTORICAL MODEL	P <sub>25 °C</sub> (1)	P <sub>70°C</sub> (1)	P <sub>125 °C</sub> (1)	WORKING VOLTAGE (2) V	RESISTANCE RANGE <sup>(3)</sup> Ω	TOLERANCE ± %	TEMPERATURE COEFFICIENT ± ppm/°C	
ROX050	ROX-1/2	2.0	1.4	1.0	2K	1M to 100M	1, 2, 5, 10	50	
						1K to 100M	1, 2, 5, 10	100	
						1K to 1G	1, 2, 5, 10	200	
ROX075	ROX-3/4	3.0	2.16	1.5	5K -	1M to 100M	1, 2, 5, 10	50	
						1K to 500M	1, 2, 5, 10	100	
HUXU/3						1K to 3G	1, 2, 5, 10	200	
						100 to 1M	1, 2, 5, 10	Non-inductive (4)	
	ROX-1	4.0	2.88	2.0	7.5K	1M to 100M	1, 2, 5, 10	50	
DOV400						1K to 500M	1, 2, 5, 10	100	
ROX100						1K to 3G	1, 2, 5, 10	200	
						100 to 1M	1, 2, 5, 10	Non-inductive (4)	
ROX150	ROX-1-1/2	5.0	3.6	2.5	11K	1M to 100M	1, 2, 5, 10	50	
						1K to 500M	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						100 to 1M	1, 2, 5, 10	Non-inductive (4)	
	ROX-2	6.0	4.32	3.0	15K	1M to 500M	1, 2, 5, 10	50	
ROX200						1K to 1G	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						100 to 1M	1, 2, 5, 10	Non-inductive (4)	
ROX300	ROX-3	10.0	7.2	5.0	22.5K	1M to 500M	1, 2, 5, 10	50	
						1K to 1G	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						400 to 10M	1, 2, 5, 10	Non-inductive (4)	
						1M to 500M	1, 2, 5, 10	50	
ROX400	ROX-4	12.0	8.64	6.0	30K	1K to 1G	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						500 to 10M	1, 2, 5, 10	Non-inductive (4)	
ROX500	ROX-5	16.0	11.52	8.0	37.5K	1M to 500M	1, 2, 5, 10	50	
						1K to 1G	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						500 to 10M	1, 2, 5, 10	Non-inductive (4)	
ROX600	ROX-6	20.0	14.4	10.0	45K -	1M to 500M	1, 2, 5, 10	50	
						1K to 1G	1, 2, 5, 10	100	
						1K to 3G	1, 2, 5, 10	200	
						500 to 10M	1, 2, 5, 10	Non-inductive (4)	

#### **Notes**

- All resistance values are calibrated at 100 V<sub>DC</sub>. Calibration at other voltages available.
- All resistance values are calibrated at 100 V<sub>DC</sub>. Calibration at other voltages available.  $\pm$  1 % not available above 1 G $\Omega$  Part marking: Print marked Dale, model, value, tolerance, temperature coefficient, date code Increase wattage by 40 % for 0.040" (1.02 mm) diameter leads Continuous working voltage shall be  $\sqrt{P \times R}$  or maximum working voltage, whichever is less. For resistance values above and below those listed please contact us Non-inductive  $\pm$  200 ppm/°C TCR only


TECHNICAL SPECIFICATIONS										
PARAMETER	UNIT	ROX050	ROX075	ROX100	ROX150	ROX200	ROX300	ROX400	ROX500	ROX600
Insulation Resistance	Ω	≥ 10 <sup>11</sup>								
Category Temperature Range	°C	Epoxy coated = - 55/+ 180; Silicone coated = - 55/+ 230								






#### **Notes**

- (1) Some packaging codes are model specific.
- For additional information on packaging, refer to the Through-Hole Resistor Packaging document (www.vishay.com/doc?31544).





MECHANICAL SPECIFICATIONS				
Terminal Strength	10 pound pull test			
Solderability	Continuous satisfactory coverage when tested in accordance with MIL-STD-202, Method 208			


MATERIAL SPECIFICATIONS					
Element	High temperature fired cermet film				
Core	High purity 96 % alumina, tubular or solid				
Coating	Blue flame-retardant epoxy on ROX050 thru ROX200. Black flameproof silicone on ROX300 thru ROX600				
Termination	Standard lead material is solder-coated copper; solderable and weldable. 0.032" (0.813 mm) style P 0.040" (1.02 mm) available				





www.vishay.com

Vishay Dale





## **Legal Disclaimer Notice**

Vishay

### **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## **Material Category Policy**

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Revision: 02-Oct-12 Document Number: 91000

### **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

#### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9