



Part Number: 1033A

300V, (1 pr) 20 AWG (7x28) BC, PVC/PVC, Foil Shld, PLTC-ER, CMG

Product Description

One 20 AWG pair stranded (7x28) bare copper conductors, twisted pairs, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Product Specifications

AG.Filter Attributes

Total Number of Conductors:	2
-----------------------------	---

Cabling1

Lay Direction@Cabling1:	Left Hand
-------------------------	-----------

CCB-Sub-Part Number

Print Legend:	LEGEND: BELDEN 1033A E34972 1PR20 SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES OR AWM 2464 80C 300V OR C(UL) CMG —FT4 IEEE 1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
---------------	---

Technical Specifications

AG_0401

UL Flammability:	UL1685 FT4 Loading
------------------	--------------------

APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Applicable Patents

Patent:	http://www.belden.com/p
---------	---

Bend Radius

Min Bend Radius/Minor Axis:	2.1 in
-----------------------------	--------

CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
--------------------------	-------------------------------

EU CE Mark:	Yes
-------------	-----

North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

CEC/C(UL) Specification:	CMG
--------------------------	-----

NEC/(UL) Specification:	CMG, ITC, PLTC
-------------------------	----------------

UL AWM Style:	UL Style 2464 (300 V 80°C)
---------------	----------------------------

Safety

IEEE Flammability:	1202
--------------------	------

C(UL) Flammability:	FT4
---------------------	-----

Use

Suitability - Outdoor:	Yes
------------------------	-----

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Max Recommended Pulling Tension:	16 lbs
----------------------------------	--------

Suitability - Indoor:	Yes
-----------------------	-----

Conductor DCR:

Nominal Conductor DCR

Nominal Outer Shield DCR

9.5 Ohm/1000ft	38 Ohm/1000ft
----------------	---------------

Color Chart 1:

Number	Color
1	Black & White

Voltage:

UL Voltage Rating
300 V RMS (PLTC V
CMG)
150 V RMS (ITC)

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
30 pF/ft	55 pF/ft

Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.015 in

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord	
PVC - Polyvinyl Chloride		0.21 in	0.037 in	Yes

Conductor:

AWG	Stranding	Material	No. of Pairs
20	7x28	BC - Bare Copper	1

Outersheild 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D		
Tape	Aluminum Foil-Polyester Tape			Beldfoil®	100 %	TC - Tinned Copper	22	7x30 mm

Product Variants

Part Number	Color	Put-Up Type	Length
1033A			
1033A	BLACK	Reel	3048 m
1033A 01010000	BLACK	Reel	10000 ft
1033A			
1033A	BLACK	Reel	305 m
1033A 0101000	BLACK	Reel	1000 ft
1033A			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9