



Product: [9967](#)

Electronic, 3 C #22 Str TC, PVC-NYL Ins, OA TC Brd, PVC Jkt

[Request Sample](#)

Product Description

Electronic, 3 Conductor 22AWG (19x34) Tinned Copper, PVC-NYL Insulation, Overall Tinned Copper Braid(90%) Shield, PVC Outer Jacket

Technical Specifications

Product Overview

|                        |                                                                                   |
|------------------------|-----------------------------------------------------------------------------------|
| Suitable Applications: | MIL-W-16878 (Type B) Spec; up to 600V analog signals ; up to 600V voltage control |
|------------------------|-----------------------------------------------------------------------------------|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material           | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 22  | 19x34     | TC - Tinned Copper | 3                 |

|                  |   |
|------------------|---|
| Conductor Count: | 3 |
|------------------|---|

Insulation

| Layer | Material                 | Nominal Wall Thickness |
|-------|--------------------------|------------------------|
| 1     | PVC - Polyvinyl Chloride | 0.01 in                |
| 2     | Nylon                    | 0.003 in               |

Color Chart

| Number | Color |
|--------|-------|
| 1      | White |
| 2      | Black |
| 3      | Red   |

Outer Shield Material

| Type  | Material           | Coverage [%] |
|-------|--------------------|--------------|
| Braid | TC - Tinned Copper | 90 %         |

Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.184 in         | 0.02 in                |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 15.3 Ohm/1000ft       | 5.3 Ohm/1000ft           |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 45 pF/ft                                | 88 pF/ft                                                |

Inductance

| Nominal Inductance |
|--------------------|
| 0.144 µH/ft        |

Current

| Max. Recommended Current [A]  |
|-------------------------------|
| 2.8 Amps per conductor @ 25°C |

Voltage

| Non-UL Voltage Rating |
|-----------------------|
| 600 V RMS             |

|                                   |                                |
|-----------------------------------|--------------------------------|
| Electrical Characteristics Notes: | 500 megohms/1000 ft. @ 500 VDC |
|-----------------------------------|--------------------------------|

Temperature Range

|                       |                 |
|-----------------------|-----------------|
| UL Temp Rating:       | 105°C           |
| Operating Temp Range: | -20°C To +105°C |

Mechanical Characteristics

|                                  |               |
|----------------------------------|---------------|
| Bulk Cable Weight:               | 24 lbs/1000ft |
| Max Recommended Pulling Tension: | 28.5 lbs      |
| Min Bend Radius/Minor Axis:      | 2 in          |

Standards

|                         |                                       |
|-------------------------|---------------------------------------|
| Military Specification: | MIL-W-16878E/17 (insulated conductor) |
| Other Specification:    | NEMA HP3                              |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #       | Color | UPC          |
|--------------|-------|--------------|
| 9967 009100  | White | 612825265344 |
| 9967 0091000 | White | 612825265351 |
| 9967 009500  | White | 612825265368 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.292 Revision Date: 04-28-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9