

**LSW SERIES**

**105°C Standard, Screw Terminal Type**

◆ **FEATURES**

- Load Life : 105°C 3000 hours.
- RoHS compliance.

◆ **SPECIFICATIONS**

| Items                               | Characteristics                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|--|-------------|----|----|----|----|----|--------------------|-----------------------------------|--------------------|--------------------------------------------|-----------------|------------------------------------|----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|------|-----|-----|-----|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|---------|----|----|----|----|----|----|-----|------|-----|-----|-----|----|-----|-----|------|-----|-----|-----|------|-----|------|------|------|---------|------|------|-----|-----|-----|---------|-----|-----|------|------|------|-----------------|--|
| Category Temperature Range          | -40~+105℃                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |      |      |      |      |  | -25~+105℃   |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Rated Voltage Range                 | 10~100V.DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |      |      |      |      |  | 160~400V.DC |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Capacitance Tolerance               | ±20% (20℃, 120Hz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Dissipation Factor(MAX)<br>(tan δ ) | <table><tr><td>WV \ φD</td><td>36</td><td>51</td><td>64</td><td>77</td><td>90</td></tr><tr><td>10</td><td>0.75</td><td>1.0</td><td>1.3</td><td>1.5</td><td>1.5</td></tr><tr><td>16</td><td>0.6</td><td>0.7</td><td>0.8</td><td>1.0</td><td>1.0</td></tr><tr><td>25</td><td>0.4</td><td>0.5</td><td>0.7</td><td>0.8</td><td>0.8</td></tr><tr><td>35</td><td>0.3</td><td>0.5</td><td>0.6</td><td>0.7</td><td>0.7</td></tr><tr><td>50</td><td>0.25</td><td>0.3</td><td>0.5</td><td>0.6</td><td>0.6</td></tr></table> |      |      |      |      |  | WV \ φD     | 36 | 51 | 64 | 77 | 90 | 10                 | 0.75                              | 1.0                | 1.3                                        | 1.5             | 1.5                                | 16 | 0.6 | 0.7 | 0.8 | 1.0 | 1.0 | 25 | 0.4 | 0.5 | 0.7 | 0.8 | 0.8 | 35 | 0.3 | 0.5 | 0.6 | 0.7 | 0.7 | 50 | 0.25 | 0.3 | 0.5 | 0.6 | 0.6 | <table><tr><td>WV \ φD</td><td>36</td><td>51</td><td>64</td><td>77</td><td>90</td></tr><tr><td>63</td><td>0.2</td><td>0.25</td><td>0.3</td><td>0.4</td><td>0.4</td></tr><tr><td>80</td><td>0.2</td><td>0.2</td><td>0.25</td><td>0.3</td><td>0.3</td></tr><tr><td>100</td><td>0.15</td><td>0.2</td><td>0.25</td><td>0.25</td><td>0.25</td></tr><tr><td>160~250</td><td>0.15</td><td>0.15</td><td>0.2</td><td>0.2</td><td>0.2</td></tr><tr><td>315~400</td><td>0.2</td><td>0.2</td><td>0.25</td><td>0.25</td><td>0.25</td></tr></table> |  |  |  |  |  | WV \ φD | 36 | 51 | 64 | 77 | 90 | 63 | 0.2 | 0.25 | 0.3 | 0.4 | 0.4 | 80 | 0.2 | 0.2 | 0.25 | 0.3 | 0.3 | 100 | 0.15 | 0.2 | 0.25 | 0.25 | 0.25 | 160~250 | 0.15 | 0.15 | 0.2 | 0.2 | 0.2 | 315~400 | 0.2 | 0.2 | 0.25 | 0.25 | 0.25 | (20℃,<br>120Hz) |  |
| WV \ φD                             | 36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 51   | 64   | 77   | 90   |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 10                                  | 0.75                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1.0  | 1.3  | 1.5  | 1.5  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 16                                  | 0.6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.7  | 0.8  | 1.0  | 1.0  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 25                                  | 0.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.5  | 0.7  | 0.8  | 0.8  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 35                                  | 0.3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.5  | 0.6  | 0.7  | 0.7  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 50                                  | 0.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0.3  | 0.5  | 0.6  | 0.6  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| WV \ φD                             | 36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 51   | 64   | 77   | 90   |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 63                                  | 0.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.25 | 0.3  | 0.4  | 0.4  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 80                                  | 0.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.2  | 0.25 | 0.3  | 0.3  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 100                                 | 0.15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0.2  | 0.25 | 0.25 | 0.25 |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 160~250                             | 0.15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0.15 | 0.2  | 0.2  | 0.2  |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| 315~400                             | 0.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0.2  | 0.25 | 0.25 | 0.25 |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Leakage Current(MAX)                | I=0.02CV or 5mA whichever is smaller. (After 5 minutes application of rated voltage)<br>I=Leakage Current( μ A)                      V=Rated Voltage(V)                      C=Rated Capacitance( μ F)                                                                                                                                                                                                                                                                                                            |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Endurance                           | After applying rated voltage with rated ripple current for 3000hrs at 105℃, the capacitors shall meet the following requirements. <table><tr><td>Capacitance Change</td><td>Within ±15% of the initial value.</td></tr><tr><td>Dissipation Factor</td><td>Not more than 175% of the specified value.</td></tr><tr><td>Leakage Current</td><td>Not more than the specified value.</td></tr></table>                                                                                                                |      |      |      |      |  |             |    |    |    |    |    | Capacitance Change | Within ±15% of the initial value. | Dissipation Factor | Not more than 175% of the specified value. | Leakage Current | Not more than the specified value. |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Capacitance Change                  | Within ±15% of the initial value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Dissipation Factor                  | Not more than 175% of the specified value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Leakage Current                     | Not more than the specified value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Shelf Life                          | After storage for 500 hours with no voltage applied at 105℃, the capacitors shall be subjected to the voltage treatment in JIS C 5102 and shall be meet the following requirements. <table><tr><td>Capacitance Change</td><td>Within ±15% of the initial value.</td></tr><tr><td>Dissipation Factor</td><td>Not more than 150% of the specified value.</td></tr><tr><td>Leakage Current</td><td>Not more than the specified value.</td></tr></table>                                                              |      |      |      |      |  |             |    |    |    |    |    | Capacitance Change | Within ±15% of the initial value. | Dissipation Factor | Not more than 150% of the specified value. | Leakage Current | Not more than the specified value. |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Capacitance Change                  | Within ±15% of the initial value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Dissipation Factor                  | Not more than 150% of the specified value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |
| Leakage Current                     | Not more than the specified value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |      |      |      |      |  |             |    |    |    |    |    |                    |                                   |                    |                                            |                 |                                    |    |     |     |     |     |     |    |     |     |     |     |     |    |     |     |     |     |     |    |      |     |     |     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  |  |  |  |         |    |    |    |    |    |    |     |      |     |     |     |    |     |     |      |     |     |     |      |     |      |      |      |         |      |      |     |     |     |         |     |     |      |      |      |                 |  |

◆ **MULTIPLIER FOR RIPPLE CURRENT**

Frequency coefficient

| 周波数 (Hz) Frequency | 60(50) | 120  | 400  | 1k   | 10k≤ |
|--------------------|--------|------|------|------|------|
| 10~50WV            | 0.80   | 1.00 | 1.03 | 1.05 | 1.08 |
| 63~100WV           | 0.80   | 1.00 | 1.05 | 1.07 | 1.10 |
| 160~400WV          | 0.80   | 1.00 | 1.10 | 1.13 | 1.18 |

◆ **PART NUMBER**

LSW         D×L  
 Rated Voltage Series Rated Capacitance Capacitance Tolerance Option Case Size

◆ **DIMENSIONS**

(mm)

PERFORMANCE

$\phi 36$

Technical drawing of a cylindrical component for diameter 36. The side view shows a diameter of  $D \pm 2$  and a length of  $L \pm 3$ . The front view shows a circular face with a central vent, four mounting points (W1, W2, W3, W4), and a central screw terminal (W5). The dimensions are:  $W1 \pm 1$ ,  $W2 \pm 1$ ,  $W3$ ,  $W4$ ,  $W5$ , and  $P-1$ . The component is labeled with "Mounting Clamp", "Plate", "Sleeve", "Case", "Screw Terminal", "Bolt", "Vent", and "M5 P=0.8Bolt".

$\phi 51 \sim \phi 90$

Technical drawing of a cylindrical component for diameters 51 to 90. The side view shows a diameter of  $D \pm 2$  and a length of  $L \pm 3$ . The front view shows a circular face with a central vent, four mounting points (W1, W2, W3, W4), and a central screw terminal (W5). The dimensions are:  $W1 \pm 1$ ,  $W2 \pm 1$ ,  $W3$ ,  $W4$ ,  $W5$ , and  $P-1$ . The component is labeled with "Mounting Clamp", "Plate", "Sleeve", "Case", "Screw Terminal", "Bolt", "Vent", and "M5 P=0.8Bolt".

| $\phi D$ | W1   | W2   | W3  | W4 | W5 | P    |
|----------|------|------|-----|----|----|------|
| 36       | 24.0 | 30.0 | 3.5 | 7  | 10 | 12.7 |
| 51       | 32.5 | 37.5 | 4.5 | 6  | 12 | 21.8 |
| 64       | 38.0 | 43.0 | 4.5 | 8  | 14 | 28.2 |
| 77       | 43.5 | 49.0 | 4.5 | 7  | 14 | 31.4 |
| 90       | 50.8 | 56.0 | 4.5 | 8  | 16 | 31.4 |

※Please notice the following conditions for use.

- (1) Maximum screw terminal tightening torque; 33kg/Ǝcm or less.
- (2) Maximum ripple current shall be 50Arms or less because of the rated current of M5 screw terminal.

### ◆STANDARD SIZE, RATED RIPPLE CURRENT

| WV<br>Cap(μF) | 10V         | 16V         | 25V         | 35V         | 50V         | 63V         | 80V         |
|---------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 3300          |             |             |             |             |             |             | 36×50 3.0   |
| 3900          |             |             |             |             |             |             | 36×63 3.3   |
| 4700          |             |             |             |             |             | 36×50 3.2   | 36×83 3.6   |
| 5600          |             |             |             |             |             | 36×63 3.5   | 36×83 3.9   |
| 6800          |             |             |             | 36×50 2.5   | 36×50 3.6   | 36×63 3.8   | 36×83 4.3   |
| 8200          |             |             |             | 36×50 2.8   | 36×63 3.9   | 36×83 4.3   | 36×98 5.1   |
| 10000         |             |             |             | 36×50 3.8   | 36×83 4.2   | 36×83 4.7   | 36×118 5.8  |
| 12000         |             |             |             | 36×63 4.3   | 36×83 5.0   | 36×98 5.6   | 51×83 7.0   |
| 15000         |             |             | 36×50 4.2   | 36×83 4.7   | 36×98 5.5   | 36×118 6.4  | 51×83 7.6   |
| 18000         |             |             | 36×63 4.6   | 36×83 5.1   | 36×98 5.7   | 51×83 7.5   | 51×98 7.7   |
| 22000         |             | 36×50 4.0   | 36×83 5.2   | 36×98 6.6   | 36×118 7.5  | 51×83 7.5   | 51×118 9.0  |
| 27000         | 36×50 4.4   | 36×63 5.0   | 36×83 5.4   | 36×118 6.7  | 51×83 7.5   | 51×98 8.7   | 64×99 10.1  |
| 33000         | 36×63 5.5   | 36×83 5.2   | 36×98 6.5   | 51×83 7.1   | 51×98 9.3   | 51×118 10.3 | 64×119 11.6 |
| 39000         | 36×63 6.0   | 36×83 5.8   | 36×98 7.5   | 51×83 8.4   | 51×98 9.4   | 64×99 11.2  | 64×139 13.5 |
| 47000         | 36×83 6.6   | 36×98 6.8   | 36×118 8.9  | 51×98 9.9   | 51×118 11.7 | 64×119 12.9 | 77×101 15.8 |
| 56000         | 36×83 7.5   | 36×98 6.9   | 51×83 10.0  | 51×98 10.3  | 64×99 12.4  | 64×139 15.2 | 77×121 17.0 |
| 68000         | 36×98 7.6   | 36×118 8.4  | 51×98 10.7  | 51×118 11.4 | 64×119 15.1 | 77×101 16.0 | 77×141 20.4 |
| 82000         | 36×118 9.0  | 51×83 8.4   | 51×98 12.0  | 64×99 12.5  | 77×101 15.5 | 77×121 17.7 | 77×151 21.5 |
| 100000        | 51×83 10.2  | 51×98 11.3  | 51×118 13.1 | 64×119 15.5 | 77×101 16.3 | 77×141 21.5 | 90×151 22.3 |
| 120000        | 51×83 11.0  | 51×98 11.4  | 64×99 13.7  | 77×101 15.5 | 77×121 19.1 | 90×141 22.4 |             |
| 150000        | 51×98 13.4  | 51×118 12.5 | 64×119 16.4 | 77×121 17.9 | 77×141 23.4 |             |             |
| 180000        | 51×118 14.0 | 64×99 14.2  | 77×101 16.7 | 77×141 20.0 | 90×141 23.7 |             |             |
| 220000        | 64×99 14.5  | 64×119 16.6 | 77×121 20.5 | 77×151 24.1 |             |             |             |
| 270000        | 64×119 16.0 | 77×101 17.5 | 77×141 21.3 | 90×141 26.5 |             |             |             |
| 330000        | 77×101 18.0 | 77×121 24.3 | 77×151 26.0 |             |             |             |             |
| 390000        | 77×101 19.5 | 77×141 25.2 | 90×141 27.2 |             |             |             |             |
| 470000        | 77×121 20.0 | 77×151 26.7 |             |             |             |             |             |
| 560000        | 77×141 24.1 | 90×141 29.1 |             |             |             |             |             |
| 680000        | 90×141 26.5 |             |             |             |             |             |             |

| WV<br>Cap(μF) | 100V        | 160V        | 200V        | 250V        | 315V       | 350V       | 400V       |
|---------------|-------------|-------------|-------------|-------------|------------|------------|------------|
| 220           |             |             |             |             |            | 36×50 0.9  | 36×50 1.0  |
| 270           |             |             |             |             | 36×50 1.0  | 36×50 1.0  | 36×63 1.0  |
| 330           |             |             |             |             | 36×50 1.2  | 36×63 1.2  | 36×63 1.2  |
| 390           |             |             |             |             | 36×63 1.3  | 36×83 1.3  | 36×83 1.4  |
| 470           |             |             |             | 36×50 1.3   | 36×83 1.5  | 36×83 1.5  | 36×98 1.5  |
| 560           |             |             | 36×50 1.4   | 36×63 1.6   | 36×83 1.6  | 36×98 1.7  | 36×98 1.7  |
| 680           |             |             | 36×50 1.5   | 36×83 1.7   | 36×98 1.9  | 36×98 1.9  | 51×83 2.3  |
| 820           |             | 36×50 1.4   | 36×83 1.9   | 36×83 1.9   | 36×118 2.2 | 36×118 2.1 | 51×98 2.4  |
| 1000          |             | 36×63 1.9   | 36×83 2.2   | 36×98 2.3   | 51×83 2.3  | 51×98 2.5  | 51×118 2.7 |
| 1200          |             | 36×83 2.3   | 36×83 2.3   | 36×98 2.4   | 51×98 2.7  | 51×98 2.7  | 51×118 3.0 |
| 1500          |             | 36×83 2.6   | 36×98 2.9   | 36×118 2.9  | 51×98 3.1  | 51×118 3.3 | 64×99 3.5  |
| 1800          |             | 36×83 2.6   | 36×98 2.9   | 36×118 3.0  | 51×118 3.6 | 64×99 3.8  | 64×119 3.6 |
| 2200          | 36×50 2.9   | 36×98 3.2   | 36×118 3.3  | 51×98 3.8   | 64×99 4.2  | 64×119 4.6 | 77×101 4.1 |
| 2700          | 36×63 3.4   | 36×118 3.2  | 51×83 3.8   | 51×118 4.5  | 64×119 4.3 | 77×101 4.6 | 77×121 4.8 |
| 3300          | 36×83 3.9   | 36×118 3.7  | 51×98 4.7   | 64×99 5.2   | 77×101 4.9 | 77×121 5.3 | 77×141 5.7 |
| 3900          | 36×83 4.2   | 51×98 4.3   | 51×118 5.4  | 64×119 5.2  | 77×121 5.8 | 77×141 6.2 | 90×141 6.7 |
| 4700          | 36×83 4.6   | 51×98 4.8   | 64×99 6.2   | 64×119 5.7  | 77×121 6.3 | 90×141 7.4 | 90×141 7.4 |
| 5600          | 36×98 4.9   | 51×118 5.5  | 64×99 6.3   | 77×101 6.4  | 77×141 7.3 | 90×141 8.1 |            |
| 6800          | 36×118 5.5  | 64×99 6.3   | 64×119 7.3  | 77×121 7.6  | 90×141 8.9 |            |            |
| 8200          | 51×83 6.2   | 64×119 7.1  | 77×101 8.5  | 77×141 8.3  |            |            |            |
| 10000         | 51×98 6.7   | 77×101 7.9  | 77×121 9.5  | 90×141 9.9  |            |            |            |
| 12000         | 51×98 7.3   | 77×121 9.0  | 77×141 10.5 | 90×141 10.8 |            |            |            |
| 15000         | 51×118 8.6  | 77×141 11.3 | 90×141 12.5 |             |            |            |            |
| 18000         | 64×99 8.9   | 90×141 13.0 | 90×141 13.3 |             |            |            |            |
| 22000         | 64×119 10.3 | 90×141 14.3 |             |             |            |            |            |
| 27000         | 64×139 12.1 |             |             |             |            |            |            |
| 33000         | 77×121 14.1 |             |             |             |            |            |            |
| 39000         | 77×141 16.5 |             |             |             |            |            |            |
| 47000         | 77×141 18.3 |             |             |             |            |            |            |
| 56000         | 90×141 19.2 |             |             |             |            |            |            |
| 68000         | 90×151 20.1 |             |             |             |            |            |            |

↑ Ripple Current (A r.m.s./120Hz, 105℃)  
↑ Case Size ϕ D×L(mm)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9