

# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Pre-assembled relay module with push-in connection, consisting of: relay base, relay retaining bracket, plug-in suppressor module, and power contact relay with test button and integrated status LED. Contact type: 2 PDTs. Input voltage: 230 V AC

## Key Commercial Data

|                                      |         |
|--------------------------------------|---------|
| Packing unit                         | 10 STK  |
| GTIN                                 |         |
| Weight per Piece (excluding packing) | 70.32 g |
| Weight per piece (including packing) | 70.32 g |
| Country of origin                    | Germany |

## Technical data

### Note

|                         |   |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

### Dimensions

|        |       |
|--------|-------|
| Width  | 16 mm |
| Height | 93 mm |
| Depth  | 75 mm |

### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -40 °C ... 50 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

### Coil side

|   |                     |
|---|---------------------|
| Nominal input voltage $U_N$               | 230 V AC (50/60 Hz) |
| Input voltage range in reference to $U_N$ | see diagram         |
| Typical input current at $U_N$            | 4.5 mA              |
| Typical response time                     | 4 ms ... 12 ms      |
| Typical release time range                | 4 ms ... 20 ms      |
| Coil voltage                              | 230 V AC            |
| Protective circuit                        | Varistor            |
| Operating voltage display                 | Yellow LED          |

# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

## Technical data

### Contact side

|  |                           |
|--|---------------------------|
| Contact type   | 2 PDT                     |
| Contact material                                       | AgNi                      |
| Maximum switching voltage                              | 250 V AC/DC               |
| Minimum switching voltage                              | 12 V (at 10 mA)           |
| Min. switching current                                 | 10 mA (at 12 V)           |
| Maximum inrush current                                 | 16 A (20 ms, N/O contact) |
| Limiting continuous current                            | see diagram               |
| Interrupting rating (ohmic load) max.                  | 192 W (at 24 V DC)        |
|  | 62 W (at 48 V DC)         |
|  | 42 W (at 60 V DC)         |
|  | 55 W (at 110 V DC)        |
|  | 66 W (at 220 V DC)        |
|  | 2000 VA (for 250 V AC)    |
| Switching capacity min.                                | 120 mW                    |
| Switching capacity in acc. with DIN VDE 0660/IEC 60947 | 1 A (at 24 V, DC13)       |
|  | 1.5 A (at 24 V, AC15)     |
|  | 1.5 A (at 120 V, AC15)    |
|  | 1.5 A (at 240 V, AC15)    |

### Connection data input side

|                                  |  |
|----------------------------------|--|
| Connection name                  | Coil side  |
| Connection method                | Push-in connection   |
| Stripping length                 | 8 mm   |
| Conductor cross section solid    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                   |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                   |
|                                  | 0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve)       |
|                                  | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrules without plastic sleeve) |
| Conductor cross section AWG      | 26 ... 16  |

### Connection data output side

|                                  |  |
|----------------------------------|--|
| Connection name                  | Contact side   |
| Connection method                | Push-in connection   |
| Stripping length                 | 8 mm   |
| Conductor cross section solid    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                   |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                   |
|                                  | 0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve)       |
|                                  | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrules without plastic sleeve) |
| Conductor cross section AWG      | 26 ... 16  |

### General

|  |                                       |
|--|---------------------------------------|
| Test voltage relay winding/relay contact | 4 kV <sub>rms</sub> (50 Hz, 1 min.)   |
| Test voltage PDT/PDT                     | 2.5 kV <sub>rms</sub> (50 Hz, 1 min.) |

# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

## Technical data

### General

|                                |                                |
|--------------------------------|--------------------------------|
| Operating mode                 | 100% operating factor          |
| Degree of protection           | IP20 (Relay socket)            |
|                                | RT II (Relay)                  |
| Mechanical service life        | Approx. $5 \times 10^6$ cycles |
| Standards/regulations          | DIN EN 50178                   |
|                                | IEC 62103                      |
| Rated surge voltage/insulation | 6 kV/safe isolation            |
| Rated insulation voltage       | 250 V AC                       |
| Degree of pollution            | 2                              |
| Overvoltage category           | III                            |
| Mounting position              | any                            |
| Assembly instructions          | In rows with zero spacing      |

### Standards and Regulations

|                                |                     |
|--------------------------------|---------------------|
| Standards/regulations          | DIN EN 50178        |
|                                | IEC 62103           |
| Rated insulation voltage       | 250 V AC            |
| Rated surge voltage/insulation | 6 kV/safe isolation |
| Degree of pollution            | 2                   |
| Overvoltage category           | III                 |

## Articles in set

### Relay socket - RIF-1-BPT/2X21 - 2900931



RIF-1... relay base, for miniature power relay with 1 or 2 PDTs or solid-state relays of the same design, push-in connection, plug-in option for input/suppressor modules, for mounting on NS 35/7,5

### Single relay - REL-MR-230AC/21-21/MS - 2987972



Plug-in miniature relay, with power contact, 2 PDTs, test button, mechanical switch position indicator, status LED, coil voltage 230 V AC

# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

## Articles in set

Plug-in module - RIF-V-120-230 UC - 2900948



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 120 - 230 V AC/DC  $\pm 20\%$

Retaining bracket - RIF-RH-1-H - 2904468



Relay retaining bracket, with ejector function and holder for marking material, suitable for RIF-1 relay base, for 25 mm tall miniature power relay and solid-state relay

## Classifications

### eCl@ss


|            |          |
|------------|----------|
| eCl@ss 4.1 | 27371102 |
| eCl@ss 5.1 | 27371603 |
| eCl@ss 6.0 | 27371603 |
| eCl@ss 8.0 | 27371601 |
| eCl@ss 9.0 | 27371601 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000236 |
| ETIM 5.0 | EC001437 |


## Drawings

Circuit diagram



AC coils


Diagram



Operating voltage range


# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

Diagram




Interrupting rating

Diagram



Contact derating


Diagram



Service life reduction factor

# Relay Module - RIF-1-RPT-LV-230AC/2X21MS - 2905292

Diagram



Electrical service life

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9